

CAF

		CAF 024	CAF 030	CAF 036	CAF 042	
Indoor Units		AWSI-CAF024-N11	AWSI-CAF030-N11	AWSI-CAF036-N11	AWSI-CAF042-N11	
Outdoor Units 1-230V - 50 Hz		AWAU-YIF024-H11	AWAU-YIF030-H11	AWAU-YIF036-H11	AWAU-YIF042-H13	
Outdoor Units 3-400V - 50 Hz						
Cooling	Capacity	6,80	8,30	10,00	12,00	
	Power input	kW	2,62	2,90	3,60	4,80
	EER/Energy Label		2,59	2,86	2,77	2,50
	Outdoor temperature operating limits	°C	18 ⁷ 43° Dry bulb	18 ⁷ 43° Dry bulb	18 ⁷ 43° Dry bulb	18 ⁷ 43° Dry bulb
Heating	Capacity	7,50	8,80	11,00	14,00	
	Input power	kW	2,50	3,15	3,30	5,00
	COP/Energy Label		3,00	2,79	3,33	2,80
	Outdoor temperature operating limits	°C	-7 ⁷ 24° Dry bulb	-7 ⁷ 24° Dry bulb	-7 ⁷ 24° Dry bulb	-7 ⁷ 24° Dry bulb
Indoor unit	Sound pressure level to 1 m	dB(A)	43/45/47	48/49/51	48/51/53	48/51/53
	Sound power level	dB(A)	53/55/57	58/59/61	58/61/63	58/61/63
	Airflow	m ³ /h	1000/1080/1180	1170/1270/1400	1500/1570/1660	1500/1570/1650
	Dehumidification	l/h	2,35	2,7	2,9	4,3
	Dimensions (WxDxH)	mm	840x840x260	840x840x260	840x840x320	840x840x320
	Weight	kg	30	27	38	38
	Frame Dimensions 900x900	mm	950x950x60	950x950x60	950x950x60	950x950x60
	Weight	kg	6,5	6,5	6,5	6,5
	Part number		7SP042210	7SP042211	7SP042212	7SP042213
	Outdoor unit	Sound pressure level to 1 m	dB(A)	59	59	60
Sound power level		dB(A)	69	69	70	70
Airflow		m ³ /h	3200	4200	4000	6000
Compressor type			Rotary	Rotary	Rotary	Scroll
Dimensions (WxDxH)		mm	1018X412X700	980X427X790	1018X412X840	950x412x1250
Weight		kg	59	70	90	112
P. supply	Part number	7SP061781	7SP061782	7SP061783		
1~230V - 50 Hz	Price	€				
P. supply	Part number			7SP061784	7SP061785	
3~400V - 50 Hz	Price	€				
Power supply	Power supply side		Indoor & Outdoor	Indoor & Outdoor	Indoor & Outdoor	Indoor & Outdoor
	Power cable section	mm ²	3X1,0 - 3X4,0	3X1,0 - 3X6,0	3X1,0 - 3X6,0	
	Fuse rating	A	6 - 25	6 - 32	6 - 40	
	Electrical connections	mm³	2x0.75	2x0.75	2x0.75	
Power supply	Power supply side		Indoor & Outdoor	Indoor & Outdoor	Indoor & Outdoor	Indoor & Outdoor
	Power cable section	mm ²			3X1,0 - 5X2,5	3X1,0 - 5X2,5
	Fuse rating	A			6 - 16	6 - 20
	Electrical connections	mm³			2x0.75	2x0.75
Pipe Line	Suction pipe diameter	inches	5/8"	5/8"	3/4"	3/4"
	Liquid pipe diameter	inches	3/8"	3/8"	1/2"	1/2"
	Max length	m	30	30	50	50
	Max height	m	15	15	30	30