



## AELIA A / AELIA N

**PORTABLE UNITS**  
4 Cooling models  
From 2,6 kW to 4,17 kW



### PRODUCT ADVANTAGES

- Particularly suited for residential and light commercial air conditioning needs.
- Monobloc portable units (AELIA A 9/12) or split portable units (AELIA N 10/14).
- High dehumidification capacity.
- Low noise levels in the units.
- 3 fan speed.
- Easy installation (no specific requirements) and service.
- Easy access to the connecting hose to exhaust air out.
- Two options to control the unit by touch panel (built-in) or by wireless remote controller.
- Touch pad on the unit (AELIA A 9/12).
- On unit control and display panel (AELIA N 10/14).
- Infrared remote control with liquid crystal display (AELIA A)
- 24h timer programmer.
- Moving wheels for more convenience (AELIA A 9/12).



		<b>AELIA 9 A</b>	<b>AELIA 12 A</b>	<b>AELIA N 10 CDQC</b>	<b>AELIA N 14 CDQC</b>
<b>Cooling</b>	<b>Capacity</b>	<b>2.6</b>	<b>3.5</b>	<b>3.02</b>	<b>4.17</b>
	Power input	1.0	1.4	0.98	1.54
	EER/Energy Label	2.6 / A	2.5 / B	3.1 / A	2.7 / A
<b>Indoor unit</b>	Type	Monobloc	Monobloc	Split System	Split System
	Sound pressure level 1 m <sup>1</sup>	51/53/54	51/53/54	43/46/48	48/50/51
	Airflow <sup>2</sup>	420	450	503	433
	Dehumidification	1.6	2	1.25	1.80
	Dimensions (WxDxH)	510x425x830	510x425x830	470x360x800	470x360x800
	Weight	34	37	33	38
<b>Outdoor unit</b>	Compressor type	-	-	Rotary	Rotary
	Dimensions (WxDxH)	-	-	440x320x540	440x320x540
	Weight	-	-	17	17
	Linking pipes - Length	-	-	3	3
Max. height difference	-	-	1.6	1.6	
<b>Power supply 1-230V - 50Hz</b>	<b>Part number</b>	<b>7MB021050</b>	<b>7MB021051</b>	<b>7MB021032</b>	<b>7MB021042</b>
	<b>Price</b>	€			

<sup>1</sup>Data are relative to Low speed, Medium speed and High speed

<sup>2</sup>Data are relative to High speed