

Wall splits **ALPHA**



“One of the best solutions
for the residential sector
and the tertiary one”

Cooling only



Heat pump



Fluid R410A



ELECTRA
a i r c o n d i t i o n i n g



RC5 Remote control

Outdoor unit 7/9

4 Cooling only models : 2050 to 3550 W**4 Heat pump models : 2150 to 3630 W**

Sober, unobtrusive styling.

Easy installation and servicing.

High efficiency filtration.

Treated air sweeping.

Infrared remote control RC5.

Refrigerant R410A.

Heating mode operation down to outdoor temperatures of -15°C.

Labeled B.

T E C H N I C A L S P E C I F I C A T I O N S

ALPHA SERIES**ALPHA 7
ALPHA 7 RC****ALPHA 9
ALPHA 9 RC****ALPHA 12
ALPHA 12 RC****Cooling Capacity****kW****2,05****2,64****3,55**

Power input

kW

0,67

0,85

1,18

EER/Energy Label

3,06/B

3,11/B

3,01/B

Heating capacity**kW****2,15****2,90****3,63**

Power input

kW

0,63

0,93

1,13

COP/Energy Label

3,41/B

3,12/D

3,21/C

Indoor units

Airflow

m³/h

320/390

360/450

500/580

Acoustic pressure to 1 m (LS/HS)

dB(A)

30/37

35/40

36/42

Weight

kg

7

7

9

Dimensions (WxDxH)

mm

680x180x250

680x180x250

840x180x250

Outdoor units

Acoustic pressure to 1 m (LS/HS)

dB(A)

52/53

47/47

1,00

Compressor type

Rotary

Rotary

Rotary

Weight

kg

27,5

32

37

Dimensions (WxDxH)

mm

610x240x520

830x245x545

880x310x610

Linking specifications between units

Linking pipes (not supplied)

Power supply side

Indoor

Indoor

Indoor

Power cable section

mm²

3x1

3x1

3x1

Liquid pipe/Suction pipe diameter

inches

1/4"-3/8"

1/4"-3/8"

1/4"-3/8"

Max. length / Max. height

m

10/7

12/7

15/7

Electrical connections Ind./Out.

mm²

4x1

4x1

4x1

Electrical connections Ind./Out.

mm²

5x1

5x1

5x1

**ACE
Marketing**

1bis, avenue du 8 mai 1945

Saint-Quentin-en-Yvelines/F-78284 Guyancourt Cedex

Fax : +33 (0) 1 39 44 65 17-Tel : +33 (0) 1 39 44 78 00

ELECTRA
a i r c o n d i t i o n i n g


Y o u r d i s t r i b u t o r