



Monosplits Range

Wall mounted *ALPHA SP*




The Taylor - made comfort



ELECTRA

A i r C o n d i t i o n i n g

Alpha SP - 2 Heat Pump models : from 2 650 to 3 400W



Product advantages

- Sober, unobtrusive styling.
- Easy installation and servicing.
- High efficiency filtration.
- Treated air sweeping.
- Infrared remote control RC5.
- Refrigerant R410A.
- Heating mode operation down to outdoor temperatures of -10°C.

ALPHA SERIES

ASP 9 RC

ASP 12 RC

Cooling capacity	kW	2,55	3,3
Power Input	kW	0,89	1,16
EER		2,84/C	2,84/C
Operating limits outdoor temperature	°C	21°/46° Dry Bulb	

Heating Capacity	kW	2,65	3,4
Power Input	kW	0,82	1,05
COP / Label Energy		3,22/C	3,22/C
Operating limits outdoor temperature	°C	-10°/24° Dry Bulb	

Indoor units		ST ASP9	ST ASP12
Airflow (LS/HS)	m³/h	360/450	500/650
Acoustic pressure to 1m (LS/HS)	dB(A)	35/41	34/41
Dehumidification	l/h	0,9	1,1
Weight	kg	6	7
Dimensions (WxDxH)	mm	680x180x250	840x180x250

Part number	ESP022380	ESP022381
--------------------	------------------	------------------

Outdoor units			
Air flow	m³/h	1200	1200
Acoustic pressure to 1m (LS/HS)	dB(A)	51	53
Compressor type		Rotary	Rotary
Weight	kg	24	29
Dimensions (WxDxH)	mm	610x240x520	610x210x520

Part number 1-230V	ESP061672	ESP061673
---------------------------	------------------	------------------

Linking specifications between units

Power supply			
Power supply side		Indoor	Indoor
Power cable section	mm²	3x1	3x1
Fuse rating am	A	10	10
Electrical connections Ind./Out.	mm²	5x1	5x1

Linking pipes			
Max. length	m	15	15
Max. height	m	7	7
Suction pipe diameter	Inchs	3/8"	3/8"
Liquid pipe diameter	Inchs	1/4"	1/4"

(1) Nominal heating capacity: International conditions 20°C/12°C wet bulb - Outside air temperature: 7°C/6°C wet bulb. (2) Nominal cooling capacity: International conditions (NF EN 255.2 / 814.2 standards) - 27°C/19°C wet bulb - Outside air temperature: 35°C/24°C wet bulb. (3) Global acoustic pressure in dB(A) (1 m) at nominal conditions: outdoor unit in an open area against a reflective background - indoor unit : installation in an average sized room, (PV-0.5s reverberation)



ACE MARKETING SAS - 1 bis, av. du 8 mai 1945 - Saint-Quentin-en-Yvelines
F - 78284 Guyancourt Cedex
Fax : +33 (0) 1 39 44 65 17 - Tél. : +33 (0) 1 39 44 78 00

Your approved **ELECTRA** distributor

