



Fixed speed
Cooling only

MFH PORTABLE



A⁺

THE + «SUSTAINABLE DEVELOPMENT»

→ Environmentally friendly R290 fluid

THE + «USER»

- Easy to move with its wheels and handles
- Easy reading thanks to its digital display on the control panel
- Remotely controllable with RC unit
- Great comfort thanks to its cooling power

THE + «TECHNOLOGY»

- Sealing kit included
- Evacuation of condensates by evaporation

+ PRODUCTS

- RC08C remote control included
- Compact & design
- Economical and efficient (MFH10: 3.10/A+)

FEATURES

AIR QUALITY/CLEAN:



USER FUNCTIONS:



INSTALLER FUNCTIONS:



MFH TECHNICAL DATA

Indoor unit		AW-MFH010-C41	AW-MFH012-C41
Phase		Single phase	Single phase
COOLING			
Rated power	kW	2.93	3.52
Rated power input	kW	0.945	1.357
Current	A	4.5	5.9
EER/Energy label		3.10/A+	2.60/A
Operating limits	°C	17°/35° Dry bulb	
INDOOR UNIT			
Type		Monobloc	Monobloc
Sound pressure level to 1 m (LS/MS/HS)	dB(A)	50/51/52	50/51/52
Sound power Level	dB(A)	56	63
Airflow (LS/MS/HS)	m³/h	355/370/420	355/370/420
Diameter flexible emission duct	mm	150	
Length range of heat emission duct	m	0.50 - 1.5	
Dehumidification	l/h	1.6	1.8
Outline dimensions (WxHxD)	mm	467x765x397	467x765x397
Package dimensions (WxHxD)	mm	515x890x440	515x890x440
Net weight/Gross weight	kg	31.8/35.7	33/36.5
Part number		7MB021060	7MB021061
POWER SUPPLY			
Phase/Voltage/Frequency		1P/230V/50Hz	1P/230V/50Hz
PIPE LINE			
Refrigerant/GWP		R290/20	R290/20
Charge	kg	0.21	0.22

* Packing 8 pieces minimum

FP-MFH EN 1220 - AIRWELL RESIDENTIAL SAS - Specifications subject to change without notice. Pictures non contractual. Printed in U.E.

Airwell

10, RUE DU FORT DE SAINT CYR - 78180 MONTIGNY LE BRETONNEUX, FRANCE
TEL.: +33 (0)1 76 21 82 00 - www.airwell-res.com

AIR CONDITIONING & HEATING