



DC Inverter
Reversible

XDA MONOBLOC CONSOLE



THE «SUSTAINABLE DEVELOPMENT»

→ Ecological fluid R32, low energy consumption

THE «USER»

→ Ideal for modular constructions
→ Connected solution (WiFi with Airconnect Smart)

THE «INSTALLER»

→ Ease of installation
→ Plug & Play

THE «TECHNOLOGY»

→ Inverter technology
→ Monobloc (no outdoor unit)

+ PRODUCTS

- Remote control included XDA RC
- Monobloc solution
- Reversible product (cold/hot)
- No outdoor unit
- No fluid handling

FEATURES

AIR QUALITY / CLEAN:



NANO
PHOTOCATALYTIC
FILTER



AIR FILTER

USER FUNCTIONS:



NIGHT MODE



SUPER
QUIET



RESTART
(MEMORY)



WIFI

INSTALLER FUNCTIONS:



ERROR CODE VIA
INDOOR UNIT



SELF DIAGNOSTIC

XDA TECHNICAL DATA

Indoor unit		AW-XDA009-N91
Phase		Single phase
COOLING		
Rated power	kW	2.35 (1.5~3.0)
Rated power input	kW	0.90
EER/Energy label		2.61/A
Operating limits	°C	-10°/43° Dry bulb
HEATING		
Rated power	kW	2.36 (1.0~2.8)
Rated power input	kW	0.76
COP/Energy label		3.11/A
Operating limits	°C	-15°/24° Dry bulb
INDOOR UNIT		
Sound pressure level to 1 m (LS/MS/HS)	dB(A)	29/46/48
Sound power level	dB(A)	56
Airflow	m³/h	480
Dehumidification	l/h	0.04
Outline dimensions (WxHxD)	mm	615x965x200
Package dimensions (WxHxD)	mm	765x1030x280
Net weight/Gross weight	kg	36,2/40,2
Part number		7SP071430
POWER SUPPLY		
Phase/Voltage/Frequency		1P/220-240V/50Hz
Power cable section	mm²	3x2.5
Fuse rating am (D curve)	A	10
PIPE LINE		
Refrigerant/GWP		R32/675
Charge	kg	0.39