

## CAO

### Water console Fixed speed



- Water console with capacities from 2.3 to 4.7 kW.
- Cooling mode.
- Electrical heater in option.
- Refrigerant: R407C



#### PRODUCT ADVANTAGES

- > Ideal indoor solution when the building structure or aesthetic reasons forbid a condensing outdoor unit.
- > Able to be connected to public water network.
- > Pressostat valve supplied.



## CAO

Water console  
Fixed speed



## FEATURES

- > Ideal solution for building with local restrictions or aesthetic solution.
- > Easy and simple installation.
- > Solution for places without access to external wall.
- > High efficiency system with advance heat exchanger.
- > Built in system protection in water side.

## [ TECHNICAL DATA ]

Indoor units		CAO 230	CAO 370	CAO 580
<b>COOLING</b>				
Rated capacity	kW	<b>2.3</b>	<b>3</b>	<b>4.7</b>
Rated power input	kW	0.66	0.85	1.3
EER/Energy label		3.4/E	3.5/D	3.6/D
Operating limits	°C	15°/32° Dry Bulb		
Condenser inlet water temperature		10°/30°		
<b>INDOOR UNIT</b>				
Sound pressure level to 1 m (LS/HS)	dB(A)	37/40	38/41	41/43
New airflow	m³/h	60	60	80
Airflow (LS/HS)	m³/h	450/550	450/550	725/880
Water flow at +15°C	l/h	130	170	270
Compressor type		Rotary	Rotary	Rotary
Dimensions (WxHxD)	mm	1030x620x226	1030x620x226	1390x620x226
Weight	kg	48	49	69
Part number		<b>7CW011016</b>	<b>7CW011017</b>	<b>7CW011018</b>
<b>POWER SUPPLY 1~230V - 50HZ</b>				
Power supply side		Indoor	Indoor	Indoor
Power cable section	mm²	3x1.5	3x1.5	3x1.5
Fuse rating am		6	6	8