






## CBV CASSETTE 600x600

- → New particular design
- → Quiet operation
- → Built-in high head drain pump
- → Fresh air inlet
- → Wired controller RWV01 included on standard
- → EEV inside

## PRODUCT ADVANTAGES

- The cassette external dimension is 570x570x260mm for easy installation. It is universal and harmony with standard ceiling 600x600mm. There is no breakage for ceiling during installation.
- Airflow pass through the outlet smoothly and fluently owing to the streamline air outlet. Bring you a much more quiet space. The fan blade adopts the design of irregular helix. The indoor unit can run at the lowest sound level.



Pre-set fresh air inlet, can introduce the outside fresh air into the room, greatly improve the indoor air quality (optional).

## **CBV TECHNICAL DATA**


Indoor units			CBV 009	CBV 012	CBV 016
Code		7SP04H001	7SP04H002	7SP04H003	
CAPACITY					
Cooling		kBtu/H	9.5	12.3	15.3
		kW	2.8	3.6	4.5
Heating		kBtu/H	10.9	13.6	17.1
neating		kW	3.2	4	5
ELECTRICAL PA	ARAMETERS				
Power supply		Ph/V/Hz	1/220~230/50	1/220~230/50	1/220~230/50
PERFORMANCI	E				
Air flow (LS/MS/HS)		m³/h	700	700	700
Noise level (LS/MS/HS)		dB(A)	29/30/32	29/30/32	29/30/33
INSTALLATION					
External dimensions (WxHxD)		mm	570x570x260	570x570x260	570x570x260
Shipping dimensions (WxHxD)		mm	718x680x380	718x680x380	718x680x380
Net/Shipping weight		kg	19/21	19/21	19/21
Refrigerant liquid pipe		inches	1/4"	1/4"	1/4"
Refrigerant gas pipe		inches	3/8"	1/2"	1/2"
PANEL					
Code panel			7ACVFH001	7ACVFH001	7ACVFH001
External dimensions (WxHxD)		mm	700x700x60	700x700x60	700x700x60
Shipping dimensions (WxHxD)		mm	740x750x115	740x750x115	740x750x115
Net/Shipping weight		kg	2.8/4.8	2.8/4.8	2.8/4.8
Controller	Wired		RWV01 (S)*	RWV01 (S)*	RWV01 (S)*
	Infrared		RCV01 (O)*	RCV01 (O)*	RCV01 (O)*


<sup>\*</sup> O: optional, S: standard.

## AIRWELL SOLUTIONS



Dimensions: 009-012-016 models







RWVO



RCV01 (optional)



(optional