



DAV

DUCTED LOW STATIC PRESSURE

- 220 ultra thin design and space saving
- Elegant outlook fit with your style
- Optional air return design
- Optional static pressure
- High efficiency filter G3
- EEV inside
- Wired controller RWW01 included on standard

PRODUCT ADVANTAGES

- Ultra thick design make all the models have only 220mm height. It is more convenient for installation and maintenance.
- The indoor unit placed in the ceiling only the inlet and outlet grill can be seen. The most suited grill can be used to fit with the indoor decoration.
- There are two air return design for the different requestment. Let the decoration more optional.
- Two choice of optional static pressure 0 Pa and 20 Pa for the low static pressure duct make user more convenient.
- The unit adopts G3 grade filter which can efficiency filter the dirt etc., and improve the room air quality. At the same time, the filter can be pulled out from downside, convenient for maintenance and cleaning.



RWW01



RCV01 (optional)



(infrared receiver to combined with RCV 01)



RWW03 (optional)

DAV TECHNICAL DATA

Indoor unit		DAV 009	
Code		7SP03H002	
CAPACITY			
Cooling	kBtu/H	9.5	
	kW	2.8	
Heating	kBtu/H	10.9	
	kW	3.2	
ELECTRICAL PARAMETERS			
Power supply		Ph/V/Hz	1/220~230/50
PERFORMANCE			
Air flow (LS/MS/HS)		m³/h	400
Noise level (LS/MS/HS)		dB(A)	30/32/35
INSTALLATION			
External dimensions (WxHxD)		mm	610x484x220
Shipping dimensions (WxHxD)		mm	710x545x280
Net/Shipping weight		kg	15/17
Refrigerant liquid pipe		inches	1/4"
Refrigerant gas pipe		inches	3/8"
Static pressure		Pa	20
Controller	Wired	RWW01 (S)*	
	Infrared	RCV01 (O)*	

* O: optional, S: standard.

AIRWELL SOLUTIONS



Dimensions: 009 model

