

## PRIME

### WALL MOUNTED SPLITS HEAT PUMP

4 Cooling models  
From 2,12 kW to 5,1 kW  
4 Heat Pump models  
From 2,15 kW to 5,55 kW

INDOOR UNIT **PRIME 7-9-12-18**



**RC5 (SIMPLY)**



## SIMPLY

### WALL MOUNTED SPLIT HEAT PUMP

1 Cooling model  
of 6,54 kW  
1 Heat Pump model  
of 7,9 kW

### PRODUCT ADVANTAGES

#### PRIME

- New design with flat panel grill.
- Compact and lightweight for easy installation and maintenance.
- 2 ventilation speeds plus automatic speed.
- Cold/hot Automatic regulation.
- Automatic vertical treated air sweeping.
- High efficiency filtration.
- Supplied with RC4 remote control.

#### SIMPLY

- Automatic vertical treated air sweeping.
- High filtration.
- Compact and lightweight for easy installation and maintenance.
- Two fan speeds.
- Slow down at night.

#### FLORIDA

- Automatic sweeping of treated air.
- LCD screen.
- ESF model: ioniser and prefilter.

**RC4 (PRIME / FLORIDA)**



## FLORIDA

### WALL MOUNTED SPLIT HEAT PUMP

1 Cooling model  
of 8,5 kW  
1 Heat Pump model  
of 9,5 kW

OUTDOOR UNIT  
**GC PRIME 7-9-12 / RC**



INDOOR UNIT  
**SIM 24**



OUTDOOR UNIT  
**GC PRIME 18 / RC**



INDOOR UNIT  
**FLO 30**




OUTDOOR UNIT  
**GC SIM 24 / RC**
















OUTDOOR UNIT  
**GC 30 / RC**





## PRIME / SIMPLY / FLORIDA

		PRIME 7	PRIME 9	PRIME 12	PRIME 18	SIM 24	FLO 30	
	<b>Indoor Units</b>	<b>ST PRIME 7</b>	<b>ST PRIME 9</b>	<b>ST PRIME 12</b>	<b>ST PRIME 18</b>	<b>ST SIM 24</b>	<b>ST FLO 30</b>	
	<b>Outdoor Units</b>	<b>GC PRIME 7</b>	<b>GC PRIME 9</b>	<b>GC PRIME 12</b>	<b>GC PRIME 18</b>	<b>GC SIM 24</b>	<b>GC 30</b>	
	<b>Outdoor Units</b>	<b>GC PRIME 7RC</b>	<b>GC PRIME 9RC</b>	<b>GC PRIME 12RC</b>	<b>GC PRIME 18RC</b>	<b>GC SIM 24 RC</b>	<b>GC 30RC</b>	
	<b>Capacity</b>	kW <b>2,12</b>	<b>2,6</b>	<b>3,2</b>	<b>5,1</b>	<b>6,54</b>	<b>8,5</b>	
	Input power	kW 0,73	0,97	1,15	1,93	2,33	3,1	
	EER/Energy Label	2,9 / C	2,68 / D	2,78 / D	2,64 / D	2,8 / D	2,74 / D	
	Operating limits	°C 10/46°C Dry Bulb	10/46°C Dry Bulb	10/46°C Dry Bulb	10/46°C Dry Bulb	10/46°C Dry Bulb	10/46°C Dry Bulb	
	<b>Capacity</b>	kW <b>2,15</b>	<b>2,8</b>	<b>3,5</b>	<b>5,55</b>	<b>7,90</b>	<b>9,5</b>	
	Input power	kW 0,69	0,89	1,06	1,9	2,66	3,25	
	COP/Energy Label	3,12 / D	3,15 / D	3,3 / D	2,92 / D	2,70 / E	2,02 / D	
	Operating limits	°C -9/24°C Dry Bulb	-9/24°C Dry Bulb	-9/24°C Dry Bulb	-9/24°C Dry Bulb	-9/24°C Dry Bulb	-9/24°C Dry Bulb	
	Sound pressure level 1 mt <sup>1</sup>	dB(A) 31/37	35/40	33/40	35/44	44/50	44/48/52	
	Sound power level <sup>1</sup>	dB(A) 45/50	48/52	47/53	-	64/58	57/61/65	
	Airflow <sup>1</sup>	Pa 320/400	350/450	460/620	450/670	690/990	900/1050/1300	
	Dehumidification	l/h 0,7	1,0	1,05	2,2	3,1	4	
	Dimensions (WxDxH)	mm 680x180x250	680x180x250	840x180x250	900x200x295	1115x205x330	1280x340x236	
	Weight	kg 7	7	8	12	14	18,5	
	<b>Part number</b>	<b>7SP022758</b>	<b>7SP022759</b>	<b>7SP022760</b>	<b>7SP022761</b>	<b>7SP022182</b>	<b>7SP022275</b>	
	<b>Price</b>	€						
		Sound pressure level 1 mt	dB(A) 52	52	54	49	61	61
		Sound power level	dB(A) 62	62	65	-	71	71
		Airflow	m <sup>3</sup> /h 1200	1265	1200	-	2480	3200
		Compressor type	Rotary	Rotary	Rotary	Rotary	Rotary	Scroll
Dimensions (WxDxH)		mm 600x240x520	610x240x520	610x240x520	795x290x610	846x302x690	900x340x970	
	Weight	kg 23	27	29	42	62	84	
	<b>Part number</b>	-	-	-	<b>7SP061577</b>	<b>7SP061532</b>	<b>7SP061403</b>	
	<b>Price</b>	€	-	-	-	-	-	
	<b>Full set price</b>	€	-	-	-	-	-	
	<b>Part number</b>	-	-	-	-	-	<b>7SP061405</b>	
	<b>Price</b>	€	-	-	-	-	-	
	<b>Full set price</b>	€	-	-	-	-	-	
	<b>Part number</b>	<b>7SP061533</b>	<b>7SP061678</b>	<b>7SP061679</b>	<b>7SP061578</b>	<b>7SP061550</b>	<b>7SP061404</b>	
	<b>Price</b>	€	-	-	-	-	-	
	<b>Full set price</b>	€	-	-	-	-	-	
	<b>Part number</b>	-	-	-	-	-	<b>7SP061406</b>	
	<b>Price</b>	€	-	-	-	-	-	
	<b>Full set</b>	€	-	-	-	-	-	
	Power supply side	Indoor	Indoor	Indoor	Indoor	Indoor	Outdoor	
	Power cable section	mm <sup>2</sup> 3x1,5	3x1,5	3x1,5	3x1,5	3x2,5	3x4	
	Fuse rating am	A 10	10	16	16	20	25	
	Electrical connections	mm <sup>2</sup> 4x1	4x1	4x1,5	4x1,5	4x2,5	5x2,5	
	Electrical connections	mm <sup>2</sup> 5x1	5x1	5x1,5	5x1,5	5x2,5	6x2,5	
	Power supply side	-	-	-	-	-	Outdoor	
	Power cable section	mm <sup>2</sup> -	-	-	-	-	5x2,5	
	Fuse rating am	A -	-	-	-	-	3x16	
	Electrical connections	mm <sup>2</sup> -	-	-	-	-	5x2,5	
	Electrical connections	mm <sup>2</sup> -	-	-	-	-	6x1,5	
		Suction pipe diameter	inches 3/8"	3/8"	1/2"	1/2"	5/8"	5/8"
		Liquid pipe diameter	inches 1/4"	1/4"	1/4"	1/4"	3/8"	3/8"
		Max lenght	m 10	12	15	15	15	30
		Max height	m 7	7	7	7	7	15

<sup>1</sup>Data are relative to Low speed, Medium speed and High speed

Accessories	PRIME 7	PRIME 9	PRIME 12	PRIME 18	SIM 24	FLO 30
All seasons kit	7ACFH0077	€				
	7ACFH0078	€				
Mounting bracket	7ACTL0016	€		-	-	-
	7ACTL0018	€	-	-	-	-