

PRIME

WALL MOUNTED SPLITS HEAT PUMP

6 Cooling models
From 2,23 kW to 6,77 kW
6 Heat Pump models
From 2,32 kW to 7,08 kW

INDOOR UNIT **PRIME 7-9**



FLORIDA

WALL MOUNTED SPLIT HEAT PUMP

1 Cooling model
of 8,5 kW
1 Heat Pump model
of 9,5 kW

PRODUCT ADVANTAGES

PRIME

- New design with flat panel grill.
- Compact and lightweight for easy installation and maintenance.
- 2 ventilation speeds plus automatic speed.
- Cold/hot automatic regulation.
- Automatic vertical treated air sweeping.
- High efficiency filtration.
- Supplied with RC4 remote control.

FLORIDA

- Automatic sweeping of treated air.
- LCD screen.
- ESF model: ioniser and prefilter.

RC4



OUTDOOR UNIT
ODU WAP 7-9-12 RC



INDOOR UNIT **PRIME 12**



INDOOR UNIT **PRIME 18**



INDOOR UNIT
FLO 30



OUTDOOR UNIT
GC RELAX 18 NRC



OUTDOOR UNIT
GC 30 / NRC (FLORIDA)





PRIME / FLORIDA

| | | PRIME 7 | PRIME 9 | PRIME 12 | PRIME 18 | PRIME 21 | PRIME 24 | FLO 30 |
|---------------------------------|--|-----------------------|--------------------|---------------------|-----------------------|------------------|------------------|------------------|
| Indoor Units | | PRIME 7 | PRIME 9 | PRIME 12 | PRIME 18 | PRIME 21 | PRIME 24 | FLO 30 |
| Outdoor Units | | GC RELAX 7 RC | ODU WAP 9RC | ODU WAP 12RC | GC RELAX 18NRC | | | GCN 30 RC |
| Cooling | Capacity | kW 2,23 | 2,7 | 3,3 | 5,6 | 6,2 | 6,77 | 8,5 |
| | Power input | kW 0,72 | 0,98 | 1,17 | 1,83 | 2,05 | 2,24 | 3,1 |
| | EER/Energy Label | 3,08 / A | 2,73 / D | 2,81 / C | 3,05 / B | 3,0 / B | 3,0 / B | 2,74 / D |
| | Operating limits | °C 10/46°C Dry Bulb | 10/46°C Dry Bulb | 10/46°C Dry Bulb | 10/46°C Dry Bulb | 10/46°C Dry Bulb | 10/46°C Dry Bulb | 10/46°C Dry Bulb |
| Heating | Capacity | kW 2,32 | 2,8 | 3,8 | 6,1 | 6,5 | 7,08 | 9,5 |
| | Power input | kW 0,67 | 0,85 | 1,1 | 1,76 | | 3,93 | 3,25 |
| | COP/Energy Label | 3,45 / B | 3,3 / C | 3,45 / C | 3,45 / B | 3,5 / B | 3,0 / D | 2,02 / D |
| | Operating limits | °C -9/24°C Dry Bulb | -9/24°C Dry Bulb | -9/24°C Dry Bulb | -9/24°C Dry Bulb | -9/24°C Dry Bulb | -9/24°C Dry Bulb | -9/24°C Dry Bulb |
| Indoor unit | Sound pressure level 1 mt ¹ | dB(A) 31/37 | 35/40 | 34/41 | 37/43 | 42/44/47 | 42/44/47 | 44/48/52 |
| | Sound power level ¹ | dB(A) 45/50 | 48/52 | 49/55 | 50/55 | 55/57/60 | 55/57/60 | 57/61/65 |
| | Airflow ¹ | Pa 400/410 | 450/465 | 650/680 | 690/720 | 740/820/910 | 740/820/910 | 900/1050/1300 |
| | Dehumidification | l/h 0,7 | 1,0 | 1,0 | 2,4 | 2,3 | 2,3 | 4 |
| | Dimensions (WxDxH) | mm 680x180x250 | 680x180x250 | 840x180x250 | 900x200x295 | 1060x221x295 | 1060x221x295 | 1280x340x236 |
| | Weight | kg 7 | 7 | 8 | 11 | 15 | 15 | 18,5 |
| | Part number | 7SP022758 | 7SP022759 | 7SP022760 | 7SP022761 | 7SP022803 | 7SP022793 | 7SP022275 |
| Price | € | | | | | | | |
| Outdoor unit | Sound pressure level 1 mt | dB(A) 52 | 53 | 54 | 54 | | | 61 |
| | Sound power level | dB(A) 62 | 63 | 65 | 65 | | | 71 |
| | Airflow | m ³ /h | | | | | | 3200 |
| | Compressor type | Rotary | Rotary | Rotary | Rotary | | | Scroll |
| Dimensions (WxDxH) | mm 610x240x520 | 610x240x520 | 610x240x520 | 795x290x610 | | | 900x340x970 | |
| Weight | kg 24 | 26,5 | 32 | 47 | | | 84 | |
| Power supply 1-230V-50Hz | Part number | - | 7SP061700 | 7SP061701 | 7SP061577 | | | 7SP061403 |
| | Price | € - | | | | | | |
| | Full set price | € - | | | | | | |
| Power supply 3-400V-50Hz | Part number | - | | | | | | 7SP061405 |
| | Price | € - | | | | | | |
| | Full set price | € - | | | | | | |
| Power supply 1-230V-50Hz | Part number | 7SP061534 | 7SP061678 | 7SP061679 | 7SP061578 | | | 7SP061404 |
| | Price | € | | | | | | |
| | Full set price | € | | | | | | |
| Power supply 3-400V-50Hz | Part number | - | - | - | - | | | 7SP061406 |
| | Price | € - | - | - | - | | | |
| | Full set | € - | - | - | - | | | |
| Power supply 1-230V-50Hz | Power supply side | Indoor | Indoor | Indoor | Indoor | | | Outdoor |
| | Power cable section | mm ² 3x1,5 | 3x1,5 | 3x1,5 | 3x1,5 | | | 3x4 |
| | Fuse rating | A 10 | 10 | 16 | 16 | | | 25 |
| | Electrical connections | mm ² 4x1,5 | 4x1 | 4x1,5 | 4x1,5 | | | 5x2,5 |
| | Electrical connections | mm ² 5x1,5 | 5x1 | 5x1,5 | 5x1,5 | | | 6x2,5 |
| Power supply 3-400V-50Hz | Power supply side | - | - | - | - | | | Outdoor |
| | Power cable section | mm ² - | - | - | - | | | 5x2,5 |
| | Fuse rating | A - | - | - | - | | | 3x16 |
| | Electrical connections | mm ² - | - | - | - | | | 5x2,5 |
| | Electrical connections | mm ² - | - | - | - | | | 6x1,5 |
| Pipe line | Suction pipe diameter | inches 3/8" | 3/8" | 1/2" | 1/2" | | | 5/8" |
| | Liquid pipe diameter | inches 1/4" | 1/4" | 1/4" | 1/4" | | | 3/8" |
| | Max lenght | m 10 | 12 | 15 | 15 | | | 30 |
| | Max height | m 7 | 7 | 7 | 7 | | | 15 |

¹Data are relative to Low speed, Medium speed and High speed

| Accessories | PRIME 7 | PRIME 9 | PRIME 12 | PRIME 18 | PRIME 21 | PRIME 24 | FLO 30 |
|------------------|-----------|---------|----------|----------|----------|----------|--------|
| Mounting bracket | 7ACTL0016 | € | | | | | |
| | 7ACTL0018 | € - | - | - | - | | |