

**HIWELL RANGE**

## HAF

**WALL MOUNTED  
HEAT PUMP**

3 Heat Pump models  
From 2,1 kW to 3,8 kW

INDOOR UNIT **HAF 007-009-012**



### PRODUCT ADVANTAGES

- The HAF wall mounted range has a unique and very elegant design with a translucent panel.
- Background LED on the front panel.
- Filter cleaning indication by dedicated LED.
- Infrared remote control with LED display.
- Self diagnostic LED lighting for ease of maintenance.
- Indoor large diameter cross flow fan, allowing low operation sound level.
- Motorized flaps.
- Bended indoor coil with treated aluminum fins and coating for improved efficiency.
- Simple installation and service with easy access to the interconnecting tubing and wiring connections
- Refrigerant pipes can be connected to the indoor unit from 5 different optional directions.
- Compatible with GCAO R410A cooled water units.
- Supplied with RC4 remote control.

\* Wall mounted RCW2 remote control (Optional)

**RC4**

**RCW2\***



OUTDOOR UNIT  
**GC 7-9 ARC**



OUTDOOR UNIT  
**GC 12 ARC**





## HIWELL HAF

		HAF 007	HAF 009	HAF 012
<b>Indoor Units</b>		<b>HAF 007</b>	<b>HAF 009</b>	<b>HAF 012</b>
<b>Outdoor Units</b>		<b>GC 7 ARC</b>	<b>GC 9 ARC</b>	<b>GC 12 ARC</b>
<b>Cooling</b>	<b>Capacity</b>	<b>2,05</b>	<b>2,64</b>	<b>3,50</b>
	Power input	0,68	0,87	1,16
	EER/Energy Label	3,01 / B	3,03 / B	3,02 / B
	Operating limits	21°/46° Dry Bulb	21°/46° Dry Bulb	21°/46° Dry Bulb
<b>Heating</b>	<b>Capacity</b>	<b>2,15</b>	<b>2,8</b>	<b>3,78</b>
	Power input	0,63	0,93	1,17
	COP/Energy Label	3,41 / B	3,04 / D	3,23 / C
	Operating limits	-9°/24° Dry Bulb	-9°/24° Dry Bulb	-9°/24° Dry Bulb
<b>Indoor unit</b>	Sound pressure level 1 mt <sup>1</sup>	29/33/37	31/37/41	33/38/41
	Sound power level <sup>1</sup>	42/46/50	44/50/53	46/51/56
	Airflow (CO/HP)	108/108	125/125	172/172
	Dehumidification	0,8	1,2	1,5
	Dimensions (WxDxH)	680x188x250	680x188x250	840x188x250
	Weight	7	7	8
	<b>Part number</b>	<b>7SP022789</b>	<b>7SP022790</b>	<b>7SP022791</b>
	<b>Price</b>	€		
<b>Outdoor unit</b>	Sound pressure level 1 mt	53	51	54
	Sound power level	62	59	62
	Airflow	1200	1370	1450
	Compressor type	Rotary	Rotary	Rotary
	Dimensions (WxDxH)	610x240x250	830x245x545	830x245x545
	Weight	27,5	33,5	38
<b>Power supply 1-230V - 50 Hz</b>	<b>Part number</b>			
	<b>Price</b>	€		
	<b>Full set price</b>	€		
<b>Power supply 1-230V - 50 Hz</b>	<b>Part number</b>	<b>7SP061585</b>	<b>7SP061586</b>	<b>7SP061587</b>
	<b>Price</b>	€		
	<b>Full set price</b>	€		
<b>Power supply 1-230V - 50Hz</b>	Power supply side	Indoor	Indoor	Indoor
	Power cable section	3x1,5	3x1,5	3x1,5
	Fuse rating	10	10	10
	Electrical connections	4x1,5	4x1,5	4x1,5
	Electrical connections	5x1,5	5x1,5	5x1,5
	Suction pipe diameter	3/8"	3/8"	3/8"
<b>Pipe line</b>	Liquid pipe diameter	1/4"	1/4"	1/4"
	Max lenght	10	15	15
	Max height	7	7	7

<sup>1</sup>Data are relative to Low speed, Medium speed and High speed

Accessories	HAF 007	HAF 009	HAF 012
Outdoor Wall mounting bracket	7ACTL0016 €		
RCW Wall Mounted Remote Control	7ACEL1157 €		
RCW2 Wall Mounted Remote Control	7ACEL1212 €		