

HHF

WALL SPLIT MOUNTED



Airwell



HHF

Wall Split Mounted - Fixed RPM line

PRODUCT ADVANTAGES

- Flat panel design.
- Led display panel with room set temp display.
- Low noise level.
- High efficiency filters including photo catalytic and anti bacterial pre filters.
- R410A high performance fluid.
- Energy label class A/A (sizes 9 and 12).
- Compact dimensions.
- Auto clean and internal drying.
- Self diagnostic by failure code indication.
- Auto restart.
- Cooling and heating boosting mode.



IR remote control

			HHF009 AWSI-HHF009-N11 AWAU-YGF009-H11	HHF012 AWSI-HHF012-N11 AWAU-YGF012-H11	HHF018 AWSI-HHF018-N11 AWAU-YGF018-H11	HHF024 AWSI-HHF024-N11 AWAU-YGF024-H11
Cooling	Capacity	KW	2.64	3.22	5.30	6.15
	Power input	KW	0.82	1	1.64	1.9
	EER/Energy label		3.21/A	3.21/A	3.23/A	3.24/A
	Operating limits	°C			21/46°C Dry Bulb	
Heating	Capacity	KW	2.81	3.52	5.70	6.50
	Power input	KW	0.78	0.97	1.67	1.9
	COP/Energy label		3.61/A	3.61/A	3.41/B	3.42/B
	Operating limits	°C			- 9/24°C Dry Bulb	
Indoor units	Sound pressure level (SH/H/M/L)	dB(A)	40/37/35/32	40/38/35/32	48/45/42/38	47/44/41/38
	Sound power level (SH/H/M/L)	dB(A)	50/47/45/42	50/48/45/42	58/55/52/48	57/54/51/48
	Dehumidification	l/h	1	1	3	3
	Air Flow SH/H/M/L	m³/h	400/370/340/310	550/500/420/350	850/780/650/550	850/780/650/550
	Dimensions (WxDxH)	mm	730x174x255	790x177x265	940x200x298	940x200x298
	Weight	kg	8	9	13	13
	Part Number		7SP022856	7SP022857	7SP022858	7SP022859
Outdoor units	Sound pressure level	dB(A)	50	52	54	54
	Sound power level	dB(A)	60	62	64	64
	Airflow	m³/h	1500	1800	2790	2790
	Compressor type		Rotary	Rotary	Rotary	Rotary
	Dimensions (WxDxH)	mm	785x320x540	798x320x540	913x378x680	913x378x680
	Weight	kg	31	35	46	46
	Part Number		7SP061764	7SP061765	7SP061766	7SP061767
Power supply 1-230V - 50Hz	Power supply side		indoor	indoor	indoor	indoor
	Power cable section	mm	3x1.0	3x1.0	3x2.5	3x2.5
	Fuse rating	A	10	16	25	25
	Electrical connections	mm	5x1.5	5x1.5	5x2.5	5x2.5
Pipe line	Suction pipe diameter	inches	3/8"	1/2"	1/2"	1/2"
	liquid pipe diameter	inches	1/4"	1/4"	1/4"	1/4"
	Max lenght	m	15	20	25	25
	Max height	m	10	10	10	10

Rating conditions in accordance to ISO 5151 and ISO 13253 (for ducted units).
 Conditions: Nominal cooling capacity: ID/OD (27/19//35/24)
 Nominal heating capacity: ID/OD (20/15//7/6)

Airwell

Your official dealer



Airwell Group

1bis, Avenue du 8 mai 1945
 Saint Quentin en Yvelines
 78284 GUYANCOURT
 France
 Tel. +33 (0)139 44 78 00
 Fax +33 (0)139 44 65 17
 www.airwell.com
 contact@airwell-group.com

