

PNX / FLO N

WALL MOUNTED

8 Cooling models
From 2,23 kW to 10,15 kW
8 Heat Pump models
From 2,17 kW to 11,14 kW

INDOOR UNIT **PNX 7-9-12-14**



Ioniser



Standard filter



Active charcoal filter



Electrostatic filter

PRODUCT ADVANTAGES

- AQS version.
- R410A "green" fluid.
- High efficiency filtration.
- Functions displayed on LCD display (FLO 18/24/30/36).
- Ioniser.
- Electronic regulation and programming.
- Automatic vertical treated air sweeping.
- Supplied with RC4 remote control.
- PNX & FLO N indoor units with R410A are compatible with GCAO R410A cooled water units.

RC 4



INDOOR UNIT **PNX 18-21-24**



OUTDOOR UNIT
GC 7-9-12-14 N / NRC



OUTDOOR UNIT
GC 18-21 N / NRC



INDOOR UNIT **FLO 30-36 N**



OUTDOOR UNIT
GC 24-30 / NRC



OUTDOOR UNIT
GC 37 N / NRC





PNX / FLO

		PNX 7	PNX 9	PNX 12	PNX 14	PNX 18	PNX 21	PNX 24	FLO 30N	FLO 36N	
	Indoor Units	ST PNX 7	ST PNX 9	ST PNX 12	ST PNX 14	ST PNX 18	ST PNX 21	ST PNX 24	ST FLO 30N	ST FLO 36N	
	Outdoor Units	GC 7 N	GC 9 N	GC 12 N	GC 14 N	GC 18 N	GC 21 N	GC 24 Z	GCN 30	GC 37N	
	Outdoor Units	GC 7 NRC	GC 9 NRC	GC 12 NRC	GC 14 NRC	GC 18 NRC	GC 21 NRC	GC 24 RC Z	GCN 30 RC	GC 37NRC	
	Capacity	2,23	2,72	3,58	4,22	5,35	6,2	6,77	8,5	10,15	
	Input power	0,68	0,82	1,1	1,33	1,66	2,05	2,24	2,9	3,22	
	EER/Energy Label	3,3 / A	3,3 / A	3,2 / A	3,2 / A	3,2 / A	3,0 / B	3,0 / B	2,9 / C	3,15 / B	
	Operating limits	21°/46° Dry Bulb									
	Operating limits	°C									
	Capacity	2,17	2,9	4,19	4,40	5,4	6,5	7,08	9,08	11,14	
	Capacity at -10°C	1,15	1,52	2,02	2,26	2,73	-	3,93	4,68	5,76	
	Input power	0,59	0,84	1,14	1,31	1,56	1,57	2,4	2,9	3,6	
	COP/Energy Label	3,5 / B	3,4 / B	3,6 / A	3,3 / C	3,5 / B	3,5 / B	3,0 / D	3 / D	3,1 / D	
	Operating limits	-9°/24° Dry Bulb									
	Sound pressure level 1 mt ¹	25/27/30	28/31/35	35/39/43	36/41/46	37/40/43	42/44/47	42/44/47	44/48/52	48/50/52	
	Sound power level ¹	39/41/45	44/46/49	49/53/55	46/51/56	50/53/56	55/57/60	55/57/60	55/57/60	61/63/66	
	Airflow ¹	280/320/380	330/380/450	450/550/635	475/550/660	750/840/930	740/820/910	740/820/910	1030/1110/1360	1110/1240/1360	
	Dehumidification	0,7	0,9	1,3	1,5	1,8	2,3	2,3	3,6	4	
	Dimensions (WxDxH)	810x210x285	810x210x285	810x210x285	810x210x285	1060x221x295	1060x221x295	1060x221x295	1200x236x340	1200x236x340	
	Weight	11	11	11,5	11,5	15	15	15	17	17	
	Part number	7SP022704	7SP022705	7SP022706	7SP022707	7SP022191	7SP022718	7SP022339	7SP022195	7SP022370	
	Price	€									
		Sound pressure level 1 mt ¹	48	51	51	53	57	59	54*	58	61
		Sound power level	57	60	64	64	68	69	62	62	70
Airflow		1660	1780	1850	2160	2480	2860	3100*	3150	4150	
Compressor type		Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	
Dimensions (WxDxH)		795x290x610	795x290x610	795x290x610	795x290x610	846x302x690	846x302x690	900x340x680	900x340x680	900x340x970	
Weight		32	35	36	42,2	56	56	74*	78	87	
	Part number	7SP061440	7SP061441	7SP061442	7SP061443	7SP061444	-	7SP061680	7SP061601	7SP061621	
	Price	€									
	Part number	-	-	-	-	7SP061590	-	7SP061682	7SP061602	7SP061622	
	Price	€									
	Part number	7SP061428	7SP061429	7SP061430	7SP061431	7SP061436	7SP061595	7SP061644	7SP061604	7SP061630	
	Price	€									
	Part number	-	-	-	-	7SP061589	-	7SP061683	7SP061605	7SP061631	
	Price	€									
	Full set price	€									
	Power supply side	Indoor	Indoor	Indoor	Indoor	Ind. or Outd.	Outdoor	Outdoor	Outdoor	Outdoor	
	Power cable section	3x1,5	3x1,5	3x1,5	3x1,5	3x1,5	3x2,5	3x2,5	3x4	3x4	
	Fuse rating am	10	10	16	16	16	20	20	25	25	
	Electrical connections	4x1	4x1	4x1,5	4x1,5	4x1,5	4x2,5	5x1,5**	5x1,5	5x1,5	
	Electrical connections	5x1	5x1	5x1,5	5x1,5	5x1,5	5x2,5	6x1,5**	6x1,5	6x1,5	
	Power supply side	-	-	-	-	Outdoor	-	Ind. or Outd.	Outdoor	Outdoor	
	Power cable section	-	-	-	-	5x1,5	-	5x1,5	5x2,5	5x2,5	
	Fuse rating am	-	-	-	-	3x10	-	3x10	3x16	3x16	
	Electrical connections	-	-	-	-	5x1,5	-	5x1,5	5x2,5	5x1,5	
	Electrical connections	-	-	-	-	6x1,5	-	6x1,5	6x1,5	6x1,5	
	Electrical connections	-	-	-	-	6x1,5	-	6x1,5	6x1,5	6x1,5	
	Suction pipe diameter	3/8"	3/8"	3/8"	1/2"	1/2"	5/8"	5/8"	5/8"	3/4"	
	Liquid pipe diameter	1/4"	1/4"	1/4"	1/4"	1/4"	3/8"	3/8"	3/8"	3/8"	
	Max lenght	15	15	15	15	25	20	20	30	50	
	Max height	7	7	7	7	15	15	15	10	25	

Accessories		PNX 7	PNX 9	PNX 12	PNX 14	PNX 18	PNX 21	PNX 24	FLO 30N	FLO 36N
Mounting bracket	7ACTL0016	€	-							
	7ACTL0018	€								
All season kit	7ACFH0480	€								

¹Data are relative to Low speed, Medium speed and High speed