

WAN / WAF

WALL MOUNTED

4 Cooling models
From 2,0 kW to 5,1 kW
4 Heat Pump models
From 2,1 kW to 5,3 kW

INDOOR UNIT **WAN 7-9-12**



PRODUCT ADVANTAGES

- Sober and unobtrusive design.
- Easy to install and operate.
- R410A high efficiency fluid.
- Class B energy label (depending on models).
- High efficiency filtration.
- Automatic treated air sweeping.
- Electronic regulation and programming.
- Condensate drainage lift pump (accessory).
- Supplied with RC5 remote control.

INDOOR UNIT **WAF 18**



OUTDOOR UNIT
GC 7 A



RC5



OUTDOOR UNIT
GC 9-12 A



OUTDOOR UNIT
GC 18 A





WAN / WAF

		WAN 7	WAN 9	WAN 12	WAF 18	
	Indoor Units	ST WAN 7	ST WAN 9	ST WAN 12	ST WAF 18	
	Outdoor Units	GC 7 A	GC 9 A	GC 12 A	GC 18 A	
	Outdoor Units	GC 7 ARC	GC 9 ARC	GC 12 ARC	GC 18 ARC	
Cooling	Capacity	2,05	2,64	3,50	5,15	
	Input power	0,68	0,87	1,16	1,70	
	EER/Energy Label	3 / B	3 / B	3 / B	3 / B	
	Operating limits	21°/ 46° Dry Bulb	21°/ 46° Dry Bulb	21°/ 46° Dry Bulb	21°/ 46° Dry Bulb	
Heating	Capacity	2,15	2,8	3,8	5,35	
	Capacity at -15°C	1,09	1,43	1,9	2,7	
	Input power	0,63	0,93	1,17	1,65	
	COP/Energy Label	3,4 / B	3 / D	3,2 / C	3,2 / C	
Indoor unit	Operating limits	-10°/ 24° Dry Bulb	-10°/ 24° Dry Bulb	-10°/ 24° Dry Bulb	-10°/ 24° Dry Bulb	
	Sound pressure level 1 mt ¹	32/37	35/41	33/40	37/43	
	Sound power level ¹	44/50	49/53	47/53	50/55	
	Airflow ¹	320/390	360/450	460/620	590/720	
	Dehumidification	0,8	1,2	1,5	2,2	
	Dimensions (WxDxH)	680x180x250	680x180x250	840x180x250	900x200x295	
	Weight	7	7	8	11	
	Part number	7SP022716	7SP022711	7SP022712	7SP022308	
	Price	€				
	Outdoor unit	Sound pressure level 1 mt	53	51	54	54
		Sound power level	62	61	65	65
Airflow		1200	1370	1450	2160	
Compressor type		Rotary	Rotary	Rotary	Rotary	
Dimensions (WxDxH)		610x240x520	830x245x545	830x245x545	795x290x610	
Weight	27,5	33,5	38	43		
Power supply 1-230V-50Hz	Part number	7SP061581	7SP061582	7SP061583	7SP061584	
	Price	€				
	Full set price	€				
Power supply 1-230V-50Hz	Part number	7SP061585	7SP061586	7SP061587	7SP061588	
	Price	€				
	Full set price	€				
Power supply 1-230V-50Hz	Power supply side	Indoor	Indoor	Indoor	Indoor	
	Power cable section	3x1,5	3x1,5	3x1,5	3x1,5	
	Fuse rating am	10	10	10	16	
	Electrical connections	4x1,5	4x1,5	4x1,5	4x1,5	
	Electrical connections	5x1,5	5x1,5	5x1,5	5x1,5	
Pipe line	Suction pipe diameter	3/8"	3/8"	3/8"	1/2"	
	Liquid pipe diameter	1/4"	1/4"	1/4"	1/4"	
	Max lenght	10	15	15	15	
	Max height	7	7	7	7	

¹Data are relative to Low speed, Medium speed and High speed

Accessories	WAN 7	WAN 9	WAN 12	WAF 18
Mounting bracket	7ACTL0016	€		-
	7ACTL0018	€	-	-