

ALASKA RANGE

WAN

WALL MOUNTED

3 Cooling models
From 2,0 kW to 3,5 kW
3 Heat Pump models
From 2,1 kW to 3,8 kW

INDOOR UNIT **WAN 7-9-12**



PRODUCT ADVANTAGES

- Wall mounted On/Off range with elegant design.
- Easy access to tubing and wiring connections.
- Piping height difference up to 15 m between indoor and outdoor units.
- Sober and unobtrusive design.
- Easy to install and operate.
- R410A high efficiency fluid.
- High COP with Class B energy label.
- High efficiency filtration.
- Automatic treated air sweeping.
- Electronic regulation and programming.
- Condensate drainage lift pump (accessory).
- Dehumidification rate up to 1,5 litre per hour.
- Supplied with RC5 remote control.


OUTDOOR UNIT
GC 7 A / ARC



RC5



OUTDOOR UNIT
GC 9-12 A / ARC





ALASKA WAN

		WAN 7	WAN 9	WAN 12	
	Indoor Units	WAN 7	WAN 9	WAN 12	
	Outdoor Units	GC 7 A	GC 9 A	GC 12 A	
	Outdoor Units	GC 7 ARC	GC 9 ARC	GC 12 ARC	
Cooling	Capacity	2,05	2,64	3,50	
	Power input	0,67	0,87	1,16	
	EER/Energy Label	3,06 / B	3,03 / B	3,02 / B	
	Operating limits	21° / 46° Dry Bulb	21° / 46° Dry Bulb	21° / 46° Dry Bulb	
Heating	Capacity	2,15	2,83	3,78	
	Capacity at -15°C	1,09	1,43	1,9	
	Power input	0,63	0,93	1,17	
	COP/Energy Label	3,41 / B	3,04 / D	3,23 / C	
Indoor unit	Operating limits	-10° / 24° Dry Bulb	-10° / 24° Dry Bulb	-10° / 24° Dry Bulb	
	Sound pressure level 1 mt ¹	32/37	35/41	33/40	
	Sound power level ¹	44/50	49/51	47/54	
	Airflow ¹	320/390	360/450	460/620	
Outdoor unit	Dehumidification	l/h	1,2	1,5	
	Dimensions (WxDxH)	mm	680x180x250	840x180x250	
	Weight	kg	7	8	
	Part number	7SP022716	7SP022711	7SP022712	
	Price	€			
	Sound pressure level 1 mt	dB(A)	53	51	54
	Sound power level	dB(A)	62	61	67
	Airflow	m ³ /h	1200	1370	1450
	Compressor type		Rotary	Rotary	Rotary
	Dimensions (WxDxH)	mm	610x240x520	830x245x545	830x245x545
Power supply 1-230V-50Hz	Weight	kg	27,5	33,5	38
	Part number	7SP061581	7SP061582	7SP061583	
	Price	€			
Power supply 1-230V-50Hz	Full set price	€			
	Part number	7SP061585	7SP061586	7SP061587	
Power supply 1-230V-50Hz	Price	€			
	Full set price	€			
Power supply 1-230V-50Hz	Power supply side	Indoor	Indoor	Indoor	
	Power cable section	mm ²	3x1,5	3x1,5	3x1,5
	Fuse rating	A	10	10	10
	Electrical connections	mm ²	4x1,5	4x1,5	4x1,5
	Electrical connections	mm ²	5x1,5	5x1,5	5x1,5
	Pipe line	Suction pipe diameter	inches	3/8"	3/8"
Pipe line	Liquid pipe diameter	inches	1/4"	1/4"	
	Max length	m	10	15	15
	Max height	m	7	7	7

¹Data are relative to Low speed and High speed

Accessories	WAN 7	WAN 9	WAN 12
Mounting bracket	7ACTL0016	€	