



WALL MOUNTED RANGE

ALASKA WN & WAF



Airwell
INNOVATION & SERVICE

Airwell

WN



WN 7/9 RC



GC 7 ARC



WAF 17 RC



GCNG 18 RC

This range of 4 Cooling Only or Heat Pump models (2310 to 5350 W) is particularly suited to the need for heating and air conditioning in housing and offices. With its streamlined design including a new flat front panel and ease of use, this product provides high-level comfort to users and ease of installation.

> Product benefits

- FLAT PANEL design (WN).
- Sober and unobtrusive design.
- Compact and light-weight for easy installation and maintenance.
- R410A high efficiency fluid.
- Class B Energy Label (depending on models).
- Indoor units compatible with DUO Multisplits.
- 3 fan speeds plus auto fan speed.
- Night running function.
- Automatic treated air sweeping.
- High performance filtration.
- Electronic regulation and programming (timer).
- Delivered with RC5 remote control.



ALASKA Series

		WN 7	WN 9	WN 12	WAF 18
		WN 7RC	WN 9RC	WN 12RC	WAF 18RC
Cooling capacity	kW	2,32	2,76	3,6	5,15
Power input	kW	0,72	0,84	1,12	1,70
EER / Energy label		3,2 / B	3,3 / A	3,2 / A	3 / B
Operating limit outdoor temperature	°C	21°/ 46° Dry Bulb			
Heating capacity	kW	2,31	3,07	3,84	5,35
Heating capacity at -10° out.	kW	1,09	1,43	1,12	2,7
Power input	kW	0,68	0,9	1,17	1,65
COP / Energy label		3,4 / B	3,4 / B	3,4 / B	3,2 / C
Operating limit outdoor temperature	°C	-10°/ 24° Bulbe Sec			

Indoor units		ST WN 7	ST WN 9	ST WN 12	ST WAF 18
Air flow (LS/HS)	m³/h	320/390	360/450	460/620	590/720
Acoustic pressure at 1m (LS/HS)	dB(A)	32/37	35/41	33/40	37/43
Dehumidification	l/h	0,8	1,2	1,5	2,2
Weight	kg	7	8	8	11
Dimensions (WxDxH)	mm	680x180x250	680x180x250	840x180x250	900x295x200

Outdoor units		GC 7 A GC 7 ARC	GC 9 A GC 9 ARC	GC 12 A GC 12 ARC	GC 18 A GC 18 ARC
Air flow	m³/h	1200	1370	1450	2160
Acoustic pressure at 1m	dB(A)	53	51	54	54
Compressor type		Rotary	Rotary	Rotary	Rotary
Weight	kg	27,5	33,5	38	43
Dimensions (WxDxH)	mm	610x240x520	830x245x545	830x245x545	795x290x610

Linking specifications between indoor and outdoor units					
Power supply 1~230 V					
Power supply side		Indoor	Indoor	Indoor	Indoor
Power cable section	mm²	3x1,5	3x1,5	3x1,5	3x1,5
Fuse rating am	A	10	10	10	16
Electrical connections	mm²	4x1	4x1	4x1	4x1,5
Electrical connections	mm²	5x1	5x1	5x1	5x1,5
Linking pipes					
Max. lenght	m	10	15	15	15
Max. height difference	m	7	7	7	7
Suction pipe diameter	Inches	3/8"	3/8"	3/8"	1/2"
Liquid pipe diameter	Inches	1/4"	1/4"	1/4"	1/4"

Airwell



Your approved *Airwell* distributor

ACE MARKETING SAS - 1 bis, av. du 8 mai 1945 - Saint-Quentin-en-Yvelines
 F - 78284 Guyancourt Cedex
 Fax : +33 (0) 1 39 44 65 17 - Tél. : +33 (0) 1 39 44 78 00 - e-mail : contact@airwell.com
www.airwell.com