

WN / WAF

WALL MOUNTED

4 Cooling models
From 2,3 kW to 5,1 kW
4 Heat Pump models
From 2,3 kW to 5,3 kW

INDOOR UNIT **WN 7-9-12**



PRODUCT ADVANTAGES

- Sober and unobtrusive design.
- Easy to install and operate.
- R410A high efficiency fluid.
- Class B energy label (depending on models).
- High efficiency filtration.
- Automatic treated air sweeping.
- Electronic regulation and programming.
- Condensate drainage lift pump (accessory).
- Supplied with RC5 remote control.

INDOOR UNIT **WAF 18**



OUTDOOR UNIT
GC 7 A



RC5



OUTDOOR UNIT
GC 9-12 A



OUTDOOR UNIT
GC 18 A





WN / WAF

		WN 7	WN 9	WN 12	WAF 18	
	Indoor Units	ST WN 7	ST WN 9	ST WN 12	ST WAF 18	
	Outdoor Units	GC 7 A	GC 9 A	GC 12 A	GC 18 A	
	Outdoor Units	GC 7 ARC	GC 9 ARC	GC 12 ARC	GC 18 ARC	
Cooling	Capacity	kW 2,32	2,76	3,6	5,15	
	Input power	kW 0,72	0,84	1,12	1,70	
	EER/Energy Label	3,2 / A	3,3 / A	3,2 / A	3 / B	
	Operating limits	°C -10° / 46° Dry Bulb	21° / 46° Dry Bulb	21° / 46° Dry Bulb	21° / 46° Dry Bulb	
	Capacity	kW 2,31	3,07	3,84	5,35	
Heating	Capacity at -15°C	kW 1,09	1,43	1,12	2,7	
	Input power	kW 0,68	0,9	1,17	1,65	
	COP/Energy Label	3,4 / B	3,4 / B	3,4 / B	3,2 / C	
	Operating limits	°C -10° / 24° Dry Bulb	-10° / 24° Dry Bulb	-10° / 24° Dry Bulb	-10° / 24° Dry Bulb	
	Sound pressure level 1 mt ¹	dB(A) 32/37	35/41	33/40	37/43	
Indoor unit	Sound power level ¹	dB(A) 44/50	49/53	47/53	50/55	
	Airflow ¹	m ³ /h 320/390	360/450	460/620	590/720	
	Dehumidification	l/h 0,8	1,2	1,5	2,2	
	Dimensions (WxDxH)	mm 680x180x250	680x180x250	840x180x250	900x200x295	
	Weight	kg 7	7	8	11	
	Part number	7SP022727	7SP022728	7SP022729	7SP022308	
	Price	€				
	Outdoor unit	Sound pressure level 1 mt	dB(A) 53	51	54	54
		Sound power level	dB(A) 62	61	65	65
		Airflow	m ³ /h 1200	1370	1450	2160
Compressor type		Rotary	Rotary	Rotary	Rotary	
Dimensions (WxDxH)		mm 610x240x520	830x245x545	830x245x545	795x290x610	
Power supply 1-230V-50Hz	Weight	kg 27,5	33,5	38	43	
	Part number	7SP061581	7SP061582	7SP061583	7SP061584	
	Price	€				
Power supply 1-230V-50Hz	Full set price	€				
	Part number	7SP061585	7SP061586	7SP061587	7SP061588	
Power supply 1-230V-50Hz	Price	€				
	Full set price	€				
Power supply 1-230V-50Hz	Power supply side	Indoor	Indoor	Indoor	Indoor	
	Power cable section	mm ² 3x1,5	3x1,5	3x1,5	3x1,5	
	Fuse rating am	A 10	10	10	16	
	Electrical connections	mm ² 4x1,5	4x1,5	4x1,5	4x1,5	
	Electrical connections	mm ² 5x1,5	5x1,5	5x1,5	5x1,5	
	Pipe line	Suction pipe diameter	inches 3/8"	3/8"	3/8"	1/2"
	Liquid pipe diameter	inches 1/4"	1/4"	1/4"	1/4"	
	Max lenght	m 10	15	15	15	
	Max height	m 7	7	7	7	

¹Data are relative to Low speed, Medium speed and High speed

Accessories	WN 7	WN 9	WN 12	WAF 18
Mounting bracket	7ACTL0016 €			-
	7ACTL0018 €	-	-	-