

XLF

LOW / HIGH WALL MOUNTED

2 Cooling models
From 2,5 kW to 3,3 kW
2 Heat Pump models
From 2,8 kW to 3,3 kW



BLOWN AIR IN 4 DIRECTIONS

Treated air is distributed in four directions. The user can direct the treated air to optimise comfort levels, depending on the chosen operating mode:

Cooling mode: air blown upwards falls back down evenly to cool the room.

Heating mode: air blown towards the floor rises progressively to spread more effectively throughout the room.

Side blowing: ensures uniform air distribution throughout the room without creating the feeling of draughts.

INDOOR UNIT **XLF 9-12**




PRODUCT ADVANTAGES

- Low or high wall mounted installation.
- Innovative, ultra-compact design (only 14 cm deep).
- High performance filtration.
- Electronic regulation and programming.
- Treated air distribution from all 4 sides.
- Ultra-quiet operation.
- Compatible with Multisplits DUO 9-9 / 9-12 / 12-12.
- Compatible with water condenser unit GCAO N.
- Supplied with RC4 remote control.

* Wall mounted RCW2 remote control (Optional)

OUTDOOR UNIT
GCNG 9-12



RC4

RCW2*





XLF

		XLF 9	XLF 12
	Indoor Units	ST XLF 9	ST XLF 12
	Outdoor Units	GCNG 9	GCNG 12
	Outdoor Units	GCNG 9 RC	GCNG 12 RC
Cooling	Capacity	2,6	3,3
	Input power	0,8	1,09
	EER/Energy Label	3,2 / A	3,0 / B
	Operating limits	21° / 46° Dry Bulb	21° / 46° Dry Bulb
Heating	Capacity	2,8	3,7
	Input power	0,83	1,21
	COP/Energy Label	3,4 / B	3,0 / D
	Operating limits	-9° / 24° Dry Bulb	-9° / 24° Dry Bulb
Indoor unit	Sound pressure level 1 mt ¹	31/33/35	32/35/39
	Sound power level ¹	44/46/48	44/47/51
	Airflow ¹	330/360/390	310/360/430
	Dehumidification	l/h	1,2
	Dimensions (WxDxH)	mm	570x160x570
	Weight	kg	13,5
	Part number	7SP022714	7SP022715
	Price	€	
Outdoor unit	Sound pressure level 1 mt	53	51
	Sound power level	62	61
	Airflow	m ³ /h	1780
	Compressor type	Rotary	Rotary
	Dimensions (WxDxH)	mm	795x290x610
Power supply 1-230V-50Hz	Part number	7SP061441	7SP061442
	Price	€	
	Full set price	€	
Power supply 1-230V-50Hz	Part number	7SP061429	7SP061430
	Price	€	
	Full set price	€	
Power supply 1-230V-50Hz	Power supply side	Indoor	Indoor
	Power cable section	mm ²	3x1,5
	Fuse rating am	A	10
	Electrical connections	mm ²	4x1,5
	Electrical connections	mm ²	5x1,5
Pipe line	Suction pipe diameter	inches	3/8"
	Liquid pipe diameter	inches	1/4"
	Max lenght	m	15
	Max height	m	7

¹Data are relative to Low speed, Medium speed and High speed

Accessories		XLF 9	XLF 12
Mounting bracket	7ACTL0016	€ -	
Remote control RCW2	7ACEL1212	€	