




CD
DUCTED
 1 Heat Pump model
 of 18,1 kW




PRODUCT ADVANTAGES

- Suspended ceiling installation.
- Horizontal mounting.
- Reusable air filter.
- Pressure available for connection to a duct network.
- High available static pressure.
- Supplied with RC4 remote control.

* Wall mounted RCW2 remote control (Optional)



		CD 60
Indoor Unit		ST CD 60
Outdoor Unit		GC CD 60 RC
Cooling	Capacity	16.4 kW
	Input power	5.52 kW
	EER/Energy Label	2.97
	Operating limits	21°/ 46° Dry Bulb °C
Heating	Capacity	18.1 kW
	Input power	5.17 kW
	COP/Energy Label	3.5
	Operating limits	-9°/ 24° Dry Bulb °C
Indoor unit	Sound pressure level 1 mt ¹	55/59/61 dB(A)
	Sound power level ¹	67/71/73 dB(A)
	Airflow ¹	2430/3050/3265 m ³ /h
	Static pressure ¹	120/200 Pa
	Dehumidification	4.6 l/h
	Dimensions (WxDxH)	1350x400x640 mm
	Weight	75 kg
	Part number	7SP032091
	Price	€
	Outdoor unit	Sound pressure level 1 mt ¹
Sound power level ¹		64/70 dB(A)
Airflow		4650/5500 m ³ /h
Compressor type		Scroll
Dimensions (WxDxH)		900x340x1255 mm
Power supply 3-400V - 50 Hz	Part number	7SP0711401
	Price	€
	Full set price	€
Power supply 3-400V - 50Hz	Power supply side	Outdoor
	Power cable section	mm ²
	Fuse rating am	A
	Electrical connections	mm ²
Pipe line	Suction pipe diameter	7/8"
	Liquid pipe diameter	1/2"
	Max lenght	50 m
	Max height	25 m



Accessories **CD 60**

Remote control 7ACEL1212 € - RCW2

¹Data are relative to Low speed, Medium speed and High speed