



## CD

### DUCTED

1 Heat Pump model  
of 18,1 kW

INDOOR UNIT **CD 60**



### PRODUCT ADVANTAGES

- Suspended ceiling installation.
- Horizontal mounting.
- Reusable air filter.
- Pressure available for connection to a duct network.
- High available static pressure.
- Supplied with RC7 remote control.

\* Wall mounted RCW2 remote control (Optional)

RECEIVER

RC7



RCW-2\*



OUTDOOR UNIT **YCF055**



### Accessories

**CD 60**

Remote control 7ACEL1212 € -  
RCW2

	Indoor Unit	CD 60
	<b>Outdoor Unit</b>	<b>ST CD 60</b>
		<b>AWAU-YCF055H13</b>
<b>Cooling</b>	<b>Capacity</b>	<b>16.4</b> kW
	Power input	5.52 kW
	EER	2.97 / C
	Operating limits	21° / 46° Dry Bulb °C
<b>Heating</b>	<b>Capacity</b>	<b>18.1</b> kW
	Power input	5.17 kW
	COP	3.5 / B
	Operating limits	-9° / 24° Dry Bulb °C
<b>Indoor unit</b>	Sound pressure level 1 mt <sup>1</sup>	50/55/58 dB(A)
	Sound power level <sup>1</sup>	67/71/73 dB(A)
	Airflow <sup>1</sup>	2510/3150/3380 m <sup>3</sup> /h
	Static pressure <sup>2</sup>	120/200 Pa
	Dehumidification	l/h 4.6
	Dimensions (WxDxH)	1350x640x400 mm
	Weight	75 kg
	<b>Part number</b>	<b>7SP032091</b>
	<b>Price</b>	€
	<b>Outdoor unit</b>	Sound pressure level 1 mt
Sound power level		71 dB(A)
Airflow		5500 m <sup>3</sup> /h
Compressor type		Rotary
Dimensions (WxDxH)		900x340x1255 mm
Weight		110 kg
<b>Power supply 3-400V - 50 Hz</b>	<b>Part number</b>	<b>7SP061751</b>
	<b>Price</b>	€
	<b>Full set price</b>	€
<b>Power supply 3-400V - 50Hz</b>	Power supply side	Outdoor
	Power cable section	5x2,5 mm <sup>2</sup>
	Fuse rating	3x25 A
	Electrical connections	6x1,5 mm <sup>2</sup>
	Suction pipe diameter	3/4" inches
<b>Pipe line</b>	Liquid pipe diameter	1/2" inches
	Max lenght	50 m
	Max height	25 m

<sup>1</sup>Data are relative to Low speed, Medium speed and High speed

<sup>2</sup>Nominal/Max