




CD
DUCTED
 1 Heat Pump model
 of 18,1 kW



PRODUCT ADVANTAGES


- Suspended ceiling installation.
- Horizontal mounting.
- Reusable air filter.
- Pressure available for connection to a duct network.
- High available static pressure.
- Supplied with RC4 remote control.

* Wall mounted RCW2 remote control (Optional)



		CD 60
Indoor Unit		ST CD 60
Outdoor Unit		GC CD 60 RC
Cooling	Capacity	16.4 kW
	Power input	5.52 kW
	EER	2.97
	Operating limits	21°/ 46° Dry Bulb °C
Heating	Capacity	18.1 kW
	Power input	5.17 kW
	COP	3.5
	Operating limits	-9°/ 24° Dry Bulb °C
Indoor unit	Sound pressure level 1 mt ¹	50/55/58 dB(A)
	Sound power level ¹	67/71/73 dB(A)
	Airflow ¹	2430/3050/3265 m ³ /h
	Static pressure ²	120/200 Pa
	Dehumidification	4.6 l/h
	Dimensions (WxDxH)	1350x640x400 mm
	Weight	75 kg
	Part number	7SP032091
	Price	€
	Outdoor unit	Sound pressure level 1 mt ¹
Sound power level ¹		64/70 dB(A)
Airflow ¹		4650/5500 m ³ /h
Compressor type		Scroll
Dimensions (WxDxH)		900x340x1255 mm
Power supply 3-400V - 50 Hz	Part number	7SP0711401
	Price	€
	Full set price	€
Power supply 3-400V - 50Hz	Power supply side	Outdoor
	Power cable section	5x2,5 mm ²
	Fuse rating	3x20 A
	Electrical connections	6x1,5 mm ²
Pipe line	Suction pipe diameter	7/8" inches
	Liquid pipe diameter	1/2" inches
	Max lenght	50 m
	Max height	25 m

¹Data are relative to Low speed, Medium speed and High speed
²Nominal/Max



Accessories	CD 60
Remote control 7ACEL1212	€ -
RCW2	