

DAF

| | | DAF 009 | DAF 012 | DAF 018 | DAF 024 | DAF 030 | DAF 036 | DAF 042 | DAF 060 |
|-------------------------------------|--|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|
| Indoor Units | | AWSI-DAF009-N11 | AWSI-DAF012-N11 | AWSI-DAF018-N11 | AWSI-DAF024-N11 | AWSI-DAF030-N11 | AWSI-DAF036-N11 | AWSI-DAF042-N11 | AWSI-DAF060-N11 |
| Outdoor Units 1-230V - 50 Hz | | AWAU-YIF009-H11 | AWAU-YIF012-H11 | AWAU-YIF018-H11 | AWAU-YIF024-H11 | AWAU-YIF030-H11 | AWAU-YIF036-H11 | AWAU-YIF042-H13 | AWAU-YIF060-H13 |
| Outdoor Units 3-400V - 50 Hz | | | | | | | AWAU-YIF036-H13 | | |
| Cooling | Capacity | 2,60 | 3,50 | 5,00 | 7,00 | 8,30 | 10,00 | 12,00 | 16,00 |
| | Power input | 1,00 | 1,20 | 2,10 | 2,66 | 3,00 | 4,00 | 5,30 | 6,50 |
| | EER/Energy Label | 2,60 | 2,91 | 2,38 | 2,63 | 2,76 | 2,50 | 2,26 | 2,46 |
| | Outdoor temperature operating limits | 187° 43° Dry bulb | 187° 43° Dry bulb | 187° 43° Dry bulb | 187° 43° Dry bulb | 187° 43° Dry bulb | 187° 43° Dry bulb | 187° 43° Dry bulb | 187° 43° Dry bulb |
| Heating | Capacity | 2,85 | 3,60 | 5,70 | 8,00 | 9,10 | 11,00 | 14,00 | 18,50 |
| | Input power | 0,97 | 1,10 | 1,80 | 2,51 | 3,00 | 3,50 | 4,90 | 5,50 |
| | COP/Energy Label | 2,93 | 3,27 | 3,16 | 3,18 | 3,03 | 3,14 | 2,85 | 3,36 |
| | Outdoor temperature operating limits | | | | -77° 24° Dry bulb | | | | |
| Indoor unit | Sound pressure level to 1 m (LS/MS/HS) | 34/36/37 | 36/38/40 | 38/40/42 | 40/42/44 | 40/42/44 | 46/48/50 | 46/48/50 | 48/50/53 |
| | Sound power level (LS/MS/HS) | 44/46/47 | 46/48/50 | 48/50/52 | 50/52/54 | 50/52/54 | 56/58/60 | 56/58/60 | 58/60/63 |
| | Airflow (LS/MS/HS) | 400/470/550 | 490/540/600 | 680/750/840 | 1220/1350/1400 | 1200/1320/1400 | 1380/1650/2000 | 1380/1650/2000 | 1800/2100/2500 |
| | Dehumidification | 1 | 1,3 | 1,9 | 2,4 | 2,5 | 2,9 | 4,3 | 4,7 |
| | Dimensions (WxDxH) | 913x680x220 | 913x680x220 | 1012x736x266 | 1270x504x268 | 1270x530x268 | 1251x744x290 | 1251x744x290 | 1251x788x330 |
| | Weight | 27 | 27 | 36 | 37 | 37 | 57 | 57 | 66 |
| | Part number | 7SP032114 | 7SP032115 | 7SP032116 | 7SP032117 | 7SP032118 | 7SP032119 | 7SP032120 | 7SP032121 |
| | Price | € | | | | | | | |
| Outdoor unit | Sound pressure level to 1 m | 55 | 56 | 56 | 59 | 59 | 60 | 60 | 64 |
| | Sound power level | 65 | 66 | 66 | 69 | 69 | 70 | 70 | 74 |
| | Airflow | 2800 | 2800 | 2800 | 3200 | 4200 | 4000 | 6000 | 6000 |
| | Compressor type | Rotary | Rotary | Rotary | Rotary | Rotary | Scroll | Scroll | Scroll |
| | Dimensions (WxDxH) | 848X320X540 | 848X320X540 | 848X320X540 | 1018X412X700 | 980X427X790 | 1018X412X840 | 950x412x1250 | 950x412x1250 |
| Weight | 32 | 32 | 40 | 59 | 70 | 90 | 112 | 123 | |
| P. supply | Part number | 7SP061778 | 7SP061779 | 7SP061780 | 7SP061781 | 7SP061782 | 7SP061783 | | |
| 1~230V - 50 Hz | Price | € | | | | | | | |
| P. supply | Part number | | | | | | 7SP061784 | 7SP061785 | 7SP061786 |
| 3~400V - 50 Hz | Price | € | | | | | | | |
| Power supply 1~230V - 50 Hz | Power supply side | Indoor & Outdoor | Indoor & Outdoor | Indoor & Outdoor | Indoor & Outdoor | Indoor & Outdoor | Indoor & Outdoor | Indoor & Outdoor | Indoor & Outdoor |
| | Power cable section | 3X1,0 - 3X1,5 | 3X1,0 - 3X1,5 | 3X1,0 - 3X2,5 | 3X1,0 - 3X4,0 | 3X1,0 - 3X6,0 | 3X1,5 - 3X6,0 | | |
| | Fuse rating | 6 - 10 | 6 - 16 | 6 - 20 | 6 - 25 | 6 - 32 | 10 - 40 | | |
| | Electrical connections | mm² | 2x0.75 | 2x0.75 | 2x0.75 | 2x0.75 | 2x0.75 | 2x0.75 | |
| Power supply 3~400V - 50 Hz | Power supply side | Indoor & Outdoor | Indoor & Outdoor | Indoor & Outdoor | Indoor & Outdoor | Indoor & Outdoor | Indoor & Outdoor | Indoor & Outdoor | Indoor & Outdoor |
| | Power cable section | | | | | | 3X1,5 - 5X2,5 | 3X1,5 - 5X2,5 | 3X1,5 - 5X2,5 |
| | Fuse rating | | | | | | 10-16 | 10 - 20 | 10 - 20 |
| | Electrical connections | mm² | | | | | 2x0.75 | 2x0.75 | 2x0.75 |
| Pipe Line | Suction pipe diameter | inches 3/8" | 1/2" | 1/2" | 5/8" | 5/8" | 3/4" | 3/4" | 3/4" |
| | Liquid pipe diameter | inches 1/4" | 1/4" | 1/4" | 3/8" | 3/8" | 1/2" | 1/2" | 1/2" |
| | Max length | m 20 | 20 | 20 | 30 | 30 | 50 | 50 | 50 |
| | Max height | m 15 | 15 | 15 | 15 | 15 | 30 | 30 | 30 |