

## **CAPWELL RANGE DC INVERTER DUCTED UNITS**

1 Heat Pump model of 16 kW





## **PRODUCT ADVANTAGES**

- Suitable solution for residential and light commercial ducted air conditioning.
- High level DC inverter system of 6HP (14kW) combined with ducted indoor unit.
- The outdoor unit is only 1250mm height.
- Quiet operation thanks to a large aerodynamic designed fans of 500 mm diameter.
- Variable cooling and heating capacity from 30% to 115% (of rated capacity).
- High COP "A" class energy rating.
- Emergency Water-float to prevent over flow at indoor
- Internal crankcase heater combined with compressor motor windings.
- Ready for base heater and additional crank case heater installation including software support.
- Compatible with Airconet regulation
- Dry contact output and inputs Standby, Night mode, Power shedding and Alarm.
- HMI Display consists of 7-segments shows system diagnostics and setup.
- Monitoring software (PC port for high level service).
- Operating range Cooling: From -10°C to 46°C outdoors.
- Operating range Heating: From -15°C to 24°C outdoors.
- Brushless compressor and outdoor fan motors.
- High available static pressure.
- Supplied with RC4 remote control.
- \* Wall mounted RCW2 remote control (Optional)















## **CAPWELL CD DCI**

			CD 60 DCI	
	Indoor Units		ST CD 60 DCI	
	Outdoor Units		GC 60 DCI	
٠ انسب	Capacity	kW	14,0	
Cooling	Power input	kW	4,2	
	EER/Energy Label		3,3 / A	
	Operating limits	°C	11,4	
Heating	Capacity	kW	16,0	
Heating	Power input	kW	4,4	
	COP/Energy Label		3,6 / A	
	Operating limits	°C	-10°/ 46° Dry Bulb	
Indoor	Sound pressure level 1 mt <sup>1</sup>	dB(A)	50/55/58	
ınaoor unit	Sound power level <sup>1</sup>	dB(A)	66/70/73	
unit	Airflow <sup>1</sup>	m³/h	555/805/917	
	Dehumidification	l/h	4.0	
	Dimensions (WxDxH)	mm	740x400x1350	
	Weight	kg	75	
	Part number		7SP032111	
	Price	€		
Outdoor	Sound pressure level 1 m <sup>-1</sup>	dB(A)	56/58	
unit	Sound power level <sup>1</sup>	dB(A)	68/70	
	Airflow <sup>1</sup>	m³/h	5700	
	Compressor type		Rotary	
	Dimensions (WxDxH)	mm	900x340x1255	
	Weight	kg	110	
ower supply -230V-50Hz	Part number		7SP071402	
I-230V-50Hz	Price	€		
	Full set price	€		
	Power supply side		Outdoor	
Power supply 1-230V-50Hz	Power cable section	mm²	3x6,0	
	Fuse rating	А	32	
	Electrical connections	mm²	3x1,5	
	Suction pipe diameter	inches	3/4"	
Pipe line	Liquid pipe diameter	inches	3/8"	
	Max lenght	m	70	
	Max height	m	30	
	<sup>1</sup> Data are relative to Low speed, Med	dium speed and High speed		

Accessories			CD 60 DCI
Base Heater	439878	€	
Room thermostat +	442298+442296	€	
Extension Cable (Shielded)			
RCW Wall Mounted	7ACEL1157	€	
Remote Control			
Remote control RCW2	7ACEL1212	€	