



CCE

COLUMN SPLIT SYSTEM

1 Heat pump model of 15 kW

INDOOR UNIT **CCE 45**



Multifunction control panel

- Automatic Cooling/ Heating regulation.
- 3 fan (ventilation) speeds.
- Automatic ventilation.
- Night time low running (SLEEP) function.
- Dehumidification mode.
- Programming (TIMER) function.
- LCD display.

PRODUCT ADVANTAGES

- Multifunction control panel with LCD display.
- High efficiency filtration.
- Clogged filter indicator.
- Ioniser.
- Automatic treated air sweeping.
- Air range: 12 m.
- Electronic regulation and programming.
- Scroll compressor.
- Phase controller.
- Refrigeration pipe lengths up to 40 m.

OUTDOOR UNIT **GC CCE 40 RC**



		CCE 45	
		ST CCE 45	
		GC CCE 40 RC	
Cooling	Capacity	kW	12,9
	Input power	kW	4,82
	EER/Energy Label		2,7 / D
	Operating limits	°C	21°/ 46° Dry Bulb
Heating	Capacity	kW	15
	Input power	kW	4,57
	COP/Energy Label		3,2 / C
	Operating limits	°C	-9°/ 24° Dry Bulb
Indoor unit	Sound pressure level 1 mt ¹	dB(A)	52/56
	Airflow	m ³ /h	2000
	Dimensions (WxDxH)	mm	600x370x1900
	Weight	kg	70
Part number		7SP022234	
Price		€	
Outdoor unit	Sound pressure level 1 mt	dB(A)	69
	Airflow	m ³ /h	4200
	Compressor type		Scroll
	Dimensions (WxDxH)	mm	900x340x970
Weight	kg	95	
Power supply 3-400V-50Hz	Part number		7SP061521
	Price		€
	Full set price		€
Power supply 3-400V-50Hz	Power supply side		Outdoor
	Power cable section	mm ²	5x2,5
	Fuse rating am	A	10
	Electrical connections	mm ²	6x2,5
Pipe line	Suction pipe diameter	inches	3/4"
	Liquid pipe diameter	inches	3/8"
	Max lenght	m	40
	Max height	m	20

¹Data are relative to Low speed and High speed