

# FSF

			FSF045
Indoor Units			AWSI-FSF045-N11
Outdoor Units			AWAU-YFF045-H13
<b>Cooling</b>	<b>Capacity</b>	<b>kW</b>	12.4
	Input power	kW	4,94
	EER/Energy Label		2,51
	Outdoor temperature operating limits	°C	18/43°C Dry Bulb
<b>Heating</b>	<b>Capacity</b>	<b>kW</b>	13,6
	Dehumidification	l/h	6
	Input power	kW	4,84
	COP/Energy Label		2,81
Outdoor temperature operating limits			-7/24°C Dry Bulb
<b>Indoor unit</b>	Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	46/48/50/52
	Sound power level (LS/MS/HS/SS)	dB(A)	56/58/60/62
	Airflow (LS/MS/HS/SS)	m3/h	1350/1500/1650/1800
	Dimensions (WxDxH)	mm	518x395x1870
	Weight	kg	63
	<b>Part number</b>		<b>7SP011082</b>
<b>Outdoor unit</b>	Sound pressure level to 1 m	dB(A)	59
	Sound power level	dB(A)	69
	Airflow	m3/h	4000
	Compressor type		Scroll
	Dimensions (WxDxH)	mm	1032x412x1250
	Weight	kg	110
P. supply	<b>Part number</b>		7SP061802
3~400V - 50 Hz	<b>Price</b>	€	
3~400V - 50 Hz	<b>Full set Price</b>	€	
<b>Power supply 3~400V - 50 Hz</b>	Power supply side		Outdoor
	Power cable section	mm2	5x2,5
	Fuse rating am	A	25
	Electrical connections	mm2	3x1.0+5x1.0+4x1.0
<b>Pipe Line</b>	Suction pipe diameter	inches	3/4"
	Liquid pipe diameter	inches	1/2"
	Max lenght	m	10
	Max height	m	5