



YAZ

PREMIUM MULTI DUO/TRIO/QUATTRO/CINCO

- > Capacity range. Available in 5 capacities from 4.1 up to 10 kW.
- > DC Inverter and sine wave compressor drive technology.

PRODUCT ADVANTAGES

- > Flexy match with wide range of indoor unit including PNXA, XLD, SX, CK, DLS, DLF lines (for the IDU price, refer to monosplit table on page 14).
- > Precharge to maximum tubing length up to 80 m.
- > Possibility to connect to alarm output, unit ON/OFF, night mode and power consumption level.
- > Fuzzy logic for precise capacity balance between indoor unit under operation.
- > Same indoor for multi and single application.



YAZ TECHNICAL DATA

	Outdoor Units		AWAU-YAZ214-H11	AWAU-YAZ218-H11	AWAU-YAZ318-H11	AWAU-YAZ324-H11	AWAU-YAZ430-H11	AWAU-YAZ536-H11
COOLING	Capacity	kW	4.1 (1.2-6.4)	5 (1.2-6.4)	5.20 (1.0-6.6)	7.35 (1.3-9)	8 (1.4-9.2)	10,0 (4,3-11,0)
	Input power	kW	1.06	1.47	1.46	2.24	2.38	2,94
	EER/Energy Label		3.88/A	3,4/A	3.56/A	3.28/A	3.36/A	3,4 / A
	Outdoor temperature operating limits	°C	-10°/ 46° Dry bulb					
HEATING	Capacity	kW	6.0 (1.0-6.8)	6.0 (1.0-6.8)	6.60(1.0-8.15)	9.2 (0.95-11)	9.8 (0.95-11)	11,0 (2,0-12,0)
	Capacity at -15°C	kW	3.7	3.7	4.0	5.4	5.7	
	Input power	kW	1.66	1.66	1.71	2.31	2.36	4,3
	COP/Energy Label		3.61/A	3.61/A	3.86/A	3.98/A	4.15/ A	4,0 / A
	Outdoor temperature operating limits	°C	-15°/ 24° Dry bulb					
OUTDOOR UNIT	Sound pressure level to 1 m	dB(A)	53	53	56	57	57	58/59
	Sound power level	dB(A)	63	63	67	69	69	68/70
	Airflow	m³/h	2160	2160	2860	3600	3600	4150
	Compressor type		Rotary DCI	Rotary DCI	Twin Rotary DCI	Twin Rotary DCI	Twin Rotary DCI	Twin Rotary DCI
	Dimensions (WxDxH)	mm	795x290x610	795x290x610	846x302x690	950x413x864	950x413x864	970x340x900
	Weight	kg	39	39	48	69	70	81,5
	Part number		7SP091154	7SP091150	7SP091153	7SP091149	7SP091151	7SP091152
POWER SUPPLY 1~230V - 50 Hz	Power supply side		Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
	Power cable section	mm²	3x2.5	3x2.5	3x2.5	3x2.5	3x2.5	3x4
	Fuse rating am	A	20	20	20	25	25	25
	Electrical connections	mm²	2x(4x1.5)	2x(4x1.5)	3x(4x1.5)	3x(4x1.5)	4x(4x1.5)	5x(4x1.5)
PIPE LINE	Suction pipe diameter	inches	2x3/8"	2x3/8"	3x3/8"	2x3/8" + 1x1/2"	3x3/8" + 1x1/2"	3x3/8" + 2x1/2"
	Liquid pipe diameter	inches	2x1/4"	2x1/4"	3x1/4"	3x1/4"	4x1/4"	5x1/4"
	Max lenght	m	30	30	30	50	70	80
	Max lenght per circuit	m	25	25	25	25	25	25
	Max height between indoor and outdoor units	m	10	10	15	15	15	15
	Max height between indoor units	m	5	5	15	15	15	15

AIRWELL SOLUTIONS



CAPACITY COMBINATION



Indoor units combinations	COOLING										HEATING											
	Capacity (kW)				Power input (kW)			EER/ Energy label	Capacity (kW)				Power input (kW)			COP/ Energy label						
	A	B	C	D	Totale	Min	Max		Nom.	Min	Max	A	B	C	D		Totale	Min	Max	Nom.	Min	Max
7	2200				2200	1200	2500	600	420	900	3.67/A	2600				2600	1000	3000	720	375	800	3.61/A
9	2500				2500	1200	3600	700	420	1000	3.57/A	3000				3000	1000	4000	830	375	1500	3.61/A
12	3500				3500	1200	4300	1000	420	1200	3.50/A	4000				4000	1000	4500	1100	375	1700	3.64/A
7+7	2050	2050			4100	1700	5000	1056	500	1800	3.88/A	2200	2200			4400	1700	5000	1200	500	1800	3.67/A
7+9	1790	2310			4100	1700	5800	1056	500	2000	3.88/A	2060	2640			4700	1700	5800	1300	500	1800	3.62/A
7+12	1510	2590			4100	1800	6000	1056	550	2100	3.88/A	2210	3790			6000	1800	6000	1660	550	1800	3.61/A
9+9	2050	2050			4100	1800	6000	1056	550	2100	3.88/A	3000	3000			6000	2000	6500	1660	580	1800	3.61/A
9+12	1760	2340			4100	1800	6300	1056	550	2130	3.88/A	2570	3430			6000	2000	6650	1660	580	1890	3.61/A
12+12	2050	2050			4100	1800	6400	1056	550	2130	3.88/A	3000	3000			6000	2000	6800	1660	580	1890	3.61/A

Based on wall mounted combination



Indoor units combinations	COOLING										HEATING											
	Capacity (kW)				Power input (kW)			EER/ Energy label	Capacity (kW)				Power input (kW)			COP/ Energy label						
	A	B	C	D	Totale	Min	Max		Nom.	Min	Max	A	B	C	D		Totale	Min	Max	Nom.	Min	Max
7	2200				2200	1200	2500	600	420	900	3.67/A	2600				2600	1000	3000	720	375	800	3.61/A
9	2500				2500	1200	3600	700	420	1000	3.57/A	3000				3000	1000	4000	830	375	1500	3.61/A
12	3500				3500	1200	4300	1000	420	1200	3.50/A	4000				4000	1000	4500	1100	375	1700	3.64/A
7+7	2200	2200			4400	1700	5000	1200	500	1800	3.67/A	2200	2200			4400	1700	5000	1200	500	1800	3.67/A
7+9	2060	2640			4700	1700	5800	1300	500	2000	3.62/A	2060	2640			4700	1700	5800	1300	500	1800	3.62/A
7+12	1840	3160			5000	1800	6000	1470	550	2100	3.40/A	2210	3790			6000	1800	6000	1660	550	1800	3.61/A
9+9	2500	2500			5000	1800	6000	1470	550	2100	3.40/A	3000	3000			6000	2000	6500	1660	580	1800	3.61/A
9+12	2140	2860			5000	1800	6300	1470	550	2130	3.40/A	2570	3430			6000	2000	6650	1660	580	1890	3.61/A
12+12	2500	2500			5000	1800	6400	1470	550	2130	3.40/A	3000	3000			6000	2000	6800	1660	580	1890	3.61/A

Based on wall mounted combination

YAZ3-18



Indoor units combinations	COOLING										HEATING											
	Capacity (kW)				Power input (kW)			EER/ Energy label	Capacity (kW)				Power input (kW)			COP/ Energy label						
	A	B	C	D	Totale	Min	Max		Nom.	Min	Max	A	B	C	D		Totale	Min	Max	Nom.	Min	Max
7	2200				2200	1000	2600	645	450	750	3.41/A	2600				2600	1000	3000	710	450	800	3.66/A
9	2500				2500	1100	3500	740	510	1040	3.38/A	3000				3000	1000	3500	800	450	920	3.75/A
12	3500				3500	1200	4200	1020	510	1250	3.43/A	4200				4200	1000	4500	1080	510	1160	3.89/A
7+7	2200	2200			4400	1400	5200	1170	520	1500	3.76/A	2600	2600			5200	1600	6000	1400	460	1560	3.71/A
7+9	2060	2640			4700	1450	6100	1220	530	1530	3.85/A	2450	3150			5600	1600	6500	1600	460	1750	3.50/A
7+12	1920	3280			5200	1720	6200	1460	610	1910	3.56/A	2430	4170			6600	2000	7500	1710	510	1900	3.86/A
9+9	2500	2500			5000	1710	6200	1400	610	1910	3.57/A	3000	3000			6000	1800	7000	1600	480	1750	3.75/A
9+12	2230	2970			5200	1710	6280	1460	600	1930	3.56/A	2830	3770			6600	2000	7800	1710	510	1900	3.86/A
12+12	2600	2600			5200	1800	6400	1460	635	2100	3.56/A	3300	3300			6600	2100	7800	1710	515	1900	3.86/A
7+7+7	1730	1730	1730		5200	1860	6400	1460	635	2100	3.56/A	2200	2200	2200		6600	2100	7800	1710	525	1900	3.86/A
7+7+9	1580	1580	2030		5200	1870	6400	1460	635	2100	3.56/A	2010	2010	2580		6600	2100	7800	1710	525	1900	3.86/A
7+7+12	1400	1400	2400		5200	1870	6450	1460	635	2100	3.56/A	1780	1780	3050		6600	2120	8000	1710	530	1900	3.86/A
7+9+9	1460	1870	1870		5200	1870	6450	1460	635	2100	3.56/A	1850	2380	2380		6600	2120	8000	1710	635	1900	3.86/A
7+9+12	1300	1670	2230		5200	1880	6450	1460	640	2100	3.56/A	1650	2120	2830		6600	2130	8000	1710	640	1900	3.86/A
9+9+9	1730	1730	1730		5200	1860	6450	1460	640	2100	3.56/A	2200	2200	2200		6600	2120	8000	1710	640	1900	3.86/A
9+9+12	1560	1560	2080		5200	1880	6500	1460	640	2150	3.56/A	1980	1980	2640		6600	2200	8150	1710	640	1900	3.86/A

Based on wall mounted combination

CAPACITY COMBINATION



Indoor units combinations	COOLING										HEATING											
	Capacity (kW)						Power input (kW)				EER/ Energy label	Capacity (kW)				Power input (kW)				COP/ Energy label		
	A	B	C	D	Totale	Min	Max	Nom.	Min	Max		A	B	C	D	Totale	Min	Max	Nom.		Min	Max
9	-	-		2.50	2.50	1.30	3.70	685	500	1 025	3.65/A	-	-		3.40	3.40	0.95	4.00	685	500	897	4.96/A
12	-	-		3.50	3.50	1.30	4.40	968	500	1 223	3.62/A	-	-		4.30	4.30	0.95	5.20	1 003	485	1 320	4.29/A
18	-	-		5.00	5.00	1.49	5.93	1 393	566	1 656	3.59/A	-	-		6.20	6.20	1.11	7.50	1 673	549	2 131	3.71/A
9+9	-	2.60		2.60	5.19	1.86	6.56	1 532	683	1 856	3.39/A	-	3.68		3.68	7.36	1.43	9.10	1 933	649	2 636	3.81/A
9+12	-	2.62		3.49	6.11	1.86	7.73	1 823	683	2 541	3.35/A	-	3.33		4.44	7.77	1.43	9.50	2 062	649	2 711	3.77/A
9+18	-	2.49		4.98	7.47	1.86	9.00	2 251	659	3 046	3.32/A	-	3.07		6.13	9.20	1.43	10.10	2 514	622	2 737	3.66/A
12+12	-	3.53		3.53	7.06	1.86	9.00	2 120	683	2 246	3.33/A	-	4.09		4.09	8.18	1.43	9.80	2 191	649	2 711	3.73/A
12+18	-	2.99		4.48	7.47	1.86	9.00	2 251	659	3 055	3.32/A	-	3.68		5.52	9.20	1.43	10.50	2 514	622	2 871	3.66/A
9+9+9	2.45	2.45		2.45	7.35	2.69	8.98	2 240	949	3 049	3.28/A	3.07	3.07		3.07	9.20	2.06	10.99	2 310	804	3 013	3.98/A
9+9+12	2.25	2.25		2.99	7.48	2.69	9.00	2 281	949	3 157	3.28/A	2.76	2.76		3.68	9.20	2.06	11.00	2 310	804	2 966	3.98/A
9+9+18	1.87	1.87		3.74	7.47	2.69	9.00	2 278	962	3 097	3.28/A	2.30	2.30		4.60	9.20	2.06	11.00	2 310	773	2 826	3.98/A
9+12+12	2.04	2.71		2.71	7.46	2.69	9.00	2 275	949	3 097	3.28/A	2.51	3.34		3.34	9.19	2.06	11.00	2 307	804	2 938	3.98/A
9+12+18	1.72	2.30		3.45	7.46	2.69	9.00	2 275	962	3 061	3.28/A	2.12	2.82		4.24	9.18	2.14	11.00	2 305	773	2 752	3.98/A
12+12+12	2.49	2.49		2.49	7.47	2.69	9.00	2 278	990	3 085	3.28/A	3.07	3.07		3.07	9.20	2.06	11.00	2 310	804	2 845	3.98/A
12+12+18	2.13	2.13		3.19	7.45	2.69	9.00	2 272	962	3 086	3.28/A	2.63	2.63		3.94	9.19	2.14	11.00	2 307	773	2 696	3.98/A

Based on wall mounted combination

YAZ4-30



Indoor units combinations	COOLING											HEATING										
	Capacity (kW)							Power input (kW)				EER/ Energy label	Capacity (kW)					Power input (kW)				COP/ Energy label
	A	B	C	D	Totale	Min	Max	Nom.	Min	Max	A		B	C	D	Totale	Min	Max	Nom.	Min	Max	
9	-	-	-	2.50	2.50	1.40	3.70	685	500	1 025	3.65/A	-	-	-	3.40	3.40	0.95	4.00	685	400	859	4.96/A
12	-	-	-	3.50	3.50	1.40	4.40	968	500	1 223	3.62/A	-	-	-	4.30	4.30	0.95	5.20	946	388	1 207	4.54/A
18	-	-	-	5.00	5.00	1.60	5.60	1 393	570	1 563	3.59/A	-	-	-	6.20	6.20	1.11	7.50	1 497	455	1 875	4.14/A
9+9	-	-	2.54	2.54	5.08	2.00	6.20	1 453	689	1 742	3.49/A	-	-	3.75	3.75	7.51	1.43	8.63	1 768	539	2 172	4.25/A
9+12	-	-	2.56	3.42	5.98	2.00	7.30	1 722	689	2 385	3.47/A	-	-	3.40	4.53	7.92	1.43	9.01	1 902	539	2 235	4.17/A
9+18	-	-	2.54	5.08	7.61	2.00	8.50	2 210	665	2 858	3.45/A	-	-	3.13	6.26	9.38	1.43	9.58	2 337	516	2 255	4.02/A
12+12	-	-	3.45	3.45	6.90	2.10	8.80	1 998	689	2 921	3.46/A	-	-	4.17	4.17	8.34	1.43	9.29	1 988	539	2 235	4.20/A
12+18	-	-	3.15	4.72	7.87	2.10	8.80	2 285	665	2 876	3.44/A	-	-	3.92	5.88	9.80	1.43	9.96	2 396	516	2 366	4.09/A
9+9+9	-	2.40	2.40	2.40	7.19	2.90	9.00	2 112	915	2 938	3.40/A	-	3.13	3.13	3.13	9.38	2.06	11.00	2 226	671	2 621	4.22/A
9+9+12	-	2.36	2.36	3.15	7.87	2.90	9.00	2 445	915	2 899	3.22/A	-	2.94	2.94	3.92	9.80	2.06	11.00	2 308	671	2 891	4.25/A
9+9+18	-	2.00	2.00	4.01	8.01	2.90	9.00	2 466	928	2 851	3.25/A	-	2.45	2.45	4.90	9.80	2.06	11.00	2 144	646	2 883	4.57/A
9+12+12	-	2.17	2.90	2.90	7.97	2.90	9.00	2 445	915	2 851	3.26/A	-	2.67	3.56	3.56	9.78	2.06	11.00	2 246	671	2 874	4.35/A
9+12+18	-	1.87	2.50	3.74	8.11	2.90	9.00	2 476	928	2 821	3.28/A	-	2.26	3.01	4.51	9.78	2.14	11.00	2 082	646	2 731	4.70/A
12+12+12	-	2.69	2.69	2.69	8.07	2.90	9.00	2 372	955	2 841	3.40/A	-	3.26	3.26	3.26	9.79	2.06	11.00	2 226	671	2 857	4.40/A
12+12+18	-	2.31	2.31	3.47	8.10	2.90	9.00	2 372	928	2 802	3.42/A	-	2.79	2.79	4.19	9.78	2.14	11.00	2 062	646	2 671	4.74/A
9+9+9+9	2.00	2.00	2.00	2.00	8.00	3.70	9.17	2 380	981	2 937	3.36/A	2.45	2.45	2.45	2.45	9.80	2.69	10.97	2 360	561	2 935	4.15/A
9+9+9+12	1.87	1.87	1.87	2.49	8.10	3.70	9.20	2 413	981	2 915	3.36/A	2.25	2.25	2.25	3.01	9.77	2.69	11.00	2 336	561	2 900	4.18/A
9+9+9+18	1.62	1.62	1.62	3.25	8.12	3.70	9.20	2 337	957	2 882	3.48/A	1.96	1.96	1.96	3.92	9.80	2.77	11.00	2 274	551	2 779	4.31/A
9+9+12+12	1.74	1.74	2.32	2.32	8.11	3.70	9.20	2 402	981	2 882	3.38/A	2.10	2.10	2.80	2.80	9.79	2.69	11.00	2 287	561	2 857	4.28/A
9+9+12+18	1.52	1.52	2.03	3.05	8.12	3.70	9.20	2 304	957	2 849	3.53/A	1.84	1.84	2.45	3.67	9.79	2.77	11.00	2 177	551	2 762	4.50/A
9+12+12+12	1.62	2.16	2.16	2.16	8.11	3.70	9.20	2 391	981	2 871	3.39/A	1.96	2.61	2.61	2.61	9.78	2.69	11.00	2 250	561	2 822	4.35/A
9+12+12+18	1.43	1.91	1.91	2.87	8.12	3.70	9.20	2 304	957	2 890	3.53/A	1.73	2.30	2.30	3.45	9.78	2.77	11.00	2 177	551	2 903	4.49/A
12+12+12+12	2.03	2.03	2.03	2.03	8.12	3.70	9.20	2 380	981	2 838	3.41/A	2.45	2.45	2.45	2.45	9.80	2.69	11.00	2 360	551	2 796	4.15/A

Based on wall mounted combination

CAPACITY COMBINATION



Indoor units combinations	COOLING												HEATING											
	Capacity (kW)					Power input (kW)			EER/ Energy label	Capacity (kW)					Power input (kW)			COP/ Energy label						
	A	B	C	D	E	Totale	Min	Max		Nom.	Min	Max	A	B	C	D	E		Totale	Min	Max	Nom.	Min	Max
7	2.2	-	-	-	-	2.2	1.40	3.0	0.68	0.40	0.92	3.24/A	2.8	-	-	-	-	2.8	0.95	4.0	0.60	0.30	0.80	4.67/A
9	2.5	-	-	-	-	2.5	1.50	3.5	0.76	0.40	1.01	3.29/A	3.4	-	-	-	-	3.4	0.95	5.2	0.69	0.40	0.86	4.96/A
12	3.5	-	-	-	-	3.5	1.50	4.2	1.03	0.40	1.29	3.40/A	4.3	-	-	-	-	4.3	1.11	7.5	0.95	0.39	1.21	4.54/A
18	-	-	-	-	5.0	5.0	2.20	6.0	1.44	0.42	1.63	3.47/A	-	-	-	-	6.2	6.2	1.50	8.0	1.50	0.46	1.87	4.14/A
21	-	-	-	-	6.0	6.0	2.20	7.0	1.93	0.40	2.13	3.11/B	-	-	-	-	7.0	7.0	1.80	8.4	1.85	0.40	2.13	3.78/A
24	-	-	-	-	7.0	7.0	2.50	8.0	2.58	0.41	2.71	2.71/D	-	-	-	-	8.0	8.0	2.00	9.2	2.42	0.41	2.71	3.31/C
7+7	2.3	2.3	-	-	-	4.5	2.0	6.0	1.13	0.60	1.60	3.98/A	2.6	2.6	-	-	-	5.3	2.0	7.0	1.13	0.60	1.60	4.66/A
7+9	2.1	2.7	-	-	-	4.8	2.1	6.3	1.27	0.60	1.77	3.78/A	2.5	3.2	-	-	-	5.6	2.1	7.3	1.27	0.60	1.77	4.43/A
7+12	2.1	3.7	-	-	-	5.8	2.1	6.7	1.71	0.60	2.20	3.41/A	2.5	4.3	-	-	-	6.8	2.1	7.7	1.71	0.60	2.20	3.99/A
7+18	2.1	5.3	-	-	-	7.4	2.3	7.6	2.45	0.56	2.71	3.01/B	2.4	6.2	-	-	-	8.6	2.3	8.6	2.45	0.56	2.71	3.52/B
7+21	2.0	6.0	-	-	-	8.0	2.4	8.1	2.75	0.56	3.05	2.90/C	2.3	7.0	-	-	-	9.3	2.4	9.1	2.75	0.56	3.05	3.40/C
7+24	1.8	6.3	-	-	-	8.1	2.5	8.5	2.81	0.56	3.20	2.88/C	2.1	7.3	-	-	-	9.5	2.5	9.5	2.81	0.56	3.20	3.37/C
9+9	2.6	2.6	-	-	-	5.1	2.1	6.6	1.36	0.58	1.95	3.76/A	3.0	3.0	-	-	-	6.0	2.1	7.6	1.36	0.58	1.95	4.40/A
9+12	2.6	3.5	-	-	-	6.1	2.2	7.0	2.01	0.54	2.54	3.05/B	3.1	4.1	-	-	-	7.2	2.2	8.0	2.01	0.54	2.54	3.58/B
9+18	2.6	5.1	-	-	-	7.7	2.4	7.9	2.58	0.56	3.20	2.97/C	3.0	6.0	-	-	-	9.0	2.4	8.9	2.58	0.56	3.20	3.48/B
9+21	2.4	5.6	-	-	-	8.0	2.5	8.4	2.75	0.56	3.28	2.90/C	2.8	6.5	-	-	-	9.3	2.5	9.4	2.75	0.56	3.28	3.40/C
9+24	2.2	5.9	-	-	-	8.1	2.6	8.8	2.81	0.56	3.32	2.88/C	2.6	6.9	-	-	-	9.5	2.6	9.8	2.81	0.56	3.32	3.37/C
12+12	3.6	3.6	-	-	-	7.2	2.3	7.5	2.40	0.54	2.55	2.98/C	4.2	4.2	-	-	-	8.4	2.3	8.5	2.40	0.54	2.55	3.49/B
12+18	3.2	4.8	-	-	-	8.0	2.5	8.4	2.76	0.56	3.22	2.89/C	3.7	5.6	-	-	-	9.3	2.5	9.4	2.76	0.56	3.22	3.38/C
12+21	2.9	5.1	-	-	-	8.1	2.6	8.8	2.73	0.56	3.18	2.96/C	3.4	6.0	-	-	-	9.5	2.6	9.8	2.73	0.56	3.18	3.47/B
12+24	2.7	5.5	-	-	-	8.2	2.6	9.2	2.78	0.56	3.18	2.94/C	3.2	6.4	-	-	-	9.6	2.6	10.2	2.78	0.56	3.18	3.45/B
18+18	4.5	4.5	-	-	-	9.0	2.6	11.0	3.00	0.59	3.16	3.00/C	5.3	5.3	-	-	-	10.5	2.6	11.5	2.94	0.59	3.16	3.58/B
18+21	4.2	4.9	-	-	-	9.1	2.7	11.0	3.08	0.57	3.12	2.96/C	4.9	5.7	-	-	-	10.6	2.7	11.0	2.98	0.57	3.12	3.56/B
18+24	4.0	5.3	-	-	-	9.3	2.8	11.0	3.17	0.55	3.20	2.92/C	4.6	6.1	-	-	-	10.7	2.8	11.0	3.02	0.55	3.20	3.53/B
21+21	4.6	4.6	-	-	-	9.3	2.8	11.0	3.17	0.55	3.20	2.92/C	5.3	5.3	-	-	-	10.7	2.8	11.0	3.02	0.55	3.20	3.53/B
21+24	4.4	5.0	-	-	-	9.4	2.9	11.0	3.25	0.55	3.20	2.88/C	5.0	5.7	-	-	-	10.7	2.9	11.0	3.05	0.55	3.20	3.51/B
24+24	4.8	4.8	-	-	-	9.5	3.0	11.0	3.33	0.55	3.40	2.85/C	5.4	5.4	-	-	-	10.8	3.0	12.0	3.09	0.55	3.40	3.49/B
7+7+7	1.9	1.9	1.9	-	-	5.6	2.50	8.5	1.86	0.69	2.41	3.02/B	2.3	2.3	2.3	-	-	6.9	2.50	8.5	1.86	0.69	2.41	3.69/A
7+7+9	1.8	1.8	2.3	-	-	5.9	2.6	8.6	1.97	0.67	2.51	2.98/C	2.2	2.2	2.8	-	-	7.2	2.6	8.7	1.97	0.67	2.51	3.64/A
7+7+12	1.8	1.8	3.0	-	-	6.5	2.7	8.8	2.31	0.69	2.97	2.83/C	2.2	2.2	3.7	-	-	8.0	2.7	9.1	2.31	0.69	2.97	3.47/B
7+7+18	1.5	1.5	3.8	-	-	6.7	2.9	9.2	2.32	0.70	2.92	2.89/C	1.8	1.8	4.6	-	-	8.2	2.9	9.8	2.32	0.70	2.92	3.54/B
7+7+21	1.4	1.4	4.1	-	-	6.8	3.0	9.4	2.37	0.68	2.88	2.87/C	1.7	1.7	5.0	-	-	8.3	3.0	10.1	2.37	0.68	2.88	3.51/B
7+7+24	1.3	1.3	4.3	-	-	6.8	3.1	9.6	2.39	0.68	2.88	2.85/C	1.5	1.5	5.3	-	-	8.3	3.1	10.5	2.39	0.68	2.88	3.48/B
7+9+9	1.7	2.2	2.2	-	-	6.1	2.6	8.8	2.10	0.69	2.94	2.91/C	2.1	2.7	2.7	-	-	7.5	2.6	9.0	2.10	0.69	2.94	3.57/B
7+9+12	1.7	2.1	2.8	-	-	6.6	2.7	9.0	2.35	0.69	2.97	2.82/C	2.0	2.6	3.5	-	-	8.1	2.7	9.3	2.35	0.69	2.97	3.45/B
7+9+18	1.4	1.8	3.6	-	-	6.7	2.9	9.4	2.37	0.70	2.92	2.83/C	1.7	2.2	4.3	-	-	8.2	2.9	10.0	2.37	0.70	2.92	3.47/B
7+9+21	1.3	1.7	3.9	-	-	6.8	3.0	9.6	2.39	0.68	2.88	2.85/C	1.6	2.0	4.7	-	-	8.3	3.0	10.4	2.39	0.68	2.88	3.48/B
7+9+24	1.2	1.5	4.1	-	-	6.8	3.1	9.8	2.39	0.68	2.88	2.85/C	1.5	1.9	5.0	-	-	8.3	3.1	10.7	2.39	0.68	2.88	3.48/B
7+12+12	1.5	2.6	2.6	-	-	6.7	2.8	9.2	2.35	0.69	2.92	2.86/C	1.9	3.2	3.2	-	-	8.2	2.8	9.7	2.35	0.69	2.92	3.50/B
7+12+18	1.3	2.2	3.3	-	-	6.7	3.0	9.6	2.32	0.70	2.89	2.89/C	1.6	2.7	4.0	-	-	8.2	3.0	10.4	2.32	0.70	2.89	3.54/B

Based on wall mounted combination

YAZ5-36



Indoor units combinations	COOLING											HEATING												
	Capacity (kW)					Power input (kW)			EER/ Energy label	Capacity (kW)					Power input (kW)			COP/ Energy label						
	A	B	C	D	E	Totale	Min	Max		Nom.	Min	Max	A	B	C	D	E		Totale	Min	Max	Nom.	Min	Max
7+12+21	1.2	2.0	3.6	-	-	6.8	3.1	9.8	2.35	0.68	2.86	2.89/C	1.5	2.5	4.4	-	-	8.3	3.1	10.7	2.35	0.68	2.86	3.54/B
7+12+24	1.2	2.0	4.0	-	-	7.2	3.2	10.0	2.51	0.68	3.00	2.88/C	1.4	2.5	4.9	-	-	8.8	3.2	11.1	2.51	0.68	3.00	3.52/B
7+18+18	1.1	3.0	3.0	-	-	7.1	3.2	10.0	2.40	0.68	3.05	2.94/C	1.4	3.6	3.6	-	-	8.6	3.2	11.1	2.40	0.68	3.05	3.60/B
7+18+21	1.1	2.8	3.3	-	-	7.2	3.3	10.2	2.50	0.66	3.02	2.89/C	1.3	3.5	4.0	-	-	8.8	3.3	11.4	2.50	0.66	3.02	3.54/B
7+18+24	1.1	2.8	3.7	-	-	7.7	3.4	10.4	2.65	0.66	3.05	2.89/C	1.3	3.4	4.6	-	-	9.4	3.4	11.8	2.65	0.66	3.05	3.53/B
7+21+21	1.1	3.3	3.3	-	-	7.7	3.4	10.4	2.65	0.66	3.05	2.89/C	1.3	4.0	4.0	-	-	9.4	3.4	11.8	2.65	0.66	3.05	3.53/B
7+21+24	1.0	3.1	3.6	-	-	7.7	3.5	10.5	2.68	0.60	3.21	2.89/C	1.3	3.8	4.4	-	-	9.5	3.5	12.0	2.68	0.60	3.21	3.53/B
9+9+9	2.5	2.5	2.5	-	-	7.5	2.7	8.9	2.25	0.69	3.01	3.18/B	3.3	3.3	3.3	-	-	10.0	2.7	11.0	2.25	0.69	3.01	4.10/A
9+9+12	2.4	2.4	3.1	-	-	7.8	2.8	9.1	2.41	0.69	2.97	3.25/A	3.0	3.0	4.1	-	-	10.1	2.8	11.1	2.42	0.69	2.97	4.18/A
9+9+18	2.1	2.1	4.3	-	-	8.5	3.0	9.5	2.51	0.70	2.92	3.38/A	2.6	2.6	5.2	-	-	10.4	3.0	11.4	2.39	0.70	2.92	4.35/A
9+9+21	2.0	2.0	4.8	-	-	8.8	3.1	9.7	2.61	0.68	2.88	3.38/A	2.4	2.4	5.6	-	-	10.4	3.1	11.5	2.39	0.68	2.88	4.35/A
9+9+24	2.0	2.0	5.2	-	-	9.2	3.2	9.9	2.71	0.68	3.05	3.38/A	2.2	2.2	5.9	-	-	10.4	3.2	11.6	2.39	0.68	3.05	4.35/A
9+12+12	2.2	3.0	3.0	-	-	8.2	2.9	9.3	2.46	0.69	2.92	3.31/A	2.8	3.7	3.7	-	-	10.3	2.9	11.3	2.41	0.69	2.92	4.27/A
9+12+18	2.0	2.7	4.1	-	-	8.8	3.1	9.7	2.61	0.70	2.89	3.38/A	2.4	3.2	4.8	-	-	10.4	3.1	11.5	2.39	0.70	2.89	4.35/A
9+12+21	2.0	2.6	4.6	-	-	9.2	3.2	9.9	2.71	0.68	3.00	3.38/A	2.2	3.0	5.2	-	-	10.4	3.2	11.6	2.39	0.68	3.00	4.35/A
9+12+24	1.9	2.5	5.1	-	-	9.5	3.3	10.1	2.81	0.68	3.02	3.38/A	2.1	2.8	5.5	-	-	10.4	3.3	11.8	2.39	0.68	3.02	4.35/A
9+18+18	1.9	3.8	3.8	-	-	9.5	3.3	10.1	2.81	0.66	3.02	3.38/A	2.1	4.2	4.2	-	-	10.4	3.3	11.8	2.39	0.66	3.02	4.35/A
9+18+21	1.8	3.6	4.2	-	-	9.5	3.4	10.3	2.81	0.66	3.02	3.38/A	2.0	3.9	4.6	-	-	10.4	3.4	11.9	2.39	0.66	3.02	4.35/A
9+18+24	1.7	3.4	4.5	-	-	9.5	3.5	10.5	2.81	0.66	3.05	3.38/A	1.8	3.7	4.9	-	-	10.4	3.5	12.0	2.39	0.66	3.05	4.35/A
9+21+21	1.7	3.9	3.9	-	-	9.5	3.5	10.5	2.81	0.66	3.05	3.38/A	1.8	4.3	4.3	-	-	10.4	3.5	12.0	2.39	0.66	3.05	4.35/A
9+21+24	1.6	3.7	4.2	-	-	9.5	3.6	10.5	2.81	0.66	3.20	3.38/A	1.7	4.0	4.6	-	-	10.4	3.6	12.0	2.39	0.66	3.20	4.35/A
12+12+12	2.8	2.8	2.8	-	-	8.5	3.0	9.5	2.51	0.72	2.91	3.38/A	3.5	3.5	3.5	-	-	10.4	3.0	11.4	2.39	0.72	2.91	4.35/A
12+12+18	2.6	2.6	3.9	-	-	9.2	3.2	9.9	2.71	0.70	3.00	3.38/A	3.0	3.0	4.6	-	-	10.7	3.2	11.6	2.45	0.70	3.00	4.35/A
12+12+21	2.5	2.5	4.4	-	-	9.5	3.3	10.1	2.81	0.68	3.02	3.38/A	2.9	2.9	5.0	-	-	10.8	3.3	11.8	2.48	0.68	3.02	4.35/A
12+12+24	2.4	2.4	4.8	-	-	9.5	3.4	10.3	2.81	0.68	3.05	3.38/A	2.7	2.7	5.5	-	-	10.9	3.4	11.9	2.51	0.68	3.05	4.35/A
12+18+18	2.4	3.6	3.6	-	-	9.5	3.4	10.3	2.81	0.68	3.02	3.38/A	2.7	4.1	4.1	-	-	10.9	3.4	11.9	2.51	0.68	3.02	4.35/A
12+18+21	2.2	3.4	3.9	-	-	9.5	3.5	10.5	2.81	0.66	3.05	3.38/A	2.6	3.9	4.6	-	-	11.1	3.5	12.0	2.54	0.66	3.05	4.35/A
7+7+7+7	1.7	1.7	1.7	1.7	-	6.9	3.00	9.0	2.18	0.81	2.67	3.15/B	2.0	2.0	2.0	2.0	-	7.8	3.00	9.0	2.18	0.81	2.67	3.58/B
7+7+7+9	1.6	1.6	1.6	2.1	-	7.0	3.1	9.2	2.19	0.81	2.67	3.17/B	1.8	1.8	1.8	2.4	-	7.9	3.1	9.3	2.17	0.81	2.67	3.64/A
7+7+7+12	1.5	1.5	1.5	2.6	-	7.0	3.3	9.5	2.21	0.81	2.65	3.19/B	1.7	1.7	1.7	2.9	-	8.0	3.3	9.6	2.16	0.81	2.65	3.70/A
7+7+7+18	1.3	1.3	1.3	3.2	-	7.0	3.6	10.1	2.15	0.79	2.62	3.27/A	1.4	1.4	1.4	3.7	-	8.0	3.6	10.4	2.39	0.79	2.62	3.35/C
7+7+7+21	1.2	1.2	1.2	3.7	-	7.5	3.7	10.4	2.30	0.77	2.75	3.25/A	1.4	1.4	1.4	4.3	-	8.5	3.7	10.8	2.38	0.77	2.75	3.57/B
7+7+7+24	1.2	1.2	1.2	4.1	-	7.7	3.9	10.7	2.36	0.77	2.73	3.24/A	1.4	1.4	1.4	4.6	-	8.7	3.9	11.1	2.38	0.77	2.73	3.66/A
7+7+9+9	1.5	1.5	2.0	2.0	-	7.0	3.2	9.4	2.19	0.81	2.67	3.17/B	1.7	1.7	2.2	2.2	-	7.9	3.2	9.5	2.16	0.81	2.67	3.66/A
7+7+9+12	1.4	1.4	1.8	2.4	-	7.0	3.4	9.7	2.21	0.81	2.65	3.19/B	1.6	1.6	2.1	2.7	-	8.0	3.4	9.9	2.15	0.81	2.65	3.72/A
7+7+9+18	1.2	1.2	1.6	3.2	-	7.2	3.7	10.3	2.20	0.79	2.70	3.28/A	1.4	1.4	1.8	3.6	-	8.2	3.7	10.6	2.38	0.79	2.70	3.45/B
7+7+9+21	1.2	1.2	1.5	3.6	-	7.5	3.8	10.6	2.30	0.77	2.71	3.25/A	1.4	1.4	1.7	4.1	-	8.5	3.8	11.0	2.37	0.77	2.71	3.59/B
7+7+9+24	1.1	1.1	1.5	3.9	-	7.7	4.0	10.9	2.35	0.77	2.75	3.26/A	1.3	1.3	1.7	4.4	-	8.7	4.0	11.4	2.37	0.77	2.75	3.67/A
7+7+12+12	1.3	1.3	2.2	2.2	-	7.0	3.5	10.0	2.21	0.81	2.62	3.19/B	1.5	1.5	2.5	2.5	-	8.0	3.5	10.3	2.15	0.81	2.62	3.72/A
7+7+12+18	1.2	1.2	2.0	3.1	-	7.5	3.8	10.6	2.30	0.79	2.71	3.25/A	1.4	1.4	2.3	3.5	-	8.5	3.8	11.0	2.37	0.79	2.71	3.59/B

Based on wall mounted combination

CAPACITY COMBINATION



Indoor units combinations	COOLING											HEATING												
	Capacity (kW)					Power input (kW)			EER/ Energy label	Capacity (kW)					Power input (kW)			COP/ Energy label						
	A	B	C	D	E	Totale	Min	Max		Nom.	Min	Max	A	B	C	D	E		Totale	Min	Max	Nom.	Min	Max
7+7+12+21	1.1	1.1	2.0	3.4	-	7.7	4.0	10.9	2.35	0.77	2.75	3.26/A	1.3	1.3	2.2	3.9	-	8.7	4.0	11.4	2.36	0.77	2.75	3.69/A
7+7+18+18	1.1	1.1	2.9	2.9	-	7.9	4.1	11.0	2.45	0.77	2.90	3.23/A	1.3	1.3	3.2	3.2	-	9.0	4.1	11.5	2.27	0.77	2.90	3.96/A
7+9+9+9	1.4	1.8	1.8	1.8	-	7.0	3.3	9.6	2.14	0.81	2.67	3.25/A	1.6	2.1	2.1	2.1	-	7.9	3.3	9.8	2.16	0.81	2.67	3.66/A
7+9+9+12	1.3	1.7	1.7	2.3	-	7.0	3.5	9.9	2.21	0.81	2.65	3.19/B	1.5	1.9	1.9	2.6	-	8.0	3.5	10.1	2.15	0.81	2.65	3.72/A
7+9+9+18	1.2	1.5	1.5	3.1	-	7.3	3.8	10.5	2.23	0.79	2.71	3.28/A	1.4	1.7	1.7	3.5	-	8.3	3.8	10.9	2.38	0.79	2.71	3.49/B
7+9+9+21	1.1	1.5	1.5	3.4	-	7.5	3.9	10.8	2.30	0.77	2.75	3.25/A	1.3	1.7	1.7	3.9	-	8.5	3.9	11.3	2.36	0.77	2.75	3.60/B
7+9+9+24	1.1	1.5	1.5	3.9	-	7.9	4.1	11.0	2.43	0.77	2.89	3.26/A	1.3	1.7	1.7	4.4	-	9.0	4.1	11.5	2.36	0.77	2.89	3.81/A
7+9+12+12	1.3	1.6	2.2	2.2	-	7.2	3.6	10.2	2.20	0.81	2.70	3.28/A	1.4	1.8	2.5	2.5	-	8.2	3.6	10.5	2.52	0.81	2.70	3.25/C
7+9+12+18	1.1	1.5	2.0	2.9	-	7.5	3.9	10.8	2.30	0.81	2.75	3.25/A	1.3	1.7	2.2	3.3	-	8.5	3.9	11.3	2.35	0.81	2.75	3.62/A
7+9+12+21	1.1	1.5	1.9	3.4	-	7.9	4.1	11.0	2.45	0.77	2.89	3.23/A	1.3	1.7	2.2	3.9	-	9.0	4.1	11.5	2.34	0.77	2.89	3.85/A
7+9+18+18	1.1	1.4	2.7	2.7	-	7.9	4.2	11.0	2.45	0.77	2.89	3.23/A	1.2	1.6	3.1	3.1	-	9.0	4.2	11.5	2.26	0.77	2.89	3.98/A
7+9+18+21	1.0	1.3	2.6	3.0	-	7.9	4.4	11.0	2.43	0.77	3.03	3.26/A	1.1	1.5	2.9	3.4	-	9.0	4.4	11.5	2.25	0.77	3.03	4.00/A
7+12+12+12	1.2	2.1	2.1	2.1	-	7.5	3.8	10.5	2.30	0.81	2.71	3.25/A	1.4	2.4	2.4	2.4	-	8.5	3.8	10.9	2.55	0.81	2.71	3.33/C
7+12+12+18	1.1	1.9	1.9	2.9	-	7.9	4.1	11.0	2.45	0.79	2.75	3.23/A	1.3	2.2	2.2	3.3	-	9.0	4.1	11.5	2.35	0.79	2.75	3.83/A
7+12+12+21	1.1	1.8	1.8	3.2	-	7.9	4.2	11.0	2.43	0.77	2.89	3.26/A	1.2	2.1	2.1	3.6	-	9.0	4.2	11.5	2.34	0.77	2.89	3.85/A
9+9+9+9	2.2	2.2	2.2	2.2	-	8.8	3.4	9.8	2.33	0.81	2.67	3.77/A	2.5	2.5	2.5	2.5	-	10.0	3.4	10.0	2.08	0.81	2.67	4.80/A
9+9+9+12	2.1	2.1	2.1	2.8	-	9.1	3.6	10.1	2.22	0.81	2.65	3.83/A	2.4	2.4	2.4	3.2	-	10.3	3.6	10.4	2.15	0.81	2.65	4.00/A
9+9+9+18	1.9	1.9	1.9	3.9	-	9.7	3.9	10.7	2.30	0.79	2.71	3.94/A	2.2	2.2	2.2	4.3	-	10.8	3.9	11.1	2.36	0.79	2.71	4.00/A
9+9+9+21	1.9	1.9	1.9	4.4	-	10.0	4.0	11.0	2.32	0.77	2.75	4.00/A	2.1	2.1	2.1	4.8	-	11.0	4.0	11.5	2.35	0.77	2.75	4.00/A
9+9+9+24	1.8	1.8	1.8	4.7	-	10.0	4.2	11.0	2.43	0.77	2.89	4.00/A	1.9	1.9	1.9	5.2	-	11.0	4.2	11.5	2.35	0.77	2.89	3.80/A
9+9+12+12	2.0	2.0	2.7	2.7	-	9.4	3.7	10.4	2.23	0.81	2.71	3.89/A	2.3	2.3	3.0	3.0	-	10.5	3.7	10.8	2.55	0.81	2.71	4.00/A
9+9+12+18	1.9	1.9	2.5	3.8	-	10.0	4.0	11.0	2.42	0.79	2.75	4.00/A	2.1	2.1	2.8	4.1	-	11.0	4.0	11.5	2.33	0.79	2.75	4.00/A
9+9+12+21	2.0	2.0	2.7	2.7	-	9.4	3.7	10.4	2.45	0.77	2.89	3.89/A	2.3	2.3	3.0	3.0	-	10.5	3.7	10.8	2.30	0.77	2.89	4.00/A
9+9+18+18	1.7	1.7	3.3	3.3	-	10.0	4.3	11.0	2.41	0.77	2.89	4.00/A	1.8	1.8	3.7	3.7	-	11.0	4.3	11.5	2.25	0.77	2.89	3.60/B
9+12+12+12	1.9	2.6	2.6	2.6	-	9.7	3.9	10.7	2.30	0.81	2.61	3.94/A	2.2	2.9	2.9	2.9	-	10.8	3.9	11.1	2.52	0.81	2.61	4.00/A
9+12+12+18	1.8	2.4	2.4	3.5	-	10.0	4.2	11.0	2.43	0.79	2.89	4.00/A	1.9	2.6	2.6	3.9	-	11.0	4.2	11.5	2.29	0.79	2.89	3.80/A
9+12+12+21	1.7	2.2	2.2	3.9	-	10.0	4.3	11.0	2.50	0.79	2.89	4.00/A	1.8	2.4	2.4	4.3	-	11.0	4.3	11.5	2.29	0.79	2.89	3.60/B
12+12+12+12	2.5	2.5	2.5	2.5	-	10.0	4.0	11.0	2.50	0.81	2.92	4.00/A	2.8	2.8	2.8	2.8	-	11.0	4.0	11.5	2.50	0.81	2.92	4.00/A
7+7+7+7+7	1.9	1.9	1.9	1.9	1.9	9.5	4.00	10.2	2.94	0.78	3.50	3.15/B	2.1	2.1	2.1	2.1	2.1	10.5	4.00	11.0	2.94	0.78	3.50	3.80/A
7+7+7+7+9	1.8	1.8	1.8	1.8	2.3	9.6	4.1	10.4	2.94	0.78	3.50	3.26/A	2.0	2.0	2.0	2.0	2.6	10.8	4.1	11.3	2.94	0.78	3.50	3.94/A
7+7+7+7+12	1.7	1.7	1.7	1.7	2.9	9.8	4.2	10.6	2.94	0.78	3.50	3.43/A	2.0	2.0	2.0	2.0	3.4	11.3	4.2	11.8	2.94	0.78	3.50	4.15/A
7+7+7+7+18	1.5	1.5	1.5	1.5	3.9	10.0	4.3	11.0	2.92	0.79	3.49	3.70/A	1.8	1.8	1.8	1.8	4.7	12.0	4.3	12.5	2.92	0.79	3.49	4.50/A
7+7+7+7+21	1.4	1.4	1.4	1.4	4.3	10.0	4.4	11.0	2.91	0.80	3.48	3.70/A	1.7	1.7	1.7	1.7	5.1	12.0	4.4	12.5	2.91	0.80	3.48	4.50/A
7+7+7+9+9	1.7	1.7	1.7	2.2	2.2	9.7	4.1	10.5	2.94	0.78	3.50	3.37/A	2.0	2.0	2.0	2.6	2.6	11.1	4.1	11.6	2.94	0.78	3.50	4.08/A
7+7+7+9+12	1.6	1.6	1.6	2.1	2.8	9.9	4.2	10.8	2.94	0.78	3.50	3.54/A	1.9	1.9	1.9	2.5	3.3	11.6	4.2	12.1	2.94	0.78	3.50	4.29/A
7+7+7+9+18	1.5	1.5	1.5	1.9	3.8	10.0	4.4	11.0	2.92	0.79	3.49	3.70/A	1.8	1.8	1.8	2.3	4.5	12.0	4.4	12.5	2.92	0.79	3.49	4.50/A
7+7+7+12+12	1.6	1.6	1.6	2.1	2.8	9.9	4.2	10.8	2.94	0.78	3.50	3.54/A	1.9	1.9	1.9	2.5	3.3	11.6	4.2	12.1	2.94	0.78	3.50	4.29/A
7+7+9+9+9	1.7	1.7	2.2	2.2	2.2	9.8	4.2	10.7	2.94	0.78	3.50	3.48/A	1.9	1.9	2.5	2.5	2.5	11.4	4.2	11.9	2.94	0.78	3.50	4.22/A
7+7+9+9+12	1.6	1.6	2.0	2.0	2.7	10.0	4.3	10.9	2.94	0.78	3.50	3.65/A	1.9	1.9	2.4	2.4	3.2	11.9	4.3	12.4	2.94	0.78	3.50	4.43/A
7+7+9+9+18	1.4	1.4	1.8	1.8	3.6	10.0	4.5	11.0	2.92	0.79	3.49	3.70/A	1.7	1.7	2.2	2.2	4.3	12.0	4.5	12.5	2.92	0.79	3.49	4.50/A

Based on wall mounted combination

YAZ5-36



Indoor units combinations	COOLING											HEATING												
	Capacity (kW)					Power input (kW)			EER/ Energy label	Capacity (kW)					Power input (kW)			COP/ Energy label						
	A	B	C	D	E	Totale	Min	Max		Nom.	Min	Max	A	B	C	D	E		Totale	Min	Max	Nom.	Min	Max
7+7+9+12+12	1.5	1.5	1.9	2.6	2.6	10.0	4.4	11.0	2.94	0.78	3.50	3.70/A	1.8	1.8	2.3	3.1	3.1	12.0	4.4	12.5	2.94	0.78	3.50	4.50/A
7+9+9+9+9	1.6	2.1	2.1	2.1	2.1	9.9	4.3	10.8	2.94	0.78	3.50	3.59/A	1.9	2.4	2.4	2.4	2.4	11.7	4.3	12.2	2.94	0.78	3.50	4.36/A
7+9+9+9+12	1.5	2.0	2.0	2.0	2.6	10.0	4.3	11.0	2.94	0.78	3.50	3.70/A	1.8	2.3	2.3	2.3	3.1	12.0	4.3	12.5	2.94	0.78	3.50	4.50/A
7+9+9+9+18	1.3	1.7	1.7	1.7	3.5	10.0	4.5	11.0	2.92	0.79	3.49	3.70/A	1.6	2.1	2.1	2.1	4.2	12.0	4.5	12.5	2.92	0.79	3.49	4.50/A
7+9+9+12+12	1.3	1.7	1.7	1.7	3.5	10.0	4.5	11.0	2.94	0.78	3.50	3.70/A	1.6	2.1	2.1	2.1	4.2	12.0	4.5	12.5	2.94	0.78	3.50	4.50/A
9+9+9+9+9	2.0	2.0	2.0	2.0	2.0	10.0	4.3	11.0	2.94	0.78	3.50	3.70/A	2.4	2.4	2.4	2.4	2.4	12.0	4.3	12.5	2.94	0.78	3.50	4.50/A
9+9+9+9+12	1.9	1.9	1.9	1.9	2.6	10.3	4.4	11.0	2.94	0.78	3.50	3.60/A	2.3	2.3	2.3	2.3	3.0	12.0	4.4	12.5	2.94	0.78	3.50	4.30/A
9+9+9+9+18	1.8	1.8	1.8	1.8	3.5	10.5	4.6	11.0	2.92	0.79	3.49	3.40/A	2.0	2.0	2.0	2.0	4.0	12.0	4.6	12.5	2.92	0.79	3.49	4.20/A
9+9+9+12+12	1.9	1.9	1.9	2.5	2.5	10.5	4.50	11.0	2.94	0.78	3.50	3.50/A	2.1	2.1	2.1	2.8	2.8	12.0	4.50	12.5	2.94	0.78	3.50	4.30/A

Based on wall mounted combination