



YAZE

Unique solutions



FLEXY MATCH



ADVANCED CONTROL OPTIONS

PREMIUM MULTI DUO/TRIO/QUATTRO/CINCO

- Capacity range available in 4 capacities from 5 up to 9.5 kW.
- DC Inverter and sine wave compressor drive technology.

COMPATIBLE WITH

HIGH WALL **HJD**



FLOOR CEILING **SXE**



CASSETTE **CNE**



DUCTED LSP **DLF**



DUCTED MSP **DLS**



PRODUCT ADVANTAGES

- **Flexy match** with wide range of indoor unit including HJD, SXE, CNE, DLS, DLF lines.
- Precharge to maximum tubing length up to 80 m.
- Possibility to connect to alarm output, unit ON/OFF, night mode and power consumption level.
- Fuzzy logic for precise capacity balance between indoor unit under operation.
- Same indoor for multi and single application.



FLEXY MATCH



A/A CLASS EFFICIENCY



DC INVERTER



SINE WAVE COMPRESSOR DRIVE



1 W STANDBY POWER



LOW VOLTAGE STARTUP



LOW TEMPERATURE STARTUP



R410A FLUID



ELECTRONIC EXPANSION VALVE



ANTI-DUST AND UV CASING



FILTER CLEAN INDICATION



SUPER QUIET



SELF DIAGNOSTIC-DIGITAL



RESTART (MEMORY)



ADVANCED DEFFROST



AUTO FAN



PRESENCE DETECTOR INPUT



BMS COMPATIBLE



SERVICE MONITOR TOOL



POWER CONSUMPTION CONTROL



OUTDOOR UNIT DIGITAL DIAGNOSTIC



OUTDOOR UNIT NIGHT MODE DRY CONTACT



OUTDOOR UNIT STAND-BY



OUTDOOR UNIT ALARM OUTPUT



FULL LENGTH REFRIGERANT PRECHARGE



TECHNICIAN TEST MODE



LOW AMBIENT COOLING



LOW AMBIENT HEATING



ADVANCED INSTALLATION TEST

YAZE TECHNICAL DATA

Outdoor units		AWAU-YAZE218-H11	AWAU-YAZE318-H11	AWAU-YAZE324-H11	AWAU-YAZE430-H11	AWAU-YAZE536-H11
COOLING						
Rated Capacity	kW	5 (1.2-6.4)	5.20 (1.0-6.6)	7.35 (1.3-9)	8 (1.4-9.2)	9.5 (2.0-11.0)
Pdesignnc	kW	5	5.20	7.35	8	9.5
Input power	kW	1.47	1.46	2.24	2.38	2.81
SEER/Energy Label		5.61/A+	5.61/A+	5.61/A+	5.61/A+	4.70/B
Operating limits	°C	-10°/46° Dry bulb				
HEATING						
Rated Capacity	kW	6.0 (1.0-6.8)	6.60 (1.0-8.15)	9.2 (0.95-11)	9.8 (0.95-11)	11.5 (2.4-12.5)
Pdesignnh	kW	5.0	5.2	7.5	8.5	11.5
Input power	kW	1.7	1.71	2.36	2.71	2.65
SCOP/Energy Label		4.00/A+	4.00/A+	4.00/A+	4.00/A+	4.50/A+
Operating limits	°C	-15°/24° Dry bulb				
OUTDOOR UNIT						
Sound pressure level to 1 m	dB(A)	53	56	57	57	58
Sound power level	dB(A)	63	67	69	69	69
Airflow	m³/h	2160	2860	3600	3600	4150
Compressor type		Rotary DC Inverter	Twin Rotary DC Inverter	Twin Rotary DC Inverter	Twin Rotary DC Inverter	Twin Rotary DC Inverter
Outline Dimensions (WxHxD)	mm	795x610x290	846x690x302	950x864x413	950x864x413	900x970x340
Package Dimensions (WxHxD)	mm	970x655x395	990x770x430	1070x940x510	1070x940x510	985x1020x435
Net Weight/Gross Weight	kg	39/42	48/52	69/75	70/76	85/87.8
Part number		7SP091164	7SP091165	7SP091162	7SP091163	7SP091161
POWER SUPPLY 1~230V - 50 HZ						
Power supply side		Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
Power cable section	mm²	3x2.5	3x2.5	3x2.5	3x2.5	3x2.5
Fuse rating am	A	20	20	25	25	25
Electrical connections	mm²	2x(4x1.5)	3x(4x1.5)	3x(4x1.5)	4x(4x1.5)	5x (4x1.5)
PIPE LINE						
Suction pipe diameter	inches	2x3/8"	3x3/8"	2x3/8" + 1x1/2"	3x3/8" + 1x1/2"	3x3/8" + 2x1/2"
Liquid pipe diameter	inches	2x1/4"	3x1/4"	3x1/4"	4x1/4"	5x1/4"
Max length	m	30	30	50	70	80
Max length per circuit	m	25	25	25	25	25
Max height between indoor and outdoor units	m	10	15	15	15	15
Max height between indoor units	m	5	15	15	15	15

AIRWELL SOLUTIONS





YAZE2-18

Unique solutions



PREMIUM MULTI DUO/TRIO/QUATTRO/CINCO

COMPATIBLE WITH

HIGH WALL **HJD**



FLOOR CEILING **SXE**



CASSETTE **CNE**



DUCTED LSP **DLF**



DUCTED MSP **DLS**



CAPACITY COMBINATION

Mandatory to connect all IDU

Indoor units combinations	COOLING											HEATING										
	Capacity (kW)						Power input (kW)			SEER	Capacity (kW)						Power input (kW)			SCOP		
	A	B	C	D	Totale	Min	Max	Nom.	Min		Max	A	B	C	D	Totale	Min	Max	Nom.		Min	Max
9	2.50				2.50	1.20	3.60	0.70	0.42	1.00	3.57	3.00				3.00	1.00	4.00	0.83	0.38	1.50	3.61
12	3.50				3.50	1.20	4.30	1.00	0.42	1.20	3.50	4.00				4.00	1.00	4.50	1.10	0.38	1.70	3.64
9+9	2.50	2.50			5.00	1.80	6.00	1.47	0.55	2.10	3.40	3.00	3.00			6.00	2.00	6.50	1.66	0.58	1.80	3.61
9+12	2.14	2.86			5.00	1.80	6.30	1.47	0.55	2.13	3.40	2.57	3.43			6.00	2.00	6.65	1.66	0.58	1.89	3.61
12+12	2.50	2.50			5.00	1.80	6.40	1.47	0.55	2.13	3.40	3.00	3.00			6.00	2.00	6.80	1.66	0.58	1.89	3.61

Based on wall mounted combination



YAZE3-18

Unique solutions



PREMIUM MULTI DUO/TRIO/QUATTRO/CINCO

COMPATIBLE WITH

HIGH WALL HJD



FLOOR CEILING SXE



CASSETTE CNE



DUCTED LSP DLF



DUCTED MSP DLS



CAPACITY COMBINATION

Mandatory to connect all IDU

Indoor units combinations	COOLING											HEATING											
	Capacity (kW)						Power input (kW)					SEER	Capacity (kW)						Power input (kW)				SCOP
	A	B	C	D	Totale	Min	Max	Nom.	Min	Max	A		B	C	D	Totale	Min	Max	Nom.	Min	Max		
9	2.50				2.50	1.10	3.50	0.74	0.51	1.04	3.38	3.00				3.00	1.00	3.50	0.80	0.45	0.92	3.75	
12	3.50				3.50	1.20	4.20	1.02	0.51	1.25	3.43	4.20				4.20	1.00	4.50	1.08	0.51	1.16	3.89	
9+9	2.50	2.50			5.00	1.71	6.20	1.40	0.61	1.91	3.57	3.00	3.00			6.00	1.80	7.00	1.60	0.48	1.75	3.75	
9+12	2.23	2.97			5.20	1.71	6.28	1.46	0.60	1.93	3.56	2.83	3.77			6.60	2.00	7.80	1.71	0.51	1.90	3.86	
12+12	2.60	2.60			5.20	1.80	6.40	1.46	0.64	2.10	3.56	3.30	3.30			6.60	2.10	7.80	1.71	0.52	1.90	3.86	
9+9+9	1.73	1.73	1.73		5.20	1.86	6.45	1.46	0.64	2.10	3.56	2.20	2.20	2.20		6.60	2.12	8.00	1.71	0.64	1.90	3.86	
9+9+12	1.56	1.56	2.08		5.20	1.88	6.50	1.46	0.64	2.15	3.56	1.98	1.98	2.64		6.60	2.20	8.15	1.71	0.64	1.90	3.86	

Based on wall mounted combination



YAZE3-24

Unique solutions



PREMIUM MULTI DUO/TRIO/QUATTRO/CINCO

COMPATIBLE WITH

HIGH WALL **HJD**



FLOOR CEILING **SXE**



CASSETTE **CNE**



DUCTED LSP **DLF**



DUCTED MSP **DLS**



CAPACITY COMBINATION

Mandatory to connect all IDU

Indoor units combinations	COOLING											HEATING										
	Capacity (kW)					Power input (kW)					SEER	Capacity (kW)					Power input (kW)					SCOP
	A	B	C	D	Totale	Min	Max	Nom.	Min	Max		A	B	C	D	Totale	Min	Max	Nom.	Min	Max	
9	2.50	-	-	-	2.50	1.30	3.70	0.69	0.50	1.03	3.65	3.40	-	-	--	3.40	0.95	4.00	0.69	0.50	0.90	4.96
12	3.50	-	-	-	3.50	1.30	4.40	0.97	0.50	1.22	3.62	4.30	-	-	-	4.30	0.95	5.20	1.00	0.49	1.32	4.29
18	-	-	-	5.00	5.00	1.49	5.93	1.39	0.57	1.66	3.59	-	-	-	6.20	6.20	1.11	7.50	1.67	0.55	2.13	3.71
9+9	2.60	2.60	-	-	5.19	1.86	6.56	1.53	0.68	1.86	3.39	3.68	3.68	-	-	7.36	1.43	9.10	1.93	0.65	2.64	3.81
9+12	3.49	2.62	-	-	6.11	1.86	7.73	1.82	0.68	2.54	3.35	3.33	4.44	-	-	7.77	1.43	9.50	2.06	0.65	2.71	3.77
9+18	4.98	-	-	2.49	7.47	1.86	9.00	2.25	0.66	3.05	3.32	3.07	-	-	6.13	9.20	1.43	10.10	2.51	0.62	2.74	3.66
12+12	3.53	3.53	-	-	7.06	1.86	9.00	2.12	0.68	2.25	3.33	4.09	4.09	-	-	8.18	1.43	9.80	2.19	0.65	2.71	3.73
12+18	4.48	-	-	2.99	7.47	1.86	9.00	2.25	0.66	3.06	3.32	3.68	-	-	5.52	9.20	1.43	10.50	2.51	0.62	2.87	3.66
9+9+9	2.45	2.45	2.45	-	7.35	2.69	8.98	2.24	0.95	3.05	3.28	3.07	3.07	3.07	-	9.20	2.06	10.99	2.31	0.80	3.01	3.98
9+9+12	2.99	2.25	2.25	-	7.48	2.69	9.00	2.28	0.95	3.16	3.28	2.76	2.76	3.68	-	9.20	2.06	11.00	2.31	0.80	2.97	3.98
9+9+18	3.74	1.87	1.87	-	7.47	2.69	9.00	2.28	0.96	3.10	3.28	2.30	2.30	-	4.60	9.20	2.06	11.00	2.31	0.77	2.83	3.98
9+12+12	2.71	2.71	2.04	-	7.46	2.69	9.00	2.28	0.95	3.10	3.28	3.34	2.51	3.34	-	9.19	2.06	11.00	2.31	0.80	2.94	3.98
9+12+18	3.45	2.30	-	1.72	7.46	2.69	9.00	2.28	0.96	3.06	3.28	2.82	2.12	-	4.24	9.18	2.14	11.00	2.31	0.77	2.75	3.98
12+12+12	2.49	2.49	2.49	-	7.47	2.69	9.00	2.28	0.99	3.09	3.28	3.07	3.07	3.07	-	9.20	2.06	11.00	2.31	0.80	2.85	3.98
12+12+18	3.19	2.13	-	2.13	7.45	2.69	9.00	2.27	0.96	3.09	3.28	2.63	2.63	-	3.94	9.19	2.14	11.00	2.31	0.77	2.70	3.98

Based on wall mounted combination



YAZE4-30

Unique solutions



PREMIUM MULTI DUO/TRIO/QUATTRO/CINCO

COMPATIBLE WITH



HIGH WALL HJD



FLOOR CEILING SXE



CASSETTE CNE



DUCTED LSP DLF



DUCTED MSP DLS



CAPACITY COMBINATION

Mandatory to connect all IDU

Indoor units combinations	COOLING											HEATING										
	Capacity (kW)					Power input (kW)			SEER	Capacity (kW)					Power input (kW)			SCOP				
	A	B	C	D	Totale	Min	Max	Nom.		Min	Max	A	B	C	D	Totale	Min		Max	Nom.	Min	Max
9	2.50	-	-	-	2.50	1.40	3.70	0.69	0.50	1.03	3.65	3.40	-	-	-	3.40	0.95	4.00	0.69	0.40	0.86	4.96
12	3.50	-	-	-	3.50	1.40	4.40	0.97	0.50	1.22	3.62	4.30	-	-	-	4.30	0.95	5.20	0.95	0.39	1.21	4.54
18	-	-	-	5.00	5.00	1.60	5.60	1.39	0.57	1.56	3.59	-	-	-	6.20	6.20	1.11	7.50	1.50	0.46	1.88	4.14
9+9	2.54	2.54	-	-	5.08	2.00	6.20	1.45	0.69	1.74	3.49	3.75	3.75	-	-	7.51	1.43	8.63	1.77	0.54	2.17	4.25
9+12	3.42	2.56	-	-	5.98	2.00	7.30	1.72	0.69	2.39	3.47	4.53	3.40	-	-	7.92	1.43	9.01	1.90	0.54	2.24	4.17
9+18	5.08	-	-	2.54	7.61	2.00	8.50	2.21	0.67	2.86	3.45	6.26	-	-	3.13	9.38	1.43	9.58	2.34	0.52	2.26	4.02
12+12	3.45	3.45	-	-	6.90	2.10	8.80	2.00	0.69	2.92	3.46	4.17	4.17	-	-	8.34	1.43	9.29	1.99	0.54	2.24	4.20
12+18	4.72	-	-	3.15	7.87	2.10	8.80	2.29	0.67	2.88	3.44	5.88	-	-	3.92	9.80	1.43	9.96	2.40	0.52	2.37	4.09
9+9+9	2.40	2.40	2.40	-	7.19	2.90	9.00	2.11	0.92	2.94	3.40	3.13	3.13	3.13	-	9.38	2.06	11.00	2.23	0.67	2.62	4.22
9+9+12	3.15	2.36	2.36	-	7.87	2.90	9.00	2.45	0.92	2.90	3.22	3.92	2.94	2.94	-	9.80	2.06	11.00	2.31	0.67	2.89	4.25
9+9+18	4.01	2.00	-	2.00	8.01	2.90	9.00	2.47	0.93	2.85	3.25	4.90	2.45	-	2.45	9.80	2.06	11.00	2.14	0.65	2.88	4.57
9+12+12	2.90	2.90	2.17	-	7.97	2.90	9.00	2.45	0.92	2.85	3.26	3.56	3.56	2.67	-	9.78	2.06	11.00	2.25	0.67	2.87	4.35
9+12+18	3.74	2.50	-	1.87	8.11	2.90	9.00	2.48	0.93	2.82	3.28	4.51	3.01	-	2.26	9.78	2.14	11.00	2.08	0.65	2.73	4.70
12+12+12	2.69	2.69	2.69	-	8.07	2.90	9.00	2.37	0.96	2.84	3.40	3.26	3.26	3.26	-	9.79	2.06	11.00	2.23	0.67	2.86	4.40
12+12+18	3.47	2.31	-	2.31	8.10	2.90	9.00	2.37	0.93	2.80	3.42	4.19	2.79	-	2.79	9.78	2.14	11.00	2.06	0.65	2.67	4.74
9+9+9+9	2.00	2.00	2.00	2.00	8.00	3.70	9.17	2.38	0.98	2.94	3.36	2.45	2.45	2.45	2.45	9.80	2.69	10.97	2.36	0.56	2.94	4.15
9+9+9+12	2.49	1.87	1.87	1.87	8.10	3.70	9.20	2.41	0.98	2.92	3.36	3.01	2.25	2.25	2.25	9.77	2.69	11.00	2.34	0.56	2.90	4.18
9+9+9+18	3.25	1.62	1.62	1.62	8.12	3.70	9.20	2.34	0.96	2.88	3.48	3.92	1.96	1.96	1.96	9.80	2.77	11.00	2.27	0.55	2.78	4.31
9+9+12+12	2.32	2.32	1.74	1.74	8.11	3.70	9.20	2.40	0.98	2.88	3.38	2.80	2.80	2.10	2.10	9.79	2.69	11.00	2.29	0.56	2.86	4.28
9+9+12+18	3.05	2.03	1.52	1.52	8.12	3.70	9.20	2.30	0.96	2.85	3.53	3.67	2.45	1.84	1.84	9.79	2.77	11.00	2.18	0.55	2.76	4.50
9+12+12+12	2.16	2.16	2.16	1.62	8.11	3.70	9.20	2.39	0.98	2.87	3.39	2.61	2.61	2.61	1.96	9.78	2.69	11.00	2.25	0.56	2.82	4.35
9+12+12+18	2.87	1.91	1.91	1.43	8.12	3.70	9.20	2.30	0.96	2.89	3.53	3.45	2.30	2.30	1.73	9.78	2.77	11.00	2.18	0.55	2.90	4.49
12+12+12+12	2.03	2.03	2.03	2.03	8.12	3.70	9.20	2.38	0.98	2.84	3.41	2.45	2.45	2.45	2.45	9.80	2.69	11.00	2.36	0.55	2.80	4.15

Based on wall mounted combination

YAZE5-36

Unique solutions



PREMIUM MULTI DUO/TRIO/QUATTRO/CINCO

COMPATIBLE WITH

HIGH WALL HJD



FLOOR CEILING SXE



CASSETTE CNE



DUCTED LSP DLF



DUCTED MSP DLS



CAPACITY COMBINATION

Mandatory to connect all IDU

Indoor units combinations	COOLING												HEATING											
	Capacity (kW)						Power input (kW)			SEER	Capacity (kW)						Power input (kW)			SCOP				
	A	B	C	D	E	Totale	Min	Max	Nom.		A	B	C	D	E	Totale	Min	Max	Nom.		Min	Max		
9	2.5	-	-	-	-	2.5	1.50	3.5	0.76	0.40	1.01	3.29	3.4	-	-	-	-	3.4	0.95	5.2	0.69	0.40	0.86	4.96
12	3.5	-	-	-	-	3.5	1.50	4.2	1.03	0.40	1.29	3.40	4.3	-	-	-	-	4.3	1.11	7.5	0.95	0.39	1.21	4.54
18	-	-	-	5.0	-	5.0	2.20	6.0	1.44	0.42	1.63	3.47	-	-	-	6.2	-	6.2	1.50	8.0	1.50	0.46	1.87	4.14
24	7.0	-	-	-	-	7.0	2.50	8.0	2.58	0.41	2.71	2.71	-	-	-	8.0	-	8.0	2.00	9.2	2.42	0.41	2.71	3.31
9+9	2.6	2.6	-	-	-	5.1	2.1	6.6	1.36	0.58	1.95	3.76	3.0	3.0	-	-	-	6.0	2.1	7.6	1.36	0.58	1.95	4.40
9+12	2.6	3.5	-	-	-	6.1	2.2	7.0	2.01	0.54	2.54	3.05	3.1	4.1	-	-	-	7.2	2.2	8.0	2.01	0.54	2.54	3.58
9+18	2.6	-	-	5.1	-	7.7	2.4	7.9	2.58	0.56	3.20	2.97	3.0	-	-	6.0	-	9.0	2.4	8.9	2.58	0.56	3.20	3.48
9+24	2.2	5.9	-	-	-	8.1	2.6	8.8	2.81	0.56	3.32	2.88	2.6	-	-	6.9	-	9.5	2.6	9.8	2.81	0.56	3.32	3.37
12+12	3.6	3.6	-	-	-	7.2	2.3	7.5	2.40	0.54	2.55	2.98	4.2	4.2	-	-	-	8.4	2.3	8.5	2.40	0.54	2.55	3.49
12+18	3.2	-	-	4.8	-	8.0	2.5	8.4	2.76	0.56	3.22	2.89	3.7	-	-	5.6	-	9.3	2.5	9.4	2.76	0.56	3.22	3.38
12+24	2.7	-	-	5.5	-	8.2	2.6	9.2	2.78	0.56	3.18	2.94	3.2	-	-	6.4	-	9.6	2.6	10.2	2.78	0.56	3.18	3.45
18+18	4.5	-	-	4.5	-	9.0	2.6	11.0	3.00	0.59	3.16	3.00	-	-	-	5.3	5.3	10.5	2.6	11.5	2.94	0.59	3.16	3.58
18+24	4.0	-	-	5.3	-	9.3	2.8	11.0	3.17	0.55	3.20	2.92	-	-	-	4.6	6.1	10.7	2.8	11.0	3.02	0.55	3.20	3.53
24+24	4.8	-	-	4.8	-	9.5	3.0	11.0	3.33	0.55	3.40	2.85	-	-	-	5.4	5.4	10.8	3.0	12.0	3.09	0.55	3.40	3.49
9+9+9	2.5	2.5	2.5	-	-	7.5	2.7	8.9	2.25	0.69	3.01	3.18	3.3	3.3	3.3	-	-	10.0	2.7	11.0	2.25	0.69	3.01	4.10
9+9+12	2.4	2.4	3.1	-	-	7.8	2.8	9.1	2.41	0.69	2.97	3.25	3.0	3.0	4.1	-	-	10.1	2.8	11.1	2.42	0.69	2.97	4.18
9+9+18	2.1	2.1	-	4.3	-	8.5	3.0	9.5	2.51	0.70	2.92	3.38	2.6	2.6	-	5.2	-	10.4	3.0	11.4	2.39	0.70	2.92	4.35
9+9+24	2.0	2.0	-	5.2	-	9.2	3.2	9.9	2.71	0.68	3.05	3.38	2.2	2.2	-	5.9	-	10.4	3.2	11.6	2.39	0.68	3.05	4.35
9+12+12	2.2	3.0	3.0	-	-	8.2	2.9	9.3	2.46	0.69	2.92	3.31	2.8	3.7	3.7	-	-	10.3	2.9	11.3	2.41	0.69	2.92	4.27
9+12+18	2.0	2.7	-	4.1	-	8.8	3.1	9.7	2.61	0.70	2.89	3.38	2.4	3.2	-	4.8	-	10.4	3.1	11.5	2.39	0.70	2.89	4.35
9+12+24	1.9	2.5	-	5.1	-	9.5	3.3	10.1	2.81	0.68	3.02	3.38	2.1	2.8	-	5.5	-	10.4	3.3	11.8	2.39	0.68	3.02	4.35
9+18+18	1.9	-	-	3.8	3.8	9.5	3.3	10.1	2.81	0.66	3.02	3.38	2.1	-	-	4.2	4.2	10.4	3.3	11.8	2.39	0.66	3.02	4.35
9+18+24	1.7	-	-	3.4	4.5	9.5	3.5	10.5	2.81	0.66	3.05	3.38	1.8	-	-	3.7	4.9	10.4	3.5	12.0	2.39	0.66	3.05	4.35
12+12+12	2.8	2.8	2.8	-	-	8.5	3.0	9.5	2.51	0.72	2.91	3.38	3.5	3.5	3.5	-	-	10.4	3.0	11.4	2.39	0.72	2.91	4.35
12+12+18	2.6	2.6	-	3.9	-	9.2	3.2	9.9	2.71	0.70	3.00	3.38	3.0	3.0	-	4.6	-	10.7	3.2	11.6	2.45	0.70	3.00	4.35
12+12+24	2.4	2.4	-	4.8	-	9.5	3.4	10.3	2.81	0.68	3.05	3.38	2.7	2.7	-	5.5	-	10.9	3.4	11.9	2.51	0.68	3.05	4.35
12+18+18	2.4	-	-	3.6	3.6	9.5	3.4	10.3	2.81	0.68	3.02	3.38	2.7	-	-	4.1	4.1	10.9	3.4	11.9	2.51	0.68	3.02	4.35
9+9+9+9	2.2	2.2	2.2	2.2	-	8.8	3.4	9.8	2.33	0.81	2.67	3.77	2.5	2.5	2.5	2.5	-	10.0	3.4	10.0	2.08	0.81	2.67	4.80
9+9+9+12	2.1	2.1	2.1	2.8	-	9.1	3.6	10.1	2.22	0.81	2.65	3.83	2.4	2.4	2.4	3.2	-	10.3	3.6	10.4	2.15	0.81	2.65	4.00
9+9+9+18	1.9	1.9	1.9	3.9	-	9.7	3.9	10.7	2.30	0.79	2.71	3.94	2.2	2.2	2.2	-	4.3	10.8	3.9	11.1	2.36	0.79	2.71	4.00
9+9+9+24	1.8	1.8	1.8	4.7	-	10.0	4.2	11.0	2.43	0.77	2.89	4.00	1.9	1.9	1.9	-	5.2	11.0	4.2	11.5	2.35	0.77	2.89	3.80
9+9+12+12	2.0	2.0	2.7	2.7	-	9.4	3.7	10.4	2.23	0.81	2.71	3.89	2.3	2.3	3.0	3.0	-	10.5	3.7	10.8	2.55	0.81	2.71	4.00
9+9+12+18	1.9	1.9	2.5	3.8	-	10.0	4.0	11.0	2.42	0.79	2.75	4.00	2.1	2.1	2.8	-	4.1	11.0	4.0	11.5	2.33	0.79	2.75	4.00
9+9+18+18	1.7	1.7	-	3.3	3.3	10.0	4.3	11.0	2.41	0.77	2.89	4.00	1.8	1.8	-	3.7	3.7	11.0	4.3	11.5	2.25	0.77	2.89	3.60
9+12+12+12	1.9	2.6	2.6	2.6	-	9.7	3.9	10.7	2.30	0.81	2.61	3.94	2.2	2.9	2.9	2.9	-	10.8	3.9	11.1	2.52	0.81	2.61	4.00
9+12+12+18	1.8	2.4	2.4	3.5	-	10.0	4.2	11.0	2.43	0.79	2.89	4.00	1.9	2.6	2.6	3.9	-	11.0	4.2	11.5	2.29	0.79	2.89	3.80
12+12+12+12	2.5	2.5	2.5	2.5	-	10.0	4.0	11.0	2.50	0.81	2.92	4.00	2.8	2.8	2.8	2.8	-	11.0	4.0	11.5	2.50	0.81	2.92	4.00
9+9+9+9+9	2.0	2.0	2.0	2.0	2.0	10.0	4.3	11.0	2.94	0.78	3.50	3.70	2.4	2.4	2.4	2.4	2.4	12.0	4.3	12.5	2.94	0.78	3.50	4.50
9+9+9+9+12	1.9	1.9	1.9	1.9	2.6	10.3	4.4	11.0	2.94	0.78	3.50	3.60	2.3	2.3	2.3	2.3	3.0	12.0	4.4	12.5	2.94	0.78	3.50	4.30
9+9+9+9+18	1.8	1.8	1.8	1.8	3.5	10.5	4.6	11.0	2.92	0.79	3.49	3.40	2.0	2.0	2.0	2.0	4.0	12.0	4.6	12.5	2.92	0.79	3.49	4.20
9+9+9+12+12	1.9	1.9	1.9	2.5	2.5	10.5	4.50	11.0	2.94	0.78	3.50	3.50	2.1	2.1	2.1	2.1	2.8	12.0	4.50	12.5	2.94	0.78	3.50	4.30

Based on wall mounted combination