



YX1F

WCF WINDOW

- > Window line available in capacities from 2.5 to 3.5 kW.
- > Cooling operation mode.
- > Side air supply.



R410A FLUID



REMOVABLE WASHABLE PANEL



MOTORIZED 4D AIRFLOW



SLEEP MODE



TIMER



AUTO RESTART

PRODUCT ADVANTAGES

- > Two ways to control the unit by touch panel (built in) or by wireless remote control.
- > Air control in 4 dimensional, motorize right to left and manual up to down.
- > Clock and temperature digital display.

AIRWELL SOLUTIONS



WCF TECHNICAL DATA

	Indoor Units		WCF 009	WCF 012
COOLING	Capacity	kW	2.5	3.5
	Input power	kW	0.91	1.27
	EER/Energy Label		2.75/C	2.76/C
	Outdoor temperature operating limits	°C	18°/43° Dry bulb	
INDOOR UNIT	Sound pressure level to 1 m (LS/MS/HS)	dB(A)	45/47/49	49/51/53
	Airflow (MS)	m³/h	360	480
	Compressor type		Rotary	Rotary
	Dimensions (WxDxH)	mm	450x580x350	560x618x375
	Weight	kg	36	48
	Part number		7WT012062	7WT012063
POWER SUPPLY 1~230V - 50 Hz	Power supply side		Indoor	Indoor
	Power cable section	mm²	3x1.5	3x1.5
	Fuse rating am	A	10	10