



WCF WINDOW

- Window line available in capacities from 2.5 and 3.5 kW.
- Cooling operation mode.
- Side air supply.



YX1F

PRODUCT ADVANTAGES

- Option to control the unit by touch panel (built in) or by wireless remote control.
- Complete accessories for any type of installation are included.
- Special sensor for overflow protection.



R410A FLUID



REMOVABLE WASHABLE PANEL



MOTORIZED 4D AIRFLOW



SLEEP MODE



TIMER

RESTART
AUTO RESTART (MEMORY)

WCF TECHNICAL DATA

Indoor units		WCF 009	WCF 012
COOLING			
Capacity	kW	2.5	3.5
Input power	kW	0.91	1.27
EER/Energy Label		2.75/C	2.76/C
Outdoor temperature operating limits	°C	18°/43° Dry bulb	
INDOOR UNIT			
Sound pressure level to 1 m (LS/MS/HS)	dB(A)	45/47/49	49/51/53
Airflow (MS)	m³/h	360	480
Compressor type		Rotary	Rotary
Dimensions (WxHxD)	mm	450x350x580	560x375x618
Weight	kg	36	48
Part number		7WT012062	7WT012063
POWER SUPPLY 1~230V - 50 HZ			
Power supply side		Indoor	Indoor
Power cable section	mm²	3x1.5	3x1.5
Fuse rating am	A	10	10

AIRWELL SOLUTIONS

