



NFFL

CONSOLES WITH CASING

6 Heat Pump models
From 2,5 to 8 kW



PRODUCT ADVANTAGES

- Sober and streamlined design.
- Reduced footprint.
- Simplified installation and maintenance.
- Low noise levels.
- Remote control can be integrated.

			ST NFFL 7 R	ST NFFL 9 R	ST NFFL 12 R	ST NFFL 16 R	ST NFFL 18 R	ST NFFL 24 R
Cooling	Capacity	kW	2,2	2,8	3,6	4,5	5,6	7,1
	Input power	kW	0,056	0,056	0,085	0,126	0,126	0,16
Heating	Capacity	kW	2,5	3,2	4,2	5,0	6,3	8
	Input power	kW	0,04	0,04	0,07	0,09	0,09	0,12
Indoor unit	Sound pressure level to 1 m ¹	dB(A)	28/30/33	28/30/33	29/35/39	31/35/38	31/36/39	35/38/41
	Air flow ¹	m ³ /h	300/360/420	300/360/420	360/420/540	480/540/720	660/780/900	720/840/1020
	Height	mm	615	615	615	615	615	615
	Width	mm	1065	1065	1065	1380	1380	1380
	Depth	mm	230	230	230	230	230	230
	Weight	kg	29	29	29	29	39	39
Part number			7SP01R123	7SP01R124	7SP01R125	7SP01R128	7SP01R126	7SP01R127
Pipe line	Suction pipe diameter	inches	1/2"	1/2"	1/2"	1/2"	1/2"	5/8"
	Liquid pipe diameter	inches	1/4"	1/4"	1/4"	1/4"	1/4"	3/8"

¹ Data are relative to Low Speed, Medium Speed and High Speed.

Accessories	Size	ST NFFL 7 R	ST NFFL 9 R	ST NFFL 12 R	ST NFFL 16 R	ST NFFL 18 R	ST NFFL 24 R
Wired remote control NRCT-FL	Part number	7ACELR001	7ACELR001	7ACELR001	7ACELR001	7ACELR001	7ACELR001
Infrared remote control AWAC-RCIRC-FL	Part number	7ACELR329	7ACELR329	7ACELR329	7ACELR329	7ACELR329	7ACELR329
Simplified remote control NRCB-FL	Part number	7ACELR315	7ACELR315	7ACELR315	7ACELR315	7ACELR315	7ACELR315