



NFFL

CONSOLES WITH CASING

5 Heat Pump models
From 2,5 to 8 kW

INDOOR UNIT **NFFL 7-9-12-18-24**



PRODUCT ADVANTAGES

- Sober and streamlined design.
- Reduced footprint.
- Simplified installation and maintenance.
- Low noise levels.
- Remote control can be integrated.

			ST NFFL 7	ST NFFL 9	ST NFFL 12	ST NFFL 18	ST NFFL 24
Cooling	Capacity	kW	2,2	2,8	3,6	5,6	7,1
	Input power	kW	0,056	0,056	0,085	0,126	0,16
Heating	Capacity	kW	2,5	3,2	4,2	6,3	8
	Input power	kW	0,04	0,04	0,07	0,09	0,12
Indoor unit	Sound pressure level to 1 m ¹	dB(A)	300/360/420	300/360/421	360/420/540	660/780/900	720/840/1020
	Air flow ¹	m ³ /h	28/30/33	28/30/33	29/35/39	31/36/39	35/38/41
	Height	mm	615	615	615	615	615
	Width	mm	1065	1065	1065	1380	1380
	Depth	mm	230	230	230	230	230
	Weight	kg	29	29	29	39	39
Part number			7SP02R123	7SP02R124	7SP02R125	7SP02R126	7SP02R127
Pipe line	Suction pipe diameter	inches	1/2"	1/2"	1/2"	1/2"	5/8"
	Liquid pipe diameter	inches	1/4"	1/4"	1/4"	1/4"	3/8"

¹ Data are relative to Low Speed, Medium Speed and High Speed.

Accessories	Size	ST NFFL 7	ST NFFL 9	ST NFFL 12	ST NFFL 18	ST NFFL 24
Wired remote control NRCT-FL	Part number	7ACELR001	7ACELR001	7ACELR001	7ACELR001	7ACELR001
Infrared remote control RCIRC-FL	Part number	7ACELR310	7ACELR310	7ACELR310	7ACELR310	7ACELR310
Simplified remote control NRCB-FL	Part number	7ACELR315	7ACELR315	7ACELR315	7ACELR315	7ACELR315