



## NK1FL

### 1 WAY CASSETTES

5 Heat Pump models  
From 3,2 to 8 kW



### PRODUCT ADVANTAGES

- Heights : 200 mm.
- Automatic air diffusion.
- 1 air outlet.
- Low noise levels.
- Built-in high drain pump.
- Simplified installation and maintenance.
- Fresh air intake.

			ST NK1FL 9R	ST NK1FL 12R	ST NK1FL 16R	ST NK1FL 18R	ST NK1FL 24R
<b>Cooling</b>	Capacity	kW	2,8	3,6	4,5	5,6	7,3
	Input power	kW	0,11	0,11	0,12	0,115	0,12
<b>Heating</b>	Capacity	kW	3,2	4,2	5,0	6,3	8
	Input power	kW	0,08	0,08	0,08	0,085	0,090
<b>Indoor unit</b>	Sound pressure level to 1 m <sup>1</sup>	dB(A)	33/34/36	33/34/36	34/35/36	34/36/38	36/40/45
	Air flow <sup>1</sup>	m <sup>3</sup> /h	540/600/720	540/600/720	600/660/720	600/690/790	780/900/1080
	Height	mm	200<15>*	200<15>*	200<15>*	200<15>*	200<15>*
	Width	mm	1000<1230>*	1000<1230>*	1000<1230>*	1000<1230>*	1200<1430>*
	Depth	mm	710<800>*	710<800>*	710<800>*	710<800>*	710<800>*
	Weight	kg	21<5,5>*	21<5,5>*	21<5,5>*	21<5,5>*	21<5,5>*
	<b>Part number</b>		<b>7SP04R001</b>	<b>7SP04R002</b>	<b>7SP04R003</b>	<b>7SP04R004</b>	<b>7SP04R005</b>
<b>Pipe line</b>	Suction pipe diameter	inches	1/2"	1/2"	1/2"	1/2"	1/2"
	Liquid pipe diameter	inches	1/4"	1/4"	1/4"	1/4"	1/4"

<sup>1</sup> Data are relative to Low Speed, Medium Speed and High Speed.

\* The values of the external dimensions and the weight in <> are the values of the optional ceiling panel.

Accessories	Size	ST NK1FL 9R	ST NK1FL 12R	ST NK1FL 16R	ST NK1FL 18R	ST NK1FL 24R
Front panel GR ST-KSFL 9-18	Part number	7ACVFR167	7ACVFR167	7ACVFR167	7ACVFR167	-
Front panel GR ST-KSFL 24	Part number	-	-	-	-	7ACVFR168
Wired remote control NRCT-FL	Part number	7ACELR001	7ACELR001	7ACELR001	7ACELR001	7ACELR001
Infrared remote control RCIRKS-FL	Part number	7ACELR309	7ACELR309	7ACELR309	7ACELR309	7ACELR309
Simplified remote control NRCB-FL	Part number	7ACELR315	7ACELR315	7ACELR315	7ACELR315	7ACELR315