



## XAV

### HIGH WALL

3 Heat Pump models  
From 2,5 kW to 4,2 kW



INDOOR UNIT XAV007-009-012

### PRODUCT ADVANTAGES

- Closed discharge port.
- Lighter and smaller units make the installation easy.
- Quiet operation.
- Smooth and hardwaring design.
- Washable front panel.
- Piping outlet in three directions.
- Anti-mould filters are standard.
- Air distribution is automatically altered depending on the operational mode of the unit.

			AWSI-XAV007-N11	AWSI-XAV009-N11	AWSI-XAV012-N11
<b>Cooling</b>	Capacity	kW	2.2	2.8	3.6
	Input power	kW	0.019	0.019	0.023
<b>Heating</b>	Capacity	kW	2.5	3.2	4.2
	Input power	kW	0.020	0.020	0.023
<b>Indoor unit</b>	Sound pressure level to 1 m <sup>1</sup>	dB(A)	35/32/28	35/32/28	37/33/29
	Air flow <sup>1</sup>	m <sup>3</sup> /h	540/450/360	540/450/360	600/510/390
	Height	mm	285	285	285
	Width	mm	825	825	825
	Depth	mm	217	217	217
	Weight	kg	10	10	10
	<b>Part number</b>			<b>7SP02R376</b>	<b>7SP02R377</b>
<b>Price</b>	€				
<b>Pipe line</b>	Suction pipe diameter	inches	1/2"	1/2"	1/2"
	Liquid pipe diameter	inches	1/4"	1/4"	1/4"

<sup>1</sup> Data are relative to Low Speed, Medium Speed and High Speed.

Accessories	Size	AWSI-XAV007-N11	AWSI-XAV009-N11	AWSI-XAV012-N11
Wired Remote control NRCT-FLR	Part number	7ACELR001	7ACELR001	7ACELR001
	Price €			
Infrared Remote control RCIRW-R	Part number	7ACELR312	7ACELR312	7ACELR312
	Price €			
Simplified Remote control NRCB-FLR	Part number	7ACELR315	7ACELR315	7ACELR315
	Price €			