



## DAV

### DUCTED UNITS

5 Heat Pump models  
From 2,5 kW to 6,3 kW

INDOOR UNIT **DAV 007-009-012-016-018**



### PRODUCT ADVANTAGES

- Ultra-slim profile: 200 mm for all models.
- DC fan motor greatly reduces power consumption.
- Ideal for hotel application with very narrow false ceilings.
- Anti-mould washable filters included.
- Easy maintenance and service by external electrical box.
- 40 Pa static pressure enables ductwork to be fitted.
- Includes drain pump.

			<b>AWSI-DAV007-N11</b>	<b>AWSI-DAV009-N11</b>	<b>AWSI-DAV012-N11</b>	<b>AWSI-DAV016-N11</b>	<b>AWSI-DAV018-N11</b>
<b>Cooling</b>	Capacity	kW	2.2	2.8	3.6	4.7	5.6
	Input power	kW	0.025	0.025	0.027	0.031	0.038
<b>Heating</b>	Capacity	kW	2.5	3.2	4.0	5.0	6.3
	Input power	kW	0.015	0.015	0.018	0.021	0.029
<b>Indoor unit</b>	Sound pressure level to 1 m <sup>1</sup>	dB(A)	25/27/28	27/29/30	28/30/32	30/32/34	31/33/35
	Sound power level <sup>1</sup>	dB(A)	40/42/43	42/44/45	43/45/47	45/47/49	48/50/52
	Airflow <sup>1</sup>	m <sup>3</sup> /h	360/420/480	390/450/510	420/480/540	480/570/630	600/690/750
	Height	mm	200	200	200	200	200
	Width	mm	750	750	750	750	750
	Depth	mm	640	640	640	640	640
	Weight	kg	19	19	19	19	19
	<b>Part number</b>		<b>7SP03R089</b>	<b>7SP03R090</b>	<b>7SP03R091</b>	<b>7SP03R092</b>	<b>7SP03R093</b>
	<b>Price</b>	€					
<b>Pipe line</b>	Suction pipe diameter	inches	1/2"	1/2"	1/2"	1/2"	1/2"
	Liquid pipe diameter	inches	1/4"	1/4"	1/4"	1/4"	1/4"

<sup>1</sup> Data are relative to Low Speed, Medium Speed and High Speed.

<b>Accessories</b>	Size	<b>AWSI-DAV007-N11</b>	<b>AWSI-DAV009-N11</b>	<b>AWSI-DAV012-N11</b>	<b>AWSI-DAV016-N11</b>	<b>AWSI-DAV018-N11</b>
Wired Remote control NRCT-FLR	Part number	7ACELR001	7ACELR001	7ACELR001	7ACELR001	7ACELR001
	Price €					
Infrared Remote control AWAC-RCIRC-FL	Part number	7ACELR329	7ACELR329	7ACELR329	7ACELR329	7ACELR329
	Price €					