

CK DC INVERTER

		CK 9 DCI	CK 12 DCI	CK 18 DCI	CK 21 DCI	CK 24 DCI	
		CK 9 DCI	CK 12 DCI	CK 18 DCI	CK 21 DCI	CK 24 DCI	
		GC 9 DCI	GC 12 DCI	AWAU-YBD018-H11	AWAU-YBD022-H11	AWAU-YBD024-H11	
	Indoor Units						
	Outdoor Units						
Cooling	Capacity	kW	2,5 (1,5-3,6)	3,5 (1,7-4,3)	5 (1,5-5,8)	6 (1,8-6,6)	
	Input power	kW	0,59	0,96	1,51	1,9	
	EER/Energy Label		4,24 / A	3,63 / A	3,31 / A	3,15 / B	
	Outdoor temperature operating limits	°C			-10/ 46° Dry bulb		
Heating	Capacity	kW	3,2 (1,5-4,8)	4,2 (1,6-5,5)	5,6 (1,3-6,8)	6,6 (1,6-8,0)	
	Input power	kW	0,8	1,16	1,53	1,94	
	COP/Energy Label		4 / A	3,64 / A	3,66 / A	3,4 / B	
	Outdoor temperature operating limits	°C			-15/ 24° Dry bulb		
Indoor unit	Sound pressure level to 1 m	dB(A)	28/30/32	28/31/34	34/37/42	34/36/38	
	Sound power level	dB(A)	49	51	55	58	
	Airflow	m3/h	320/370/420	320/390/470	500/560/620	540/600/660	
	Dehumidification	l/h	0,7	1,5	2	2,3	
	Dimensions (WxDxH)	mm	575x575x219	575x575x219	575x575x270	575x575x270	
	Frame for grid ceiling (WxDxH)	mm	625x625x40	625x625x40	625x625x40	625x625x40	
	Frame for hard ceiling (WxDxH)	mm	725x725x40	725x725x40	725x725x40	725x725x40	
	Weight	kg	12,9	12,9	15,2	15,2	
	Part number		7SP022750	7SP022751	7SP022752	7SP022753	7SP022754
	Part number Frame for grid ceiling		7ACVF0478	7ACVF0478	7ACVF0478	7ACVF0478	7ACVF0478
Part number Frame for hard ceiling		7ACVF0479	7ACVF0479	7ACVF0479	7ACVF0479	7ACVF0479	
Price	€						
Outdoor unit	Sound pressure level to 1 m	dB(A)	51	52	53	56	
	Sound power level	dB(A)	61	62	63	66	
	Airflow	m3/h	1780	1780	2160	2860	
	Compressor type		Rotary DC Inverter	Rotary DC Inverter	Rotary DC Inverter	Twin Rotary DC Invert	Twin Rotary DC Inverter
	Dimensions (WxDxH)	mm	795x290x610	795x290x610	795x290x610	846x302x690	950x412x835
Weight	kg	38	38,5	38	45	64,5	
P. supply	Part number	7SP061420	7SP061421	7SP061738	7SP061763	7SP061762	
1~230V - 50 Hz	Price	€					
1~230V - 50 Hz	Full set Price	€					
Power supply	Power supply side		Indoor	Indoor	Indoor	Indoor	
	Power cable section	mm2	3x1,5	3x1,5	3x2,5	3x2,5	
	Fuse rating am	A	16	16	20	20	
	Electrical connections	mm2	4x1,5	4x1,5	4x2,5	4x2,5	
Pipe Line	Suction pipe diameter	inches	3/8"	3/8"	1/2"	1/2"	
	Liquid pipe diameter	inches	1/4"	1/4"	1/4"	1/4"	
	Max lenght	m	20	20	20	20	
	Max height	m	10	10	10	10	