

# Floor Standing **RSF**

## Product benefits

- Auto mode
- Cooling
- Heating
- Dehumidification
- Sleep mode
- ON/OFF Timer (Active clock)
- Clock display
- Vertical auto swing(any position stop)
- Horizontal auto swing
- Intelligent Deicing
- Memory from power failure
- Cold air prevention in heating
- Self diagnosis (Error indications)
- LED Display
- Electrical heater 2.5 kW



OU VFF 045 RC



RSF 045 RC

## 1 Heat Pump model R410A: 13 600 W



### RSF SERIES

Indoor units

Outdoor units

### RSF 45 RC

ELSI-RSF045-N11

ELAU-VFF045-H13

Capacity	kW	12.4
Input power	kW	4.94
EER/Energy Label		2.51
Outdoor temperature operating limits	°C	18/43°C Dry Bulb

Capacity	kW	13.6
Dehumidification	l/h	6
Input power	kW	4.84
COP/Energy Label		2.81
Outdoor temperature operating limits	°C	-7/24°C Dry Bulb

#### Indoor unit

Sound pressure level to 1 m (LS/MS/HS/SS)	dB(A)	46/48/50/52
Sound power level (LS/MS/HS/SS)	dB(A)	56/58/60/62
Airflow (LS/MS/HS/SS)	m <sup>3</sup> /h	1350/1500/1650/1800
Dimensions (WxDxH)	mm	518x395x1870
Weight	kg	63
• Part number		ESP011007

#### Outdoor unit

Sound pressure level to 1 m	dB(A)	59
Sound power level	dB(A)	69
Airflow	m <sup>3</sup> /h	4000
Compressor type		Scroll
Dimensions (WxDxH)	mm	1032x412x1250
Weight	kg	110
• Part number		ESP061752

#### Linking specifications between indoor and outdoor units

Power supply side		Outdoor
Power cable section	mm <sup>2</sup>	5x2.5
Fuse rating am	A	25
Electrical connections	mm <sup>2</sup>	3x1.0 + 5x1.0 + 4x1.0

#### Pipe line

Suction pipe diameter	inches	3/4"
Liquid pipe diameter	inches	1/2"
Max length	m	10
Max height	m	5