



+ PRODUCTS

- No fluid handling.
- Economic.



RC08C included

FEATURES

TECHNOLOGY:



R410A FLUID

AIR QUALITY / CLEAN:



AIR FILTER



AUTO CLEAN/DRY

USER FUNCTIONS:



I FEEL



NIGHT MODE



RESTART
AUTO RESTART
(MEMORY)



REMOTE CONTROL
LOCK

INSTALLER FUNCTIONS:



SELF DIAGNOSTIC



- Comfort "I Feel": temperature sensor in the remote control RC08C.
- Mobile air conditioning: unit on swivel castors and side handles.
- Control screen on the unit.
- Installation kit for windows and walls as standard.
- Limitation of the amount of condensate (evaporation on the exchanger).

MAF

On/off portable



MAF TECHNICAL DATA

Indoor units		AWPO-MAF009-C11	AWPO-MAF012-C11
Phase		Single phase	Single phase
COOLING			
Rated power (min./max.)	kW	2.64	3.52
Rated power input	kW	1.01	1.35
EER/Energy label		2.60/A	2.61/A
Operating limits	°C	17°/35° Dry bulb	
INDOOR UNIT			
Type		Monobloc	Monobloc
Sound pressure level to 1 m (LS/MS/HS)	dB(A)	49/50/52	46/49/52
Sound power Level	dB(A)	65	65
Airflow (LS/MS/HS)	m³/h	350/375/420	370
Diameter flexible emission duct	mm	150	
Length range of heat emission duct	m	0.50 - 1.5	
Dehumidification	l/h	1.6	1.8
Outline dimensions (WxHxD)	mm	467x765x397	467x765x397
Package dimensions (WxHxD)	mm	515x880x443	517x880x437
Net weight/Gross weight	kg	29/34.1	33.5/37
Part number		7MB021058	7MB021057
POWER SUPPLY			
Phase/Tension/Frequency		1P/230V/50Hz	1P/230V/50Hz
PIPE LINE			
Refrigerant / GWP		R410A/2088	R410A/2088
Charge	kg	0.43	0.54

* Packing 8 pieces minimum