



+ PRODUCTS

- Unique solution.
- R32 refrigerant with low environmental impact.
- No fluid handling.



WFD RC included

FEATURES

TECHNOLOGY:



DC INVERTER



R32 FLUID

USER FUNCTIONS:



NIGHT MODE



AUTO RESTART
(MEMORY)

INSTALLER FUNCTIONS:



SELF DIAGNOSTIC



- DC Inverter compressor technology that guarantees energy savings.
- Ideal solution for modular constructions.
- Control screen on the unit.

WFD

Window

WFD TECHNICAL DATA			
Indoor units		AWWR-WFD009-C11	AWWR-WFD012-C11
Phase		Single phase	Single phase
COOLING			
Rated power (min./max.)	kW	2.75	3.7
Pdesignc	kW	2.75	3.7
Rated power input	kW	0.81	1.09
SEER/Energy label		5.10/A	5.10/A
Operating limits	°C	18°/43° Dry bulb	
INDOOR UNIT			
Sound pressure level to 1 m (LS/MS/HS)	dB(A)	45/47/49	45/47/49
Airflow (LS/MS/HS)	m³/h	310/350/380	400/450/490
Dehumidification	l/h	1.0	1.2
Compressor type		Rotary	Rotary
Outline dimensions (WxHxD)	mm	560x375x710	660x428x700
Package dimensions (WxHxD)	mm	623x425x806	739x515x793
Net weight/Gross weight	kg	34/36.7	46/50
Part number		7WT010008	7WT010009
POWER SUPPLY			
Phase/Tension/Frequency		1P/230V/50Hz	1P/230V/50Hz
Power supply side		Indoor	Indoor
Power cable section	mm²	3x1.0	3x1.5
Fuse rating am (D curve)	A	10	10
PIPE LINE			
Refrigerant / GWP		R32/675	R32/675
Charge	kg	0,51	0,63