

Fixed Speed
Cooling only

MFH

ON/OFF PORTABLE



+ PRODUCTS

- No fluid handling.
- Economic.
- R290 refrigerant with very low environmental impact.



RC08C
(included)

FEATURES

TECHNOLOGY:



AIR QUALITY/CLEAN:



USER FUNCTIONS:



INSTALLER FUNCTIONS:



- Comfort "I Feel": temperature sensor in the remote control RC08C.
- Mobile air conditioning: unit on swivel castors and side handles.
- Control screen on the unit.
- Installation kit for windows and walls as standard.
- Condensates reduction: evaporation on the exchanger.



MFH TECHNICAL DATA

Indoor unit		AW-MFH009-C41	AW-MFH012-C41
Phase		Single phase	Single phase
COOLING			
Rated power	kW	2.93	3.52
Rated power input	kW	0.945	1.357
Current	A	4.5	5.9
EER/Energy label		3.10/A+	2.60/A
Operating limits	°C	17°/35° Dry bulb	
INDOOR UNIT			
Type		Monobloc	Monobloc
Sound pressure level to 1 m (LS/MS/HS)	dB(A)	50/51/52	50/51/52
Sound power Level	dB(A)	56	63
Airflow (LS/MS/HS)	m³/h	355/370/420	355/370/420
Diameter flexible emission duct	mm	150	
Length range of heat emission duct	m	0.50 - 1.5	
Dehumidification	l/h	1.6	1.8
Outline dimensions (WxHxD)	mm	467x765x397	467x765x397
Package dimensions (WxHxD)	mm	515x890x440	515x890x440
Net weight/Gross weight	kg	31.8/35.7	33/36.5
Part number		7MB021060	7MB021061
POWER SUPPLY			
Phase/Tension/Frequency		1P/230V/50Hz	1P/230V/50Hz
PIPE LINE			
Refrigerant/GWP		R290/20	R290/20
Charge	kg	0.21	0.22

* Packing 8 pieces minimum