




DRV
Indoor units

Airwell

CVOA

2-ways cassette



RWV05
included

+ PRODUCT

- Remote control RWV05 included
- Contemporary design
- Integrated condensate pump
- Low noise level



RCV03
(optional)



RWV03
(optional)



RWV07
(optional)

FEATURES

TECHNOLOGY



ELECTRONIC
EXPANSION VALVE

USER FUNCTIONS



I FEEL



PROGRAMMABLE
TIMER



AUTO RESTART
(MEMORY)

INSTALLER FUNCTIONS



INTEGRATED
CONDENSATES
PUMP



DRY CONTACT
ON/OFF

+ «SUSTAINABLE DEVELOPMENT»

- > Energy savings (mode blocking, setpoint limiting).

+ «INSTALLER»

- > Easy integration in false ceilings, thanks to its low thickness.
- > Easy installation, thanks to its integrated condensate pump.

+ «TECHNOLOGY»

- > Optimal regulation, thanks to its electronic expansion valve.

TECHNICAL DATA

INDOOR UNIT		CVOA-025N-01M22	CVOA-035N-01M22	CVOA-050/040-01M22
Part number		7VF040005	7VF040006	7VF040007
Phase		Single phase		

RATED POWER

		9.60	12.30	15.40	19.10
Cooling mode	kBtu/h	9.60	12.30	15.40	19.10
	kW	2.80	3.60	4.50	5.60
Heating mode	kBtu/h	10.90	13.60	17.10	21.50
	kW	3.20	4.00	5.00	6.30

ELECTRICAL PARAMETERS

Phase/Voltage/Frequency		1P/220-240V/50-60Hz		
-------------------------	--	---------------------	--	--

PERFORMANCES

		550/700/840	550/700/840	550/700/840
Airflow (LS/MS/HS)	m ³ /h	550/700/840	550/700/840	550/700/840
Sound pressure (LS/MS/HS)	dB(A)	33/37/42	33/37/42	34/39/44
Sound power level (LS/MS/HS)	dB(A)	46/50/55	46/50/55	47/52/57

INSTALLATION

		817x220x620	817x220x620	817x220x620
External dimensions (WxHxD)	mm	817x220x620	817x220x620	817x220x620
Shipping dimensions (WxHxD)	mm	1015x260x695	1015x260x695	1015x260x695
Net weight/Gross weight	kg	21/23	21/23	21/23
Liquid pipe diameter	inches	1/4"	1/4"	1/4"
Suction pipe diameter	inches	3/8"	1/2"	1/2"

PANEL

Panel part number		7ACV FH005	7ACV FH005	7ACV FH005
External dimensions (WxHxD)	mm	1055x68x680	1055x68x680	1055x68x680
Shipping dimensions (WxHxD)	mm	1110x160x720	1110x160x720	1110x160x720
Net weight/Gross weight	kg	7/8	7/8	7/8