



DRV  
Indoor units

Airwell

# CVPA 1-way cassette



RWV05  
included

## + PRODUCT

- Remote control RWV05 included
- Contemporary design
- Integrated condensate pump
- Low noise level



RCV03  
(optional)



RWV03  
(optional)



RWV07  
(optional)

## FEATURES

### TECHNOLOGY



ELECTRONIC  
EXPANSION VALVE

### USER FUNCTIONS



I FEEL



PROGRAMMABLE  
TIMER



AUTO RESTART  
(MEMORY)

### INSTALLER FUNCTIONS



INTEGRATED  
CONDENSATES  
PUMP



DRY CONTACT  
ON/OFF

### + «SUSTAINABLE DEVELOPMENT»

- > Energy savings (mode blocking, setpoint limiting).

### + «INSTALLER»

- > Easy integration in false ceilings, thanks to its low thickness.
- > Easy installation, thanks to its integrated condensate pump.

### + «TECHNOLOGY»

- > Optimal regulation, thanks to its electronic expansion valve.

## TECHNICAL DATA

INDOOR UNIT		CVPA-025/022N-01M22	CVPA-035N-01M22
Part number		7VF040004	7VF040003
Phase		Single phase	
RATED POWER			
Cooling mode	kBtu/h	7.50	9.60
	<b>kW</b>	<b>2.20</b>	<b>2.80</b>
Heating mode	kBtu/h	8.50	10.90
	<b>kW</b>	<b>2.50</b>	<b>3.20</b>
ELECTRICAL PARAMETERS			
Phase/Voltage/Frequency		1P/220-240V/50-60Hz	
PERFORMANCES			
Airflow (LS/MS/HS)	m <sup>3</sup> /h	450/490/530	490/530/550
Sound pressure (LS/MS/HS)	dB(A)	24/29/32	25/30/34
Sound power level (LS/MS/HS)	dB(A)	38/43/46	39/44/48
INSTALLATION			
External dimensions (WxHxD)	mm	875x185x505	875x185x505
Shipping dimensions (WxHxD)	mm	1028x270x581	1028x270x581
Net weight/Gross weight	kg	15.3/17.9	15.3/17.9
Liquid pipe diameter	inches	1/4"	1/4"
Suction pipe diameter	inches	3/8"	1/2"
PANEL			
Panel part number		7ACVFH004	7ACVFH004
External dimensions (WxHxD)	mm	1050x122x560	1050x122x560
Shipping dimensions (WxHxD)	mm	1133x197x623	1133x197x623
Net weight/Gross weight	kg	5.3/8.3	5.3/8.3