




VRF
Indoor units

Airwell

CVQA Cassette 600x600



RWV05
included

+ PRODUCT

- RWV05 remote control
- New design
- New DC Inverter fan motor
- Integrated condensates pump
- Fresh air inlet
- Dry contact available



RCV03
(optional)



RWV03
(optional)



RWV07
(optional)

FEATURES

TECHNOLOGY



ELECTRONIC
EXPANSION VALVE

AIR QUALITY / CLEAN



FRESH AIR

FUNCTIONS USERS



I FEEL



PROGRAMMABLE
TIMER



AUTO RESTART
(MEMORY)

INSTALLER FUNCTIONS



INTEGRATED
CONDENSATES
PUMP



DRY CONTACT
ON/OFF

THE + « SUSTAINABLE DEVELOPMENT »

- > Energy savings (mode locking, setpoint limits).

THE + « USER »

- > Air renewal by supply of fresh air.
- > Multiple applications can be connected using the dry contact: room card, presence detection.

THE + « INSTALLER »

- > Easy integration into false ceilings thanks to its reduced height.
- > Simple installation thanks to its integrated condensates pump.

THE + « TECHNOLOGY »

- > Optimal regulation thanks to its electronic expansion valve.
- > Individual opening of flaps (1296 possibilities).

TECHNICAL DATA

INDOOR UNIT		CVQA-025/022/015N-01M22			CVQA-050/045/035N-01M22		
Part number		7VF040001			7VF040002		
Phase		Single phase					
RATED POWER							
Cooling mode	kBtu/h	5.10	7.50	9.50	12.30	15.30	19.10
	kW	1.50	2.20	2.80	3.60	4.50	5.60
Heating mode	kBtu/h	5.80	8.50	10.90	13.60	17.10	21.50
	kW	1.70	2.50	3.20	4.00	5.00	6.30
ELECTRICAL PARAMETERS							
Phase/Voltage/Frequency		1P/220-240V/50-60Hz					
PERFORMANCES							
Airflow (LS/MS/HS)	m ³ /h	520/450/400	520/450/400	520/450/400	520/450/400	650/520/450	760/650/520
Sound pressure (LS/MS/HS)	dB(A)	32/30/29	32/30/29	32/30/29	33/30/29	33/30/29	34/32/30
Sound power level (LS/MS/HS)	dB(A)	46/44/43	46/44/43	46/44/43	47/44/43	47/44/43	48/46/44
INSTALLATION							
External dimensions (WxHxD)	mm	570x570x260	570x570x260	570x570x260	570x570x260	570x570x260	570x570x260
Shipping dimensions (WxHxD)	mm	718x680x380	718x680x380	718x680x380	718x680x380	718x680x380	718x680x380
Net weight/Gross weight	kg	16/19	16/19	16/19	19/22	19/22	19/22
Liquid pipe diameter	inches	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Suction pipe diameter	inches	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"
PANEL							
Panel part number		CVQA PANEL	CVQA PANEL	CVQA PANEL	CVQA PANEL	CVQA PANEL	CVQA PANEL
External dimensions (WxHxD)	mm	620/620/60	620/620/60	620/620/60	620/620/60	620/620/60	620/620/60
Shipping dimensions (WxHxD)	mm	660/660/115	660/660/115	660/660/115	660/660/115	660/660/115	660/660/115