




VRF
Indoor units

Airwell

DVLA

Ducted low static pressure



RWV05
included

+ PRODUCT

- RWV05 remote control
- New DC Inverter fan motor
- Integrated condensates pump
- Extra-slim unit
- Fresh air supply
- Adjustable static pressure 0-30 Pa
- Dry contact available



RCV03
(optional)



RWV03
(optional)



RWV07
(optional)

FEATURES

TECHNOLOGY



ELECTRONIC
EXPANSION VALVE



AIRFLOW 4D

AIR QUALITY / CLEAN



FRESH AIR

FUNCTIONS USERS



I FEEL



SUPER QUIET



PROGRAMMABLE
TIMER



AUTO RESTART
(RECOVER)

INSTALLER FUNCTIONS



INTEGRATED
CONDENSATE
PUMP



DRY CONTACT
ON/OFF

THE + « SUSTAINABLE DEVELOPMENT »

- > Energy savings (mode locking, setpoint limits).

THE + « USER »

- > Super quiet 21 dB.
- > Designer solution thanks to its motorised panel.
- > Directable airflow.
- > Air renewal by supply of fresh air.
- > Multiple applications can be connected using the dry contact: room card, presence detection.

THE + « INSTALLER »

- > Simple installation: similar dimensions across the range.
- > Thickness 185 mm.

THE + « TECHNOLOGY »

- > Optimal regulation thanks to its electronic expansion valve.
- > Front panel with digital display.

TECHNICAL DATA

INDOOR UNIT		DVLA-025/022-01M22	DVLA-035-01M22	DVLA-045-01M22	
Part number		7VF030003	7VF030004	7VF030005	
Phase		Single phase			
RATED POWER					
Cooling mode	kBtu/h	7.50	9.50	12.30	15.30
	kW	2.20	2.80	3.60	4.50
Heating mode	kBtu/h	8.50	10.90	13.60	17.10
	kW	2.50	3.20	4.00	5.00
ELECTRICAL PARAMETERS					
Phase/Voltage/Frequency		1P/220-230V/50-60Hz			
PERFORMANCES					
Airflow (LS/MS/HS)	m ³ /h	480/420/360	480/420/360	550/430/370	600/540/460
Sound pressure (LS/MS/HS)	dB(A)	27/23/20	27/23/20	30/27/24	32/29/26
Sound power level (LS/MS/HS)	dB(A)	41/37/34	41/37/34	44/41/38	46/43/40
INSTALLATION					
External dimensions (WxHxD)	mm	850x420x185			
Shipping dimensions (WxHxD)	mm	1045x540x270			
Net weight/Gross weight	kg	17.5/22.5	17.5/22.5	17.5/22.5	18.5/23.5
Liquid pipe diameter	inches	1/4"	1/4"	1/4"	1/4"
Suction pipe diameter	inches	3/8"	3/8"	1/2"	1/2"
External static pressure (min./standard/max.)	Pa	0/15/30	0/15/30	0/15/30	0/15/30
Panel part number		DVLA PANEL	DVLA PANEL	DVLA PANEL	DVLA PANEL
External dimensions (WxHxD)	Outlet	mm			890x190x100
	Inlet	mm			890x290.5x32.4
Shipping dimensions (WxHxD)	mm	938x335x220			
Net weight/Gross weight	kg	4/5	4/5	4/5	4/5