



Fixed speed
Cooling & heating

Airwell

MFR Portable

A



RC08C
included

Confort optimal:
reversible solution

+ PRODUCT

- RC08C remote control included
- Monobloc solution
- No fluid handling

FEATURES

TECHNOLOGY



AIR FILTER



AUTO
CLEAN/DRY

USER FUNCTIONS



I FEEL



NIGHT MODE



24 H
PROGRAMMABLE
TIMER



RESTART
(MEMORY)



REMOTE CONTROL
LOCK

INSTALLER FUNCTIONS



SELF DIAGNOSTIC

THE + «SUSTAINABLE DEVELOPMENT»

- > Environmentally friendly R290 refrigerant.

THE + «USER»

- > Easy to move with its wheels and handles.
- > Easy to read with its digital display.
- > Remotely controllable with RC unit.

THE + «TECHNOLOGY»

- > Sealing kit included.
- > Evacuation of condensates by evaporation.

TECHNICAL DATA

INDOOR UNIT		AW-MFR012-H41
Part number		7MB021062
Phase		Single phase
COOLING		
Rated power	kW	3.52
Rated power input	kW	1.357
Courant	A	5.90
EER/Energy label		2.60/A
Operating limits	°C	17°/35° Dry bulb
HEATING		
Rated power	kW	2.93
Rated power input	kW	1.045
Courant	A	5
COP/Energy label		2.8/A
Operating limits	°C	5°/30° Dry bulb
INDOOR UNIT		
Type		Monobloc
Sound pressure level at 1 m (LS/MS/HS)	dB(A)	54/54/55
Sound level	dB(A)	63
Airflow (LS/MS/HS)	m ³ /h	355/370/420
Diameter flexible emission duct	mm	150
Length range of heat emission duct	m	0.50-1.50
Dehumidification	l/h	1.80
Outline dimensions (WxHxD)	mm	467x765x397
Package dimensions (WxHxD)	mm	515x890x440
Net weight/Gross weight	kg	33/36.5
POWER SUPPLY		
Phase/Voltage/Frequency		1P/230V/50Hz
PIPE LINE		
Refrigerant/GWP		R290/20
Charge	kg	0.22

*Packing 8 pieces minimum.