



VRF
Indoor units

Airwell

XVVA Console



RCV03
included

+ PRODUCT

- RCV03 remote control included
- DC Inverter centrifugal fan
- Compact unit
- Bidirectional airflow
- Dry contact available



RWV05
(optional)

FEATURES

TECHNOLOGY



ELECTRONIC
EXPANSION VALVE

FUNCTIONS USERS



I FEEL



SUPER
QUIET



24 H
PROGRAMMABLE
TIMER



RESTART
AUTO RESTART
(MEMORY)

INSTALLER FUNCTIONS



DRY CONTACT
ON/OFF

THE + « SUSTAINABLE DEVELOPMENT »

- > Energy savings (mode locking, setpoint limits).

THE + « USER »

- > New simple and elegant design.
- > Super-quiet unit.
- > Upward and downward blowing for greater comfort.
- > Multiple applications can be connected using the dry contact: room card, presence detection.

THE + « INSTALLER »

- > Very compact.
- > Ideal solution for rooms with low ceilings.

THE + « TECHNOLOGY »

- > Optimal regulation thanks to its electronic expansion valve.

TECHNICAL DATA

INDOOR UNIT	XVVA-050/035/025N-01M22			
Part number	7VF070001			
Phase	Single phase			
RATED POWER				
Cooling mode	kBtu/h	9.50	12.30	17.00
	kW	2.80	3.60	5.00
Heating mode	kBtu/h	10.90	13.60	18.50
	kW	3.20	4.00	5.50
ELECTRICAL PARAMETERS				
Phase/Voltage/Frequency	1P/220-230V/50-60Hz			
PERFORMANCES				
Airflow (VLS/LS/MS/HS/VH)	m ³ /h	540/460/390/310/270	580/500/420/350/270	620/540/460/390/270
Sound pressure (VLS/LS/MS/HS/VH)	dB(A)	45/42/38/33/30	47/44/40/36/30	48/45/42/38/30
Sound power level (VLS/LS/MS/HS/VH)	dB(A)	58/55/52/48/45	60/57/54/51/47	61/58/55/42/48
INSTALLATION				
External dimensions (WxHxD)	mm	700/210/600	700/210/600	700/210/600
Shipping dimensions (WxHxD)	mm	783/303/695	783/303/695	783/303/695
Net weight/Gross weight	kg	15.2/18.7	15.2/18.7	15.2/18.7
Liquid pipe diameter	inches	1/4"	1/4"	1/4"
Suction pipe diameter	inches	1/2"	1/2"	1/2"