




VRF  
Indoor units

Airwell

# CVOA

## 2-ways cassette



RWV05  
included

### + PRODUCT

- RWV05 remote control included
- Contemporary design
- Integrated condensate pump
- Low noise level



RCV03  
(optional)



RWV03  
(optional)

### FEATURES

#### TECHNOLOGY



ELECTRONIC  
EXPANSION VALVE

#### USER FUNCTIONS



I FEEL



PROGRAMMABLE  
TIMER



AUTO RESTART  
(MEMORY)

#### INSTALLER FUNCTIONS



INTEGRATED  
CONDENSATES  
PUMP



DRY CONTACT  
ON/OFF

### + "SUSTAINABLE DEVELOPMENT"

- > Energy savings (mode blocking, setpoint limiting).

### + "INSTALLER"

- > Easy integration in false ceilings, thanks to its low thickness.
- > Easy installation, thanks to its integrated condensate pump.

### + "TECHNOLOGY"

- > Optimal regulation, thanks to its electronic expansion valve.

### TECHNICAL DATA

INDOOR UNIT		CVOA-025N-01M22	CVOA-035N-01M22	CVOA-050/040-01M22	
Part number		7VF040005	7VF040006	7VF040007	
Phase		Single phase			
RATED POWER					
Cooling mode	kBtu/h	9.60	12.30	15.40	19.10
	kW	2.80	3.60	4.50	5.60
Heating mode	kBtu/h	10.90	13.60	17.10	21.50
	kW	3.20	4.00	5.00	6.30
ELECTRICAL PARAMETERS					
Phase/Voltage/Frequency		1P/220-240V/50-60Hz			
PERFORMANCES					
Airflow (LS/MS/HS)	m <sup>3</sup> /h	550/700/840			
Sound pressure (LS/MS/HS)	dB(A)	33/37/42		34/39/44	
Sound power level (LS/MS/HS)	dB(A)	46/50/55		47/52/57	
INSTALLATION					
Outline dimensions (WxHxD)	mm	817x220x620			
Package dimensions (WxHxD)	mm	1015x278x695			
Net weight/Gross weight	kg	21/23			
Liquid pipe diameter	inches	1/4"			
Suction pipe diameter	inches	3/8"	1/2"		
PANEL					
Panel part number		7ACVFH005			
Outline dimensions (WxHxD)	mm	1055x68x680			
Package dimensions (WxHxD)	mm	1110x161x720			
Net weight/Gross weight	kg	7/8			