




VRF
Indoor units

Airwell

CVTA 360° cassette



RWV05
included

+ PRODUCT

- RWV05 remote control included
- 360° air blowing
- New DC Inverter fan motor
- Integrated condensates pump
- Extra-slim cassette
- Fresh air inlet
- Dry contact available



RCV03
(optional)



RWV03
(optional)

FEATURES

TECHNOLOGY



ELECTRONIC
EXPANSION VALVE



MULTIFLOW 360°

AIR QUALITY / CLEAN



FRESH AIR

FUNCTIONS USERS



I FEEL



PROGRAMMABLE
TIMER



AUTO RESTART
(MEMORY)

INSTALLER FUNCTIONS



INTEGRATED
CONDENSATES
PUMP



DRY CONTACT
ON/OFF

THE + “SUSTAINABLE DEVELOPMENT”

- > Energy savings (mode locking, setpoint limits).

THE + “USER”

- > Optimal comfort with its 360° blown air output.
- > Air renewal by supply of fresh air.
- > Multiple applications can be connected using the dry contact: room card, presence detector.

THE + “INSTALLER”

- > Simple installation (180 mm high).

THE + “TECHNOLOGY”

- > Optimal regulation thanks to its electronic expansion valve.
- > Individual opening of each flap.

TECHNICAL DATA

INDOOR UNIT		CVTA-025/022N-01M22	CVTA-035N-01M22	CVTA-050/045N-01M22	CVTA-070N-01M22	CVTA-110/090N-01M22	CVTA-160/140N-01M22				
Part number		7VF040008	7VF040009	7VF040010	7VF040011	7VF040012	7VF040013				
Phase		Single phase									
RATED POWER											
Cooling mode	kBtu/h	7.50	9.50	12.30	15.30	19.10	24.20	30.70	38.20	47.70	54.60
	kW	2.20	2.80	3.60	4.50	5.60	7.10	9.00	11.20	14.00	16.00
Heating mode	kBtu/h	8.50	10.90	13.60	17.10	21.50	27.30	34.10	42.60	54.60	61.20
	kW	2.50	3.20	4.00	5.00	6.30	8.00	10.00	12.50	16.00	18.00
ELECTRICAL PARAMETERS											
Phase/Voltage/ Frequency		1P/220-230V/50-60Hz									
PERFORMANCES											
Airflow (LS/MS/HS)	m³/h	620/810/1000				1000/ 1190/ 1380	1670/1860/2050		1720/1910/2100		
Sound pressure (LS/MS/HS)	dB(A)	25/27/30		27/29/ 32	29/30/ 33	31/34/ 35		31/35/37		36/40/44	
INSTALLATION											
Outline dimensions (WxHxD)	mm	840x183x840				840 x204 x840	840x204x840		840x288x840		
Package dimensions (WxHxD)	mm	983x268x983				983x290 x983		983x331x983		983x373x983	
Net weight/Gross weight	kg	25/28				27/30		31/36		33/38	
Liquid pipe diameter	inches	1/4"						3/8"			
Suction pipe diameter	inches	3/8"		1/2"				5/8"			
PANEL											
Panel part number		7ACVH003									
Outline dimensions (WxHxD)	mm	950x50x950									
Package dimensions (WxHxD)	mm	1013x123x1025									
Net weight/Gross weight	kg	6.5/9									