



DC Inverter
Reversible

Airwell

HDMB HARMONIA

Colour range High wall

Complete sets:



RC08C
included



HDMB Harmonia White



HDMB Harmonia Mirror



HDMB Harmonia Grey

Build your device:

1 CHOOSE THE COLOR OF YOUR INDOOR UNIT



HDMB Harmonia White



HDMB Harmonia Grey

2 THEN SELECT THE PANEL COLOUR REFERENCE



Silver Grey



Champagne Beige



Passion Red

+ PRODUCT

- RC19 remote control included
- Design
- Performance
- Air quality (ionizer + filters)
- Quiet
- Compatible with YDZC and ZDAA multisplits

FEATURES

TECHNOLOGY



4D AIRFLOW



GOLDEN FIN TREATMENT

AIR QUALITY/CLEAN



IONIZER



ANTIBACTERIAL FILTER



AUTO CLEAN/DRY

USER FUNCTIONS



Wi-Fi



24 H



I FEEL



NIGHT MODE



SUPER QUIET



REMOTE CONTROL LOCK



REFRIGERANT LEAKAGE DETECTOR



AUTO RESTART (MEMORY)

INSTALLER FUNCTIONS



ERROR CODE VIA INDOOR UNIT



AUTO-DIAGNOSTIC



LEFT/RIGHT CONDENSATE CONNECTION



HEATING ONLY MODE

CERTIFICATION

- AIRWELL participates in the ECP programme for AC1. Check ongoing validity of certificate:

www.eurovent-certification.com



- Certified in Monosplit configuration

+ «SUSTAINABLE DEVELOPMENT»

- > High seasonal performance (SEER/SCOP).
- > Energy label A+++ in cooling mode and A++ in heating mode depending on model, guaranteeing energy savings.
- > Environmentally friendly R32 refrigerant.

+ «USER»

- > Contemporary design to fit any interior.
- > High-performance ionizer and filters for better air quality.
- > Multi-directional air louvers for air distribution throughout the room.
- > Wi-Fi included for remote control of the unit.
- > Low noise level ideal for living rooms (bedroom, office, living room, etc.).

+ «TECHNOLOGY»

- > Room sensor built into the remote control for better comfort ("I Feel" mode).
- > Automatic cleaning of heat exchangers for better hygiene and performance.
- > Golden Fin treatment on the heat exchangers (external and internal) for protection against corrosion and durability over time.



+ «INSTALLER»

- > Installer mode for direct reading of the probes on the indoor unit.
- > Technician mode for setting the operating temperatures.
- > Condensate drain to the right or left for ease of installation in the room.



AirHome connectivity

TECHNICAL DRAWS






DIMENSIONS (mm)

MODEL	W	D	H
025N-035N	802	189	297
050N	965	215	319
070N	1080	226	335

TECHNICAL DATA

INDOOR UNIT - WHITE		HDMB-025N-09M22	HDMB-035N-09M22	HDMB-050N-09M22	HDMB-070N-09M22
Indoor unit part number - White		7SP023235	7SP023236	7SP023237	7SP023238
INDOOR UNIT - GREY		HDMB-025N-09M22-GY	HDMB-035N-09M22-GY	HDMB-050N-09M22-GY	HDMB-070N-09M22-GY
Indoor unit part number - Grey		7SP023244	7SP023245	7SP023246	7SP023247
INDOOR UNIT - MIRROR		HDMB-025N-09M22-MR	HDMB-035N-09M22-MR	HDMB-050N-09M22-MR	HDMB-070N-09M22-MR
Indoor unit part number - Mirror		7SP023240	7SP023241	7SP023242	7SP023243
Phase		Single-phase			
COOLING					
Rated power (min./max.)		kW 2.64 (1.02~3.22)	3.51 (1.37~4.29)	5.27 (3.39~5.90)	7.03 (2.11~8.21)
Pdesignc	kW	2.60	3.50	5.30	7.00
Rated power input	kW	0.61	0.98	1.55	2.51
SEER/Energy label		9.3/A+++	8.5/A+++	7.0/A++	6.5/A++
Operating limits		-15~50° Dry bulb			
HEATING					
Rated power (min./max.)		kW 2.92 (0.82~3.37)	3.81 (1.07~4.38)	5.57 (3.10~5.85)	7.33 (1.55~8.21)
Pdesignh (average climate)	kW	2.40	2.60	4.10	4.90
Pdesignh (warmer climate)	kW	2.70	3.00	4.50	5.30
Rated power input	kW	0.64	0.98	1.50	2.13
SCOP/Energy label (average climate)		4.6/A++	4.6/A++	4.0/A+	4.0/A+
SCOP/Energy label (warmer climate)		6.0/A+++	6.1/A+++	5.1/A+++	5.1/A+++
Operating limits		-15~24° Dry bulb			
Power at -7°C	kW	2.78	3.18	4.73	7.20
Power at -10°C	kW	2.65	3.03	4.52	6.87
Power at -15°C	kW	2.48	2.84	4.23	6.43
INDOOR UNIT					
Sound pressure level at 1 m (VL/LS/MS/HS)	dB(A)	20/24/29/36	21/25/33/39	22/28/33/43	25/30/41/47
Sound level	dB(A)	55	55	58	63
Airflow (LS/MS/HS)	m³/h	303/362/483	395/477/584	420/500/730	640/830/1020
Dehumidification	l/h	0.9	1.2	1.8	2.4
Outline dimensions (WxHxD)	mm	802x297x189	802x297x189	965x319x215	1080x335x226
Package dimensions (WxHxD)	mm	875x380x285	875x380x285	1045x410x305	1155x320x415
Net weight/Gross weight	kg	8.6/11.1	8.6/11.1	10.9/14.2	13.7/17.3
PANEL					
Panel part number - Silver Grey		7ACTL0551	7ACTL0551	7ACTL0552	7ACTL0553
Panel part number - Champagne Beige		7ACTL0543	7ACTL0543	7ACTL0544	7ACTL0545
Panel part number - Passion Red		7ACTL0547	7ACTL0547	7ACTL0548	7ACTL0549
OUTDOOR UNIT		YDAB-025H-09M22	YDAB-035H-09M22	YDAB-050H-09M22	YDAB-070H-09M22
Part number		7SP063155	7SP063156	7SP063157	7SP063158
Sound pressure level at 1 m	dB(A)	49	51	53	55
Sound level	dB(A)	60	62	64	66
Airflow	m³/h	2150	2200	2100	3500
Compressor type		Rotary	Rotary	Rotary	Rotary
Outline dimensions (WxHxD)	mm	765x555x303	765x555x303	805x554x330	890x673x342
Package dimensions (WxHxD)	mm	887x610x337	887x610x337	915x615x370	995x740x398
Net weight/Gross weight	kg	26.4/29.5	26.4/29.5	32.8/36.2	43.9/46.9
POWER SUPPLY					
Phase/Voltage/Frequency		1P/220-240V/50-60Hz			
Power supply side		Outdoor			
Power cable section	mm²	3G1.5			
Fuse rating am	A	16			
Electrical connections in/out	mm²	5G1.5			
PIPE LINE					
Suction pipe diameter	inches	3/8"		1/2"	5/8"
Liquid pipe diameter	inches	1/4"		1/4"	3/8"
Max. length	m	25		30	50
Max. height	m	10		20	25
Refrigerant/GWP		R32/675		R32/675	R32/675
Charge (5 m)	kg	0.62		1.10	1.45
Additional charge	g/m	12		12	24

OPTIONS

ACCESSORY	PART NUMBER	PICTURE	FUNCTION
Wired remote control RCW22	7ACEL1778		<ul style="list-style-type: none"> Weekly timer, mode, fan speed, On/Off timer, "I Feel" function, temperature.
Dry On/Off contact adapter (mandatory with RCW22)	7ACEL1788		<ul style="list-style-type: none"> Air conditioning external control.
Condensate pump FlowwatchDesign (gutter)	7ACTL0518		<ul style="list-style-type: none"> Condensate evacuation from indoor units.

MATCHING

INDOOR UNIT
HIGH WALL



HDMB Colour range

COMPATIBLE WITH OUTDOOR UNIT

MONOSPLIT	MULTISPLIT	
		
YDAB	ZDAA	YDZC