



COMPATIBLE




No outdoor unit





+ PRODUCT

- XDAW RC remote control included
- Monoblock solution
- Reversible product (cooling/ heating)
- No outdoor unit
- · No fluid handling

TECHNICAL DRAWS (mm)







* Warning! To facilitate the condensate drain from the service cap, however, it is advisable to install the unit at a minimum height of 300 mm.

EUROPE PRODUCT LEAFLET I OCTOBER 2023

XDAW

Monoblock console - Built-in Wi-Fi

► New design!







XDAW RC included

O "SUSTAINABLE DEVELOPMENT"

> Environment friendly R32 refrigerant, low energy consumption.

O "USER"

> Ideal for modular constructions.

O "INSTALLER"

- > Ease of installation
- > Plug & Play.

O "TECHNOLOGY"

- > Inverter technology.
- > Monoblock (no outdoor unit).

TECHNICAL DATA

	XDAW-023R-09M25
	7MB070003
	Single-phase
kW	2.35 (1.5~3.0)
kW	0.90
	2.61/A
°C	-10°~43°C Dry bulb
kW	2.36 (1.0~2.8)
kW	0.76
	3.11/A
°C	-15°~24°C Dry bulb
dB(A)	29/46/48
dB(A)	56
m³/h	480
l/h	0.04
mm	965x615x200
mm	1030x765x280
kg	39/41
	1P/220-240V/50Hz
mm²	3x2.5
А	16
	R32/675
	kW °C kW kW °C dB(A) dB(A) m³/h l/h mm kg mm²

GROUPE **AIRWELL**